

SAFETY DATA SHEET according to regulation 1907/2006

silco[®]**Product name: 20.101 UniMix Neutral****Creation date: 17.12.2020, Revision: 07.04.2021, version: 5.0**

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product name

20.101 UniMix Neutral

Product code

20.101

UFI:

TSNS-F1QA-Y00P-ED5Y

<https://my.chemius.net/p/vvpXLv/en/pd/en>

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

No information.

Uses advised against

No information.

1.3 Details of the supplier of the safety data sheet

Supplier

SILCO d.o.o.

Sentrupert 5a

3303 Gomilsko, Slovenia

00386 3 703 3180

n.cvilak@silco.si

1.4 Emergency Telephone Number

Emergency

112

Supplier

00386 3 703 3180

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Flam. Liq. 3; H226 Flammable liquid and vapour.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP]

**Signal word: Warning**

H226 Flammable liquid and vapour.

EUH066 Repeated exposure may cause skin dryness or cracking.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground and bond container and receiving equipment.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P403 + P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with national regulation.

Contains:

n-butyl acetate

xylene

Low boiling point naphtha - unspecified

Low boiling point hydrogen treated naphtha

2.3 Other hazards

No information.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**3.1 Substances**

For mixtures see 3.2.

3.2 Mixtures

NAME	CAS EC INDEX REACH	%	CLASSIFICATION ACCORDING TO REGULATION (EC) NO 1272/2008 (CLP)	SPECIFIC CONC. LIMITS	NOTES FOR SUBSTANCES
n-butyl acetate	123-86-4 204-658-1 607-025-00-1	25-30	Flam. Liq. 3; H226 STOT SE 3; H336 EUH066	/	/
xylene	1330-20-7 215-535-7 601-022-00-9	20-25	Flam. Liq. 3; H226 Acute Tox. 4; H312 Skin Irrit. 2; H315 Acute Tox. 4; H332	/	C
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7	15-20	Flam. Liq. 3; H226	/	/
Low boiling point naphtha - unspecified	64742-95-6 265-199-0 649-356-00-4	5-10	Asp. Tox. 1; H304 Muta. 1B; H340.1B Carc. 1B; H350.1B	/	P
Low boiling point hydrogen treated naphtha	64742-48-9 265-150-3 649-327-00-6	7-10	Asp. Tox. 1; H304 Muta. 1B; H340.1B Carc. 1B; H350.1B	/	P

2-butanone oxime	96-29-7 202-496-6 616-014-00-0	0.1-1	Acute Tox. 4; H312 Skin Sens. 1; H317 Eye Dam. 1; H318 Carc. 2; H351	/	/
butan-2-ol	78-92-2 201-158-5 603-127-00-5	0.1-1	Flam. Liq. 3; H226 Eye Irrit. 2; H319 STOT SE 3; H335 STOT SE 3; H336	/	C

Notes for substances

C	Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
P	The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260- P262-P301 + P310-P331 shall apply. This note applies only to certain complex oil-derived substances in Part 3.

SECTION 4: FIRST AID MEASURES

4.1 First aid measures

General notes

Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency. When in doubt or if feeling unwell seek medical assistance. Show the safety data sheet and label to the physician. No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. When it is suspected, that there may still be harmful vapours/fumes present in the air, respiratory protection (mask; self contained breathing apparatus) must be used. Wash contaminated clothing with water before removing or use gloves.

Following inhalation

Remove patient to fresh air - move out of dangerous area. In case of unconsciousness bring patient into stable side position and seek medical attention. If breathing is irregular or respiratory arrest occurs provide artificial respiration. Keep at rest in a position comfortable for breathing. Immediately consult a doctor.

Following skin contact

Take off all contaminated clothing. Areas of the body that have come into contact with the product must be rinsed with water. Consult a physician.

Following eye contact

Immediately flush eyes with running water, keeping eyelids apart. Seek medical help.

Following ingestion

Do not induce vomiting! Aspiration hazard if swallowed. Can enter lungs and cause damage. If vomiting occurs, the patient should hold the head lower than the hips, because it reduces the possibility of aspiration. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Immediately consult a doctor. Show the physician the safety data sheet or label.

4.2 Most important symptoms and effects, both acute and delayed

Following inhalation

Excessive exposure to spray mist, fog, or vapours may cause respiratory irritation.

Following skin contact

Contact with skin may cause irritation (redness, itching).

Following eye contact

Contact with eyes can cause irritation (redness, tearing, pain).

Following ingestion

May cause nausea/vomiting and diarrhea. May cause abdominal discomfort. Aspiration into the lungs causes coughing, shortness of breath and may lead to chemical pneumonia.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically. After the product has been ingested vomiting can cause aspiration into the lungs. Because of the risk of aspiration, induction of vomiting and gastric lavage should be avoided.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide. Dry chemical powder. Water spray. Alcohol resistant foam.

Unsuitable extinguishing media

Full water jet.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

In case of a fire toxic gases can be generated; do not inhale gases/smoke.

5.3 Advice for firefighters

Protective actions

In case of fire or heating do not breathe fumes/vapours. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

Additional information

No information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Protective equipment

No information.

Precautionary measures

Ensure adequate ventilation.

Emergency procedures

No action shall be taken involving any personal risk or without suitable training. Prevent access to unprotected personnel. Evacuate the danger zone. Do not breathe vapour or mist. Avoid contact with skin, eyes and clothing.

For emergency responders

Use personal protective equipment.

6.2 Environmental precautions

Do not allow product to reach water/drains/sewage systems or permeable soil. In case of release into the environment, inform the relevant authorities.

6.3 Methods and material for containment and cleaning up

For containment

Stem the spill if this does not pose risks.

For cleaning up

Absorb product (with inert material), collect it in special container and dispose it to a licensed hazardous-waste disposal contractor. Prevent release into the sewer, water, basements or confined areas. Ventilate the premises. Clean contaminated area with plenty of water.

OTHER INFORMATION

No information.

6.4 Reference to other sections

See also sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Protective measures

Measures to prevent fire

Ensure adequate ventilation.

Measures to prevent aerosol and dust generation

Use general or local exhaust ventilation to prevent inhaling vapours and aerosols.

Measures to protect the environment

Do not discharge into drains, surface water and soil. After use immediately close container tightly.

Other measures

No information.

Advice on general occupational hygiene

Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Do not breathe vapours/mist. Avoid contact with skin, eyes and clothes. Remove contaminated clothes and wash them before reuse. Wear suitable protective equipment; see Section 8.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep in a cool, dry and well ventilated place. Keep away from food, drink and animal feeding stuffs.

Packaging materials

Store only in original container.

Requirements for storage rooms and vessels

Close opened containers after use. Put the containers upright to prevent from leaking. Do not store in unlabelled containers.

Storage class

No information.

Further information on storage conditions

No information.

7.3 Specific end use(s)

Recommendations

No information.

Industrial sector specific solutions

No information.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Occupational Exposure limit values

NAME	MG/M ³	ML/M ³	SHORT-TERM VALUE MG/M ³	SHORT-TERM VALUE ML/M ³	REMARK	BIOLOGICAL TOLERANCE VALUES
Xylene, o-,m-,p- or mixed isomers (1330-20-7)	220	50	441	100	Sk, BMGV	650 mmol methyl hippuric acid/mol creatinine in urine - Post shift
1-Methoxypropyl acetate (108-65-6)	274	50	548	100	Sk	/
Butan-2-ol (78-92-2)	308	100	462	150	/	/
Butyl acetate (123-86-4)	724	150	966	200	/	/

Information on monitoring procedures

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 482:2012+A1:2015 Workplace exposure. General requirements for the performance of procedures for the measurement of chemical agents.

DNEL/DMEL values

For product

No information.

For components

NAME	TYPE	EXPOSURE ROUTE	EXP. FREQUENCY	REMARK	VALUE
n-butyl acetate	Worker	inhalation	long term systemic effects	/	300 mg/m ³
n-butyl acetate	Worker	inhalation	short term systemic effects	/	600 mg/m ³
n-butyl acetate	Worker	inhalation	long term local effects	/	300 mg/m ³
n-butyl acetate	Worker	inhalation	short term local effects	/	600 mg/m ³
n-butyl acetate	Worker	dermal	long term systemic effects	/	11 mg/kg bw/day
n-butyl acetate	Worker	dermal	short term systemic effects	/	11 mg/kg bw/day
n-butyl acetate	Consumer	inhalation	long term systemic effects	/	35.7 mg/m ³
n-butyl acetate	Consumer	inhalation	short term systemic effects	/	300 mg/m ³
n-butyl acetate	Consumer	inhalation	long term local effects	/	35.7 mg/m ³
n-butyl acetate	Consumer	inhalation	short term local effects	/	300 mg/m ³
n-butyl acetate	Consumer	dermal	long term systemic effects	/	6 mg/kg bw/day
n-butyl acetate	Consumer	dermal	short term systemic effects	/	6 mg/kg bw/day
n-butyl acetate	Consumer	oral	long term systemic effects	/	2 mg/kg bw/day

n-butyl acetate	Consumer	oral	short term systemic effects	/	2 mg/kg bw/day
xylene	Worker	inhalation	long term systemic effects	/	221 mg/m ³
xylene	Worker	inhalation	short term systemic effects	/	442 mg/m ³
xylene	Worker	inhalation	long term local effects	/	221 mg/m ³
xylene	Worker	inhalation	short term local effects	/	442 mg/m ³
xylene	Worker	dermal	long term systemic effects	/	212 mg/kg bw/day
xylene	Consumer	inhalation	long term systemic effects	/	65.3 mg/m ³
xylene	Consumer	inhalation	short term systemic effects	/	260 mg/m ³
xylene	Consumer	inhalation	long term local effects	/	65.3 mg/m ³
xylene	Consumer	inhalation	short term local effects	/	260 mg/m ³
xylene	Consumer	dermal	long term systemic effects	/	125 mg/kg bw/day
xylene	Consumer	oral	long term systemic effects	/	12.5 mg/kg bw/day
2-methoxy-1-methylethyl acetate	Worker	inhalation	long term systemic effects	/	275 mg/m ³
2-methoxy-1-methylethyl acetate	Worker	inhalation	short term local effects	/	550 mg/m ³
2-methoxy-1-methylethyl acetate	Worker	dermal	long term systemic effects	/	796 mg/kg bw/day
2-methoxy-1-methylethyl acetate	Consumer	inhalation	long term systemic effects	/	33 mg/m ³
2-methoxy-1-methylethyl acetate	Consumer	inhalation	long term local effects	/	33 mg/m ³
2-methoxy-1-methylethyl acetate	Consumer	dermal	long term systemic effects	/	320 mg/kg bw/day
2-methoxy-1-methylethyl acetate	Consumer	oral	long term systemic effects	/	36 mg/kg bw/day
2-methoxy-1-methylethyl acetate	Consumer	oral	short term systemic effects	/	500 mg/kg bw/day
Low boiling point naphtha - unspecified	Worker	inhalation	short term systemic effects	/	1300 mg/m ³
Low boiling point naphtha - unspecified	Worker	inhalation	long term local effects	/	840 mg/m ³
Low boiling point naphtha - unspecified	Worker	inhalation	short term local effects	/	1100 mg/m ³
Low boiling point naphtha - unspecified	Consumer	inhalation	short term systemic effects	/	1200 mg/m ³
Low boiling point naphtha - unspecified	Consumer	inhalation	long term local effects	/	180 mg/m ³
Low boiling point naphtha - unspecified	Consumer	inhalation	short term local effects	/	640 mg/m ³
butan-2-ol	Worker	inhalation	long term systemic effects	/	600 mg/m ³

butan-2-ol	Worker	dermal	long term systemic effects	/	405 mg/kg bw/day
butan-2-ol	Consumer	inhalation	long term systemic effects	/	213 mg/m ³
butan-2-ol	Consumer	dermal	long term systemic effects	/	203 mg/kg bw/day
butan-2-ol	Consumer	oral	long term systemic effects	/	15 mg/kg bw/day

PNEC values

For product

No information.

For components

NAME	EXPOSURE ROUTE	REMARK	VALUE
n-butyl acetate	fresh water	/	0.18 mg/L
n-butyl acetate	water, intermittent release	/	0.36 mg/L
n-butyl acetate	marine water	/	0.018 mg/L
n-butyl acetate	water treatment plant	/	35.6 mg/L
n-butyl acetate	fresh water sediment	dry weight	0.981 mg/kg
n-butyl acetate	marine water sediment	dry weight	0.098 mg/kg
n-butyl acetate	soil	dry weight	0.09 mg/kg
xylene	fresh water	/	0.327 mg/L
xylene	water, intermittent release	/	0.327 mg/L
xylene	marine water	/	0.327 mg/L
xylene	water treatment plant	/	6.58 mg/L
xylene	fresh water sediment	dry weight	12.46 mg/kg
xylene	marine water sediment	dry weight	12.46 mg/kg
xylene	soil	dry weight	2.31 mg/kg
2-methoxy-1-methylethyl acetate	fresh water	/	0.635 mg/L
2-methoxy-1-methylethyl acetate	water, intermittent release	/	6.35 mg/L
2-methoxy-1-methylethyl acetate	marine water	/	0.064 mg/L
2-methoxy-1-methylethyl acetate	water treatment plant	/	100 mg/L
2-methoxy-1-methylethyl acetate	fresh water sediment	dry weight	3.29 mg/kg
2-methoxy-1-methylethyl acetate	marine water sediment	dry weight	0.329 mg/kg
2-methoxy-1-methylethyl acetate	soil	dry weight	0.29 mg/kg
butan-2-ol	fresh water	/	47.1 mg/L
butan-2-ol	water, intermittent release	/	47.1 mg/L

butan-2-ol	marine water	/	47.1 mg/L
butan-2-ol	water treatment plant	/	761 mg/L
butan-2-ol	fresh water sediment	dry weight	196.19 mg/kg
butan-2-ol	marine water sediment	dry weight	196.19 mg/kg
butan-2-ol	soil	dry weight	11.58 mg/kg
butan-2-ol	secondary poisoning	food	1000 mg/kg

8.2 Exposure controls

Appropriate engineering control

Substance/mixture related measures to prevent exposure during identified uses

Use good personal hygiene practices – wash hands at breaks and when done working with material. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothes. Do not eat, drink or smoke while working. Do not breathe vapours/aerosols.

Structural measures to prevent exposure

No information.

Organisational measures to prevent exposure

Remove all contaminated clothes immediately and wash them before reuse.

Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration. Keep away from food, drink and animal feeding stuffs.

Personal protective equipment

Eye and face protection

Safety glasses with side protection (EN 166).

Hand protection

Protective gloves (EN 374). Observe the manufacturer's instructions regarding the use, storage, maintenance and replacement of gloves. In case of damage or at the first signs of wear and tear, change the gloves immediately. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. The penetration time is determined by the protective glove manufacturer and must be observed.

Appropriate materials

Skin protection

Cotton protective clothing and shoes that cover the entire foot (EN ISO 20345). At high risk of skin exposure chemical suits (EN ISO 6530:2005) and boots may be required (EN ISO 20345:2012).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory protection. Wear suitable protective breathing mask (EN 136) with filter A2-P2 (EN 14387). For dust/gas/ vapor concentrations above the applicable filter limit, in case of oxygen concentrations below 17% or in vague conditions, autonomous self-contained breathing apparatus should be used, according to standard EN 137, EN 138.

Thermal hazards

No information.

Environmental exposure controls

Substance/mixture related measures to prevent exposure

No information.

Instruction measures to prevent exposure

No information.

Organisational measures to prevent exposure

No information.

Technical measures to prevent exposure

Do not allow product to reach drains, sewage systems or ground water.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical state

liquid

Colour

white

Odour

No information.

Important health, safety and environmental information

Odour threshold	No information.
pH	7 at 20 °C, conc. 100 %
Melting point/Freezing point	No information.
Initial boiling point/boiling range	No information.
Flash point	No information.
Evaporation rate	No information.
Flammability (solid, gas)	No information.
Explosion limits (vol%)	No information.
Vapour pressure	No information.
Vapour density	No information.
Density / weight	Density: 1 g/cm ³
Solubility	No information.
Partition coefficient	No information.
Auto-ignition temperature	No information.
Decomposition temperature	No information.
Viscosity	No information.
Explosive properties	No information.
Oxidising properties	No information.

9.2 OTHER INFORMATION

Solids content	0 % 0 vol %
Weight organic solvents	0 g/l

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

No information.

10.2 Chemical stability

Product is stable under normal conditions of use, recommended handling and storage conditions.

10.3 Possibility of hazardous reactions

No information.

10.4 Conditions to avoid

No information.

10.5 Incompatible materials

No information.

10.6 Hazardous decomposition products

Under normal use conditions no hazardous decomposition products are expected. In case of fire/explosion vapours/gases that pose a health hazard are released.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

(a) Acute toxicity

No information.

Additional information

The product is not classified for acute toxicity.

(b) Skin corrosion/irritation

No information.

Additional information

The product is not classified as irritating to skin and eyes.

(c) Serious eye damage/irritation

No information.

(d) Respiratory or skin sensitisation

No information.

Additional information

The product is not classified as sensitising.

(e) (Germ cell) mutagenicity

No information.

(f) Carcinogenicity

No information.

(g) Reproductive toxicity

No information.

Summary of evaluation of the CMR properties

The product is not classified as carcinogenic, mutagenic or toxic for reproduction.

(h) STOT-single exposure

No information.

Additional information

STOT SE (single exposure): Not classified.

(i) STOT-repeated exposure

No information.

Additional information

STOT RE (repeated exposure): Not classified.

(j) Aspiration hazard

No information.

Additional information

May be fatal if swallowed and enters airways. Aspiration hazard: Not classified.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Acute (short-term) toxicity

No information.

Chronic (long-term) toxicity

No information.

12.2 Persistence and degradability

Abiotic degradation, physical- and photo-chemical elimination

No information.

Biodegradation

No information.

12.3 Bioaccumulative potential

Partition coefficient

No information.

Bioconcentration factor (BCF)

No information.

12.4 Mobility in soil

Known or predicted distribution to environmental compartments

No information.

Surface tension

No information.

Adsorption/Desorption

No information.

12.5 Results of PBT and vPvB assessment

No evaluation.

12.6 Other adverse effects

No information.

12.7 Additional information

For product

Product is not classified as dangerous for environment. Do not allow to reach ground water, water courses or sewage system.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product / Packaging disposal

Waste chemical

Do not allow product to reach drains/sewage systems. Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste.

Waste codes / waste designations according to LoW

No information.

Packaging

Deliver completely emptied containers to approved waste disposal authorities. Uncleaned containers are classified as hazardous waste - they should be handled in the same manner as the contents.

Waste codes / waste designations according to LoW

No information.

Waste treatment-relevant information

No information.





Sewage disposal-relevant information

No information.

Other disposal recommendations

No information.

SECTION 14: TRANSPORT INFORMATION

ADR/RID	IMDG	IATA	ADN
14.1 UN number			
UN 1263	UN 1263	UN 1263	UN 1263
14.2 UN proper shipping name			
PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base)	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base)	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base)	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base)
14.3 Transport hazard class(es)			
3	3	3	3
			
14.4 Packing group			
III	III	III	III
14.5 Environmental hazards			
NO	NO	NO	NO
14.6 Special precautions for user			

Limited quantities 5 L Transport category 3 Tunnel restriction code (D/E)	Limited quantities 5 L EmS F-E, <u>S-E</u> Special provisions 163, 367, 650 Packing Instructions P001, IBC03, LP01, R001 Special packing provisions PP1 Tank instructions T2 Tank special provisions TP1, TP29	Limited Quantity Packing Instructions Y344 Limited Quantity Net Qty 10 L Passenger Packing Instruction Packing Instructions 355 Passenger Packing Instruction Net Qty 25 L Special provisions A3, A72, A192	Limited quantities 5 L
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code			
Goods may not be carried in bulk in bulk containers, containers or vehicles.	Goods may not be carried in bulk in bulk containers, containers or vehicles.	Not given/not applicable	Not given/not applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)(including last amendment Commission Regulation (EU) 2015/830)
- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-guideline)
not applicable

Regulation EC 648/2004 on detergents

No information.

Special instructions

Observe the regulations on employment and protection against dangerous substances for young people, pregnant women and nursing mothers.

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION

Indication of changes

No information.

Key literature references and sources for data

No information.

Abbreviations and acronyms

ATE - Acute Toxicity Estimate

ADR - Agreement concerning the International Carriage of Dangerous Goods by Road

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

CEN - European Committee for Standardisation

C&L - Classification and Labelling

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

CAS# - Chemical Abstracts Service number

CMR - Carcinogen, Mutagen, or Reproductive Toxicant

CSA - Chemical Safety Assessment

CSR - Chemical Safety Report
DMEL - Derived Minimal Effect Level
DNEL - Derived No Effect Level
DPD - Dangerous Preparations Directive 1999/45/EC
DSD - Dangerous Substances Directive 67/548/EEC
DU - Downstream User
EC - European Community
ECHA - European Chemicals Agency
EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS)
EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway)
EEC - European Economic Community
EINECS - European Inventory of Existing Commercial Substances
ELINCS - European List of notified Chemical Substances
EN - European Standard
EQS - Environmental Quality Standard
EU - European Union
Euphrac - European Phrase Catalogue
EWC - European Waste Catalogue (replaced by LoW – see below)
GES - Generic Exposure Scenario
GHS - Globally Harmonized System
IATA - International Air Transport Association
ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG - International Maritime Dangerous Goods
IMSBC - International Maritime Solid Bulk Cargoes
IT - Information Technology
IUCLID - International Uniform Chemical Information Database
IUPAC - International Union for Pure Applied Chemistry
JRC - Joint Research Centre
Kow - octanol-water partition coefficient
LC50 - Lethal Concentration to 50 % of a test population
LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose)
LE - Legal Entity
LoW - List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)
LR - Lead Registrant
M/I - Manufacturer / Importer
MS - Member States
MSDS - Material Safety Data Sheet
OC - Operational Conditions
OECD - Organization for Economic Co-operation and Development
OEL - Occupational Exposure Limit
OJ - Official Journal
OR - Only Representative
OSHA - European Agency for Safety and Health at work
PBT - Persistent, Bioaccumulative and Toxic substance
PEC - Predicted Effect Concentration
PNEC(s) - Predicted No Effect Concentration(s)
PPE - Personal Protection Equipment
(Q)SAR - Qualitative Structure Activity Relationship
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
RIP - REACH Implementation Project
RMM - Risk Management Measure
SCBA - Self-Contained Breathing Apparatus
SDS - Safety data sheet
SIEF - Substance Information Exchange Forum
SME - Small and Medium sized Enterprises
STOT - Specific Target Organ Toxicity
(STOT) RE - Repeated Exposure
(STOT) SE - Single Exposure
SVHC - Substances of Very High Concern
UN - United Nations
vPvB - Very Persistent and Very Bioaccumulative

List of relevant H phrases

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H340 May cause genetic defects.
H350 May cause cancer.
H351 Suspected of causing cancer.