SAFETY DATA SHEET according to regulation 1907/2006

Product name: 20.143 Unimix Red Oxide Reduced Creation date: 22.02.2021, Revision: 07.04.2021, version: 1.0



2021-04-07

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier Product name 20.143 Unimix Red Oxide Reduced Product code 20.143



https://my.chemius.net/p/DGB4kG/er

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses No information. Uses advised against No information.

5DSS-Q1Q0-U00F-6QNP

UFI:

1.3 Details of the supplier of the safety data sheet

Supplier SILCO d.o.o. Sentrupert 5a 3303 Gomilsko, Slovenia 00386 3 703 3180 n.cvilak@silco.si

1.4 Emergency Telephone Number Emergency National Poisons Information Centre: (01) 809 2166 Supplier 00386 3 703 3180

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP) Flam. Liq. 3; H226 Flammable liquid and vapour.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP]



Signal word: Warning

H226 Flammable liquid and vapour.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240 Ground and bond container and receiving equipment.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P403 + P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container in accordance with national regulation.

2.3 Other hazards

No information.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

For mixtures see 3.2.

3.2 Mixtures

| NAME | CAS EC INDEX REACH | % | CLASSIFICATION ACCORDING TO REGULATION (EC) NO 1272/2008 (CLP) | SPECIFIC CONC. LIMITS | NOTES FOR SUBSTANCES |
|--------------------------------|--|--------------|---|--------------------------|-------------------------|
| 1-methoxy-2- propylacetate | 108-65-6 203-603-9 607-195-00-7 | 35- 40 | Flam. Liq. 3; H226 | / | / |
| Xylene (mixture of isomers) | 1330-20-7 215-535-7 601-022-00-9 01- 2119488216- 32 | 0.01- 0.1 | Flam. Liq. 3; H226 Acute Tox. 4; H312 Skin Irrit. 2; H315 Acute Tox. 4; H332 | 1 | 1 |
| ethylbenzene | 100-41-4 202-849-4 601-023-00-4 01- 2119489370- 35 | 0.01- 0.1 | Flam. Liq. 2; H225 Asp. Tox. 1; H304 Acute Tox. 4; H332 STOT RE 2; H373 | / | 1 |

SECTION 4: FIRST AID MEASURES

4.1 First aid measures

General notes

Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency. When in doubt or if feeling unwell seek medical assistance. Show the safety data sheet and label to the physician.

Following inhalation

Remove patient to fresh air - move out of dangerous area. Obtain professional medical help!

Following skin contact

Take off all contaminated clothing. Areas of the body that have come into contact with the product must be rinsed with water. If symptoms develop and persist, seek medical attention.

Following eye contact

Immediately flush eyes with running water, keeping eyelids apart. If irritation persists, seek professional medical attention.

Following ingestion

Do not induce vomiting! Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Consult a physician. Show the physician the safety data sheet or label.

4.2 Most important symptoms and effects, both acute and delayed

Following inhalation

Excessive exposure to spray mist, fog, or vapours may cause respiratory irritation.

Following skin contact

Contact with skin may cause irritation (redness, itching).

Following eye contact

Contact with eyes can cause irritation (redness, tearing, pain).

Following ingestion

May cause nausea/vomiting and diarrhea. May cause abdominal discomfort.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media Carbon dioxide. Dry chemical powder. Water spray. Alcohol resistant foam. Unsuitable extinguishing media

Full water jet.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products In case of a fire toxic gases can be generated; do not inhale gases/smoke.

5.3 Advice for firefighters

Protective actions

In case of fire or heating do not breathe fumes/vapours. No action shall be taken involving any personal risk or without suitable training. Prolonged heating can cause an explosion. Vapours can form explosive mixtures with air. Cool containers at risk with water spray. If possible remove containers from endangered area.

Special protective equipment for fire-fighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

Additional information No information.

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Protective equipment

No information.

Precautionary measures

Ensure adequate ventilation. Keep away from sources of ignition and/or heat; No smoking!

Emergency procedures

No action shall be taken involving any personal risk or without suitable training. Prevent access to unprotected personnel. Evacuate the danger zone. Do not breathe vapour or mist. Avoid contact with skin, eyes and clothing.

For emergency responders

Use personal protective equipment.

6.2 Environmental precautions

Do not allow product to reach water/drains/sewage systems or permeable soil. In case of release into the environment, inform the relevant authorities.

6.3 Methods and material for containment and cleaning up

For containment

Stem the spill if this does not pose risks.

For cleaning up

Absorb product (with inert material), collect it in special container and dispose it to a licensed hazardous-waste disposal contractor. Use only explosion-proof instruments and equipment. Use spark-proof tools. Prevent release into the sewer, water, basements or confined areas. Ventilate the premises. Clean contaminated area with plenty of water.

OTHER INFORMATION No information.

6.4 Reference to other sections

See also sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Protective measures

Measures to prevent fire

Ensure adequate ventilation. Keep away from sources of ignition - no smoking. Use spark-proof tools. Take precautionary measures against static discharges. Vapours are heavier than air and spread along the floor. They form explosive mixtures with air.

Measures to prevent aerosol and dust generation Use general or local exhaust ventilation to prevent inhaling vapours and aerosols.

Measures to protect the environment

Do not discharge into drains, surface water and soil. After use immediately close container tightly.

Other measures No information.

Advice on general occupational hygiene

Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Do not breathe vapours/mist. Avoid contact with skin, eyes and clothes. Remove contaminated clothes and wash them before reuse. Wear suitable protective equipment; see Section 8.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep in a cool, dry and well ventilated place. Protect from open fire, heat and direct sunlight. Keep away from food, drink and animal feeding stuffs. Keep away from oxidising substances. Keep away from sources of ignition - no smoking.

Packaging materials

Store only in original container.

Requirements for storage rooms and vessels

Close opened containers after use. Put the containers upright to prevent from leaking. Do not store in unlabelled containers.

Storage class

No information.

Further information on storage conditions No information.

7.3 Specific end use(s)

Recommendations No information.

Industrial sector specific solutions No information.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Occupational Exposure limit values

No information.

Information on monitoring procedures

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 482:2012+A1:2015 Workplace exposure. General requirements for the performance of procedures for the measurement of chemical agents.

DNEL/DMEL values

For product

No information.

For components

| NAME | ТҮРЕ | EXPOSURE ROUTE | EXP. FREQUENCY | REMARK | VALUE |
|-----------------------------|----------|----------------|-----------------------------|--------|-------------------|
| Xylene (mixture of isomers) | Worker | inhalation | long term systemic effects | / | 221 mg/m³ |
| Xylene (mixture of isomers) | Worker | inhalation | short term systemic effects | / | 442 mg/m³ |
| Xylene (mixture of isomers) | Worker | inhalation | long term local effects | / | 221 mg/m³ |
| Xylene (mixture of isomers) | Worker | inhalation | short term local effects | / | 442 mg/m³ |
| Xylene (mixture of isomers) | Worker | dermal | long term systemic effects | / | 212 mg/kg bw/day |
| Xylene (mixture of isomers) | Consumer | inhalation | long term systemic effects | / | 65.3 mg/m³ |
| Xylene (mixture of isomers) | Consumer | inhalation | short term systemic effects | / | 260 mg/m³ |
| Xylene (mixture of isomers) | Consumer | inhalation | long term local effects | / | 65.3 mg/m³ |
| Xylene (mixture of isomers) | Consumer | inhalation | short term local effects | / | 260 mg/m³ |
| Xylene (mixture of isomers) | Consumer | dermal | long term systemic effects | / | 125 mg/kg bw/day |
| Xylene (mixture of isomers) | Consumer | oral | long term systemic effects | / | 12.5 mg/kg bw/day |

| ethylbenzene | Worker | inhalation | long term systemic effects | / | 77 mg/m³ |
|--------------|----------|------------|----------------------------|---|------------------|
| ethylbenzene | Worker | inhalation | short term local effects | / | 293 mg/m³ |
| ethylbenzene | Worker | dermal | long term systemic effects | / | 180 mg/kg bw/day |
| ethylbenzene | Consumer | inhalation | long term systemic effects | / | 15 mg/m³ |
| ethylbenzene | Consumer | oral | long term systemic effects | / | 1.6 mg/kg bw/day |

PNEC values

For product

No information.

For components

| NAME | EXPOSURE ROUTE | REMARK | VALUE |
|-----------------------------|-----------------------------|------------|-------------|
| Xylene (mixture of isomers) | fresh water | / | 0.327 mg/L |
| Xylene (mixture of isomers) | water, intermittent release | / | 0.327 mg/L |
| Xylene (mixture of isomers) | marine water | / | 0.327 mg/L |
| Xylene (mixture of isomers) | water treatment plant | / | 6.58 mg/L |
| Xylene (mixture of isomers) | fresh water sediment | dry weight | 12.46 mg/kg |
| Xylene (mixture of isomers) | marine water sediment | dry weight | 12.46 mg/kg |
| Xylene (mixture of isomers) | soil | dry weight | 2.31 mg/kg |
| ethylbenzene | fresh water | / | 0.1 mg/L |
| ethylbenzene | water, intermittent release | / | 0.1 mg/L |
| ethylbenzene | marine water | / | 0.01 mg/L |
| ethylbenzene | water treatment plant | / | 9.6 mg/L |
| ethylbenzene | fresh water sediment | dry weight | 13.7 mg/kg |
| ethylbenzene | marine water sediment | dry weight | 1.37 mg/kg |
| ethylbenzene | soil | dry weight | 2.68 mg/kg |
| ethylbenzene | secondary poisoning | food | 0.02 g/kg |

8.2 Exposure controls

Appropriate engineering control

Substance/mixture related measures to prevent exposure during identified uses

Use good personal hygiene practices – wash hands at breaks and when done working with material. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothes. Do not eat, drink or smoke while working. Do not breathe vapours/aerosols.

Structural measures to prevent exposure

No information.

Organisational measures to prevent exposure

Remove all contaminated clothes immediately and wash them before reuse.

Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration. Keep away from food, drink and animal feeding stuffs.

Personal protective equipment

Eye and face protection

Safety glasses with side protection (EN 166).

Hand protection

Protective gloves (EN 374). Observe the manufacturer's instructions regarding the use, storage, maintenance and replacement of gloves. In case of damage or at the first signs of wear and tear, change the gloves immediately. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. The penetration time is determined by the protective glove manufacturer and must be observed.

Appropriate materials

Skin protection

Protective antistatic clothing EN 1149 (1:2006, 2:1998 and 3:2004, 5:2008), protective antistatic shoes (EN 20345:2012). At high risk of skin exposure chemical suits (EN ISO 6530:2005) and boots may be required (EN ISO 20345:2012).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory protection. Wear suitable protective breathing mask (EN 136) with filter A2-P2 (EN 14387).

Thermal hazards No information.

Environmental exposure controls

Substance/mixture related measures to prevent exposure

No information.

Instruction measures to prevent exposure

No information.

Organisational measures to prevent exposure No information.

Technical measures to prevent exposure Do not allow product to reach drains, sewage systems or ground water.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical state

liquid

Соlоиг

гed

Odour

No information.

Important health, safety and environmental information

| Odour threshold | No information. |
|-------------------------------------|-------------------------|
| рН | 7 at 20 °C, conc. 100 % |
| Melting point/Freezing point | No information. |
| Initial boiling point/boiling range | No information. |
| Flash point | No information. |
| Evaporation rate | No information. |
| Flammability (solid, gas) | No information. |
| Explosion limits (vol%) | No information. |

| Vapour pressure | No information. |
|---------------------------|------------------------------|
| Vapour density | No information. |
| Density / weight | Density: 1 g/cm ³ |
| Solubility | No information. |
| Partition coefficient | No information. |
| Auto-ignition temperature | No information. |
| Decomposition temperature | No information. |
| Viscosity | No information. |
| Explosive properties | No information. |
| Oxidising properties | No information. |

9.2 OTHER INFORMATION

| Solids content | 0 % 0 vol % |
|-------------------------|----------------|
| Weight organic solvents | 0 g/l |

SECTION 10: STABILITY AND REACTIVITY 10.1 Reactivity No information. 10.2 Chemical stability Product is stable under normal conditions of use, recommended handling and storage conditions. 10.2 Possibility of hazardous reactions Vapours and air can form flammable or explosive mixtures. 10.4 Conditions to avoid Protect from heat, direct sunlight, open fire, sparks. 10.5 Incompatible materials Oxidants. 10.6 Hazardous decomposition products Under normal use conditions no hazardous decomposition products are expected. In case of fire/explosion vapours/gases that pose a health hazard are released.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

(a) Acute toxicity

For components

| NAME | EXPOSURE ROUTE | TYPE | SPECIES | TIME | VALUE | METHOD | REMARK |
|-----------------------------|----------------------|------------------|---------|------|--------------|--------|--------|
| 1-methoxy-2- propylacetate | oral | LD ₅₀ | rat | / | 8530 mg/kg | / | / |
| 1-methoxy-2- propylacetate | dermal | LD ₅₀ | rat | / | > 5000 mg/kg | / | / |
| Xylene (mixture of isomers) | oral | LD ₅₀ | rat | / | > 3523 mg/kg | / | / |
| Xylene (mixture of isomers) | dermal | LD ₅₀ | rabbit | / | 4200 mg/kg | / | / |
| Xylene (mixture of isomers) | inhalation (vapours) | LC ₅₀ | rat | 4 h | 29 mg/l | / | / |
| ethylbenzene | dermal | LD ₅₀ | rabbit | / | 17800 mg/kg | / | / |
| ethylbenzene | oral | LD ₅₀ | rat | / | 3500 mg/kg | / | / |
| ethylbenzene | inhalation | LC ₅₀ | / | 4 h | 11 mg/l | / | ATE |

Additional information

The product is not classified for acute toxicity.

- (b) Skin corrosion/irritation
- No information.
- Additional information

The product is not classified as irritating to skin and eyes.

(c) Serious eye damage/irritation

No information.

(d) Respiratory or skin sensitisation No information.

Additional information

- The product is not classified as sensitising.
- (e) (Germ cell) mutagenicity No information.
- (f) Carcinogenicity
- No information.
- (g) Reproductive toxicity No information.

Summary of evaluation of the CMR properties

The product is not classified as carcinogenic, mutagenic or toxic for reproduction.

(h) STOT-single exposure No information.

Additional information

STOT SE (single exposure): Not classified.

(i) STOT-repeated exposure

No information.

Additional information STOT RE (repeated exposure): Not classified.

(j) Aspiration hazard

No information.

Additional information

Aspiration hazard: Not classified.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Acute (short-term) toxicity For components

| NAME | TYPE | VALUE | EXPOSURE TIME | SPECIES | ORGANISM | METHOD | REMARK |
|-----------------------------|------------------|-----------------------|------------------|---------|---------------------|--------|--------|
| Xylene (mixture of isomers) | LC ₅₀ | 13.4 mg/L | 96 h | fish | Pimephales promelas | / | / |
| Xylene (mixture of isomers) | LC ₅₀ | 13.1 - 16.5 mg/L | 96 h | fish | Lepomis macrochirus | / | / |
| Xylene (mixture of isomers) | LC ₅₀ | 2661 - 4093 mg/L | 96 h | fish | Oncorhynchus mykiss | / | / |
| Xylene (mixture of isomers) | LC ₅₀ | 19 mg/L | 96 h | fish | Lepomis macrochirus | / | / |
| Xylene (mixture of isomers) | LC ₅₀ | 30.26 - 40.75 mg/L | 96 h | fish | Poecilia reticulata | / | / |
| Xylene (mixture of isomers) | LC ₅₀ | 23.53 - 29.97 mg/L | 96 h | fish | Pimephales promelas | / | / |
| Xylene (mixture of isomers) | LC ₅₀ | 7711 - 9591 mg/L | 96 h | fish | Lepomis macrochirus | / | / |
| Xylene (mixture of isomers) | LC ₅₀ | 780 mg/L | 96 h | fish | Cyprinus carpio | / | / |
| Xylene (mixture of isomers) | LC ₅₀ | > 780 mg/L | 96 h | fish | Cyprinus carpio | / | / |
| Xylene (mixture of isomers) | LC ₅₀ | 13.5 - 17.3 mg/L | 96 h | fish | Oncorhynchus mykiss | / | / |
| Xylene (mixture of isomers) | EC ₅₀ | 3.82 mg/L | 48 h | daphnia | / | / | / |
| ethylbenzene | EC ₅₀ | 2.1 mg/L | 48 h | Daphnia | / | / | / |

Chronic (long-term) toxicity

No information.

12.2 Persistence and degradability

Abiotic degradation, physical- and photo-chemical elimination No information. Biodegradation

For components

| NAME | ТҮРЕ | RATE | TIME | EVALUATION | METHOD | REMARK |
|----------------------------|------------------|--------------|------|-----------------------|--------|--------|
| 1-methoxy-2- propylacetate | Water solubility | > 10000 mg/L | / | / | / | / |
| 1-methoxy-2- propylacetate | biodegradability | / | / | rapidly biodegradable | / | / |

12.3 Bioaccumulative potential Partition coefficient For components

| NAME | MEDIA | VALUE | TEMPERATURE | PH | CONCENTRATION | METHOD |
|---|-----------------|-------------|------------------------|----------|------------------------|--------------|
| 1-methoxy-2- propylacetate | Log Pow | 1.2 | / | / | 1 | / |
| Bioconcentration factor (BCI No information. | -) | - | 8 | | | |
| 2.4 Mobility in soil | | | | | | |
| Known or predicted distribut No information. | ion to environ | mental com | partments | | | |
| Surface tension No information. | | | | | | |
| Adsorption/Desorption No information. | | | | | | |
| 12.5 Results of PBT and vPvB a | ssessment | | | | | |
| No evaluation. | | | | | | |
| 2.6 Other adverse effects | | | | | | |
| No information. | | | | | | |
| 2.7 Additional information | | | | | | |
| For product Product is not classified as o | dangerous for e | environmenl | t. Do not allow to rea | ach grou | nd water, water course | es or sewage |

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product / Packaging disposal

Waste chemical

Do not allow product to reach drains/sewage systems. Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste.

Waste codes / waste designations according to LoW No information.

Packaging

Deliver completely emptied containers to approved waste disposal authorities. Uncleaned containers are classified as hazardous waste - they should be handled in the same manner as the contents. Uncleaned containers should not be perforated, cut or welded. Empty containers represent a fire hazard as they may contain flammable product residues and vapour.

Waste codes / waste designations according to LoW No information.

Waste treatment-relevant information No information.

Sewage disposal-relevant information No information.

Other disposal recommendations No information.

SECTION 14: TRANSPORT INFORMATION

| ADR/RID | IMDG | ΙΑΤΑ | ADN | | | | | |
|--|---|---|---|--|--|--|--|--|
| 14.1 UN number | | | | | | | | |
| UN 1263 | UN 1263 | UN 1263 | UN 1263 | | | | | |
| 14.2 UN proper shipping name | | | | | | | | |
| PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) | PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) | PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) | PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polisi liquid filler and liquid lacquer base) | | | | | |
| 14.3 Transport hazard class(es) | | | | | | | | |
| 3 | 3 | 3 | 3 | | | | | |
| | | 3 | | | | | | |
| 14.4 Packing group | | | | | | | | |
| | 111 | 111 | 111 | | | | | |
| 14.5 Environmental hazards | | | | | | | | |
| NO | NO | NO | NO | | | | | |
| 14.6 Special precautions for user | | | | | | | | |
| Limited quantities 5 L Transport category 3 Tunnel restriction code (D/E) | Limited quantities 5 L EmS F-E, <u>S-E</u> Special provisions 163, 367, 650 Packing Instructions P001, IBC03, LP01, R001 Special packing provisions PP1 Tank instructions T2 Tank special provisions TP1, TP29 | Limited Quantity Packing Instructions Y344 Limited Quantity Net Qty 10 L Passenger Packing Instruction Packing Instructions 355 Passenger Packing Instruction Net Qty 25 L Special provisions A3, A72, A192 | Limited quantities 5 L | | | | | |
| 14.7 Transport in bulk according to A | nnex II of Marpol and the IBC Code | | | | | | | |
| Goods may not be carried in bulk in bulk containers, containers or vehicles. | Goods may not be carried in bulk in bulk containers, containers or vehicles. | Not given/not applicable | Not given/not applicable | | | | | |

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)(including last amendment Commission Regulation (EU) 2015/830)

- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-guideline) not applicable

Regulation EC 648/2004 on detergents No information.

Special instructions

Observe the regulations on employment and protection against dangerous substances for young people, pregnant women and nursing mothers.

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION

Indication of changes No information. Key literature references and sources for data No information. Abbreviations and acronyms ATE - Acute Toxicity Estimate ADR - Agreement concerning the International Carriage of Dangerous Goods by Road ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways **CEN - European Committee for Standardisation** C&L - Classification and Labelling CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008 CAS# - Chemical Abstracts Service number CMR - Carcinogen, Mutagen, or Reproductive Toxicant CSA - Chemical Safety Assessment CSR - Chemical Safety Report DMEL - Derived Minimal Effect Level **DNEL - Derived No Effect Level** DPD - Dangerous Preparations Directive 1999/45/EC DSD - Dangerous Substances Directive 67/548/EEC DU - Downstream User EC - European Community ECHA - European Chemicals Agency EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS) EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway) EEC - European Economic Community EINECS - European Inventory of Existing Commercial Substances ELINCS - European List of notified Chemical Substances EN - European Standard EQS - Environmental Quality Standard EU - European Union Euphrac - European Phrase Catalogue EWC - European Waste Catalogue (replaced by LoW – see below) **GES - Generic Exposure Scenario** GHS - Globally Harmonized System IATA - International Air Transport Association ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air IMDG - International Maritime Dangerous Goods IMSBC - International Maritime Solid Bulk Cargoes **IT - Information Technology** IUCLID - International Uniform Chemical Information Database IUPAC - International Union for Pure Applied Chemistry JRC - Joint Research Centre Kow - octanol-water partition coefficient LC50 - Lethal Concentration to 50 % of a test population LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose) LE - Legal Entity Low - List of Wastes (see http://ec.europa.eu/environment/waste/framework/list.htm) LR - Lead Registrant

M/I - Manufacturer / Importer MS - Member States MSDS - Material Safety Data Sheet OC - Operational Conditions OECD - Organization for Economic Co-operation and Development OEL - Occupational Exposure Limit OJ - Official Journal **OR - Only Representative** OSHA - European Agency for Safety and Health at work PBT - Persistent, Bioaccumulative and Toxic substance PEC - Predicted Effect Concentration PNEC(s) - Predicted No Effect Concentration(s) **PPE - Personal Protection Equipment** (Q)SAR - Qualitative Structure Activity Relationship REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006 RID - Regulations concerning the International Carriage of Dangerous Goods by Rail RIP - REACH Implementation Project RMM - Risk Management Measure SCBA - Self-Contained Breathing Apparatus SDS - Safety data sheet SIEF - Substance Information Exchange Forum SME - Small and Medium sized Enterprises STOT - Specific Target Organ Toxicity (STOT) RE - Repeated Exposure (STOT) SE - Single Exposure SVHC - Substances of Very High Concern **UN - United Nations** vPvB - Very Persistent and Very Bioaccumulative List of relevant H phrases H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H332 Harmful if inhaled. H373 May cause damage to organs through prolonged or repeated exposure.