# **Technical Data Sheet**



# 2005 Underbody Elastil Spray, Over paintable Underbody Protection

Ver.: 2020-1

# Description

Fast drying, over paintable, underbody protection that ensures excellent and durable protection against corrosion, stone chip, salt, etc. Strong adhesion on raw or painted metal, plastic materials or old underbody protection.

# **Features & benefits**

- Strong adhesion on raw or painted metal, plastic materials or old underbody protection.
- long lasting and elastic
- Builds protective film against stone chips, salt, noise etc.
- regulation of structure by pressure and distance
- Fast drying.

# **Substrate preparation**

Surfaces to be treated must be clean, dry, rust-free and grease-free.

Avoid application on brake or exhaust system.

It is recommended to use appropriate primer (epoxy, etch, etc.) to optimize corrosion protection.

# Application data Mixing ratio The product is ready to use! Shake the product before use. Application Number of coats min 2 Total dry film build 0,5 mm wet film Application air temperature 10 – 25 °C (50 – 77 °F) First coat must be completely dry before the second coat (overpainting). Drying Fully dry at 20 °C/68 °F 24 h

SILCO d.o.o., Šentrupert 5a, 3303 Gomilsko, Slovenija
Tel.: +386 (0)3 703 31 80 / Fax.: +386 (0)3 703 31 88

Page 1

E-mail: info@silco-automotive.com / www.silco-automotive.com

# **Technical Data Sheet**



# 2005 Underbody Elastil Spray, Over paintable Underbody Protection

Ver.: 2020-1

Prod. Nr.	Description	Volume	Packaging Box
2005-A	Grey	1 L	12
2005-В	Black	1 L	12

### VOC

(2004/42/IIB(e)(840) 551

## **Shelf life**

Min. 12 months from the production date under normal storage conditions and unopened can.

# **Additional Information**

### FOR PROFESSIONAL USE ONLY!

Always read the instructions.

**IMPORTANT:** This product contains hazardous substances at work so it is necessary to always use/wear appropriate protective equipment. For further instructions, check the label on the product and safety data sheet. A person who uses the product for any purpose other than recommended in this technical data sheet, acts at his own risk. It is the user's responsibility to take all necessary steps to fulfil the local legislation.

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public.

Information and methods described are based on the best information and practices known to us and serve merely as guidelines for optimal use, without liability to performance, results or fitness for any intended use. We do not accept any responsibility for the behaviour of the product or damage arising from the use of the product. Before using the product, the user must check if this is the latest version.

All products mentioned in this data sheet are trademarks owned by Silco.

SILCO d.o.o., Šentrupert 5a, 3303 Gomilsko, Slovenija

Tel.: +386 (0)3 703 31 80 / Fax.: +386 (0)3 703 31 88

E-mail: info@silco-automotive.com / www.silco-automotive.com

Page 2