Technical Data Sheet



2080 Antidust, Dust and Overspray Protection

Ver.: 2019-9

Description

Antidust is a transparent, colorless, adhesive, waterbased coating for spray booth applications. It forms a protective layer on application, which binds all the dust and dirt particles and overspray. Antidust is biodegradable. It can be used on all non-porous cabin walls.

Antidust binds overspray, dust and dirt while optmally protecting the cabin walls and existing lighting systems from contamination.

Features

- Physical state: liquid
- Packaging: canister
- Colour: colourless
- Smell: fresh
- Specific weight: 1,08 -1,1 kg/L
- Applied quantity: 1 L per 15 m²
- Solubility: well soluble in cold and hot water

Application

PREPARATION - Clean, dry and degrease cabin walls.

APPLICATION – The product is ready to use. Free from organic solvents, easy to apply with brush, paint roller or spray gun.

REMOVE – Antidust should be removed with a sponge and water or high pressure hose after 4-6 weeks.

STORAGE – Antidust is sensitive to frost. Shelf life is 12 onths at 18-20°C in closed original container.

Additional Information

FOR PROFESSIONAL USE ONLY!

Always read the instructions.

IMPORTANT: This product contains hazardous substances at work so it is necessary to always use/wear appropriate protective equipment. For further instructions, check the label on the product and safety data sheet. A person who uses the product for any purpose other than recommended in this technical data sheet, acts at his own risk. It is the user's responsibility to take all necessary steps to fulfil the local legislation. Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public.

Information and methods described are based on the best information and practices known to us and serve merely as guidelines for optimal use, without liability to performance, results or fitness for any intended use. We do not accept any responsibility for the behaviour of the product or damage arising from the use of the product. Before using the product, the user must check if this is the latest version.

All products mentioned in this data sheet are trademarks owned by Silco.

SILCO d.o.o., Šentrupert 5a, 3303 Gomilsko, Slovenija	
Tel.: +386 (0)3 703 31 80 / Fax.: +386 (0)3 703 31 88	Page 1
E-mail: info@silco-automotive.com / www.silco-automotive.com	