Product name: 3008 Dashpro Sil

Creation date: 21.10.2013 · Revision: 9.4.2019 · Version: 1



SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name

3008 Dashpro Sil

Product code

[3008]



chemius.net/YTx6b

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Interior vehicle cleaner.

Uses advised against

No information.

1.3. Details of the supplier of the safety data sheet

Manufacturer

SILCO, D.O.O.

Address: Šentrupert 5 a, 3303 Gomilsko, Slovenia

Phone: +386 3 703 3180 Fax: +386 3 703 3188

E-mail: n.cvilak@silco-automotive.com Point of contact for safety info: Nejc Cvilak

1.4. Emergency telephone number

Emergency

112

Supplier

+386 3 703 3180

SECTION 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Aerosol 1; H222 Extremely flammable aerosol.

Aerosol 1; H229 Pressurised container: May burst if heated.

Skin Irrit. 2; H315 Causes skin irritation.

STOT SE 3; H336 May cause drowsiness or dizziness.

Aquatic Chronic 2; H411 Toxic to aquatic life with long lasting effects.

Print date: 23.8.2019 Page 1 of 13

Product name: 3008 Dashpro Sil

Creation date: 21.10.2013 · Revision: 9.4.2019 · Version: 1



2.2 Label elements

2.2.1. Labelling according to Regulation (EC) No 1272/2008 [CLP]







Signal word: Danger

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

EUH208 Contains (R)-p-mentha-1,8-diene. May produce an allergic reaction.

P251 Do not pierce or burn, even after use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P410 + P412 Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122°F.

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P261 Avoid breathing mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves.

P312 Call a POISON CENTER/doctor if you feel unwell.

P391 Collect spillage.

P501 Dispose of contents/container in accordance with national regulation.

2.2.2. Contains:

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (EC: 927-510-4)

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane (EC: 921-024-6)

2.2.3. Special provisions

Vapours and air can at inadequate ventilation form an explosive mixture.

2.3. Other hazards

No information.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

For mixtures see 3.2.

Print date: 23.8.2019 Page 2 of 13

Product name: 3008 Dashpro Sil

Creation date: 21.10.2013 · Revision: 9.4.2019 · Version: 1



3.2. Mixtures

Name	CAS EC Index	%	Classification according to Regulation (EC) No 1272/2008 (CLP)	Specific Conc. Limits	REACH Registration No.	
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	- 927-510-4 -	25-50	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411		01-2119475515-33	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	- 921-024-6 -	25-50	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411		01-2119475514-35	
isobutane [C, S]	75-28-5 200-857-2 601-004-01-8	20-25	Flam. Gas 1; H220 Press. Gas; H280		-	
propane	74-98-6 200-827-9 601-003-00-5	10-20	Flam. Gas 1; H220 Press. Gas; H280		-	
butane [C]	106-97-8 203-448-7 601-004-00-0	2,5-10	Flam. Gas 1; H220 Press. Gas; H280		-	
(R)-p-mentha-1,8-diene [C]	5989-27-5 227-813-5 601-029-00-7	0,1-1	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410		-	

Notes for substances:

C Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers.

In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

S This substance may not require a label according to Article 17 (see section 1.3 of Annex I) (Table 3.1).

This substance may not require a label according to Article 23 of Directive 67/548/EEC (see section 8 of Annex VI to that Directive) (Table 3.2).

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

General notes

Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency.

Following inhalation

Remove patient to fresh air - move out of dangerous area. If symptoms develop and persist, seek medical attention.

Following skin contact

Take off all contaminated clothing. Wash affected skin areas thoroughly with plenty of water and soap. If symptoms develop and persist, seek medical attention.

Following eye contact

Immediately flush eyes with running water, keeping eyelids apart. If irritation persists, seek professional medical attention.

Following ingestion

Not likely.

Print date: 23.8.2019 Page 3 of 13

Product name: 3008 Dashpro Sil

Creation date: 21.10.2013 · Revision: 9.4.2019 · Version: 1



4.2. Most important symptoms and effects, both acute and delayed

Inhalation

Vapours may cause drowsiness and dizziness.

Skin contact

Itching, redness, pain.

Eye contact

Contact with eyes can cause irritation (redness, tearing, pain).

Ingestion

May cause nausea/vomiting and diarrhea.

4.3. Indication of any immediate medical attention and special treatment needed

-

SECTION 5. FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide. Dry chemical powder. Water spray. Alcohol resistant foam.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

In the event of fire the following can be generated: carbon monoxide (CO), carbon dioxide (CO₂).

5.3. Advice for firefighters

Protective actions

Cool containers at risk with water spray. If possible remove containers from endangered area. Prolonged heating can cause an explosion.

Special protective equipment for firefighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

Additional information

Contaminated firefighting water must be disposed of in accordance with the regulations; do not allow to reach the sewage system.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment

Use personal protective equipment (Section 8).

Emergency procedures

Ensure adequate ventilation. Keep away from sources of ignition and/or heat; No smoking! Prevent access to unprotected personnel.

6.1.2. For emergency responders

_

Print date: 23.8.2019 Page 4 of 13

Product name: 3008 Dashpro Sil

Creation date: 21.10.2013 · Revision: 9.4.2019 · Version: 1



6.2. Environmental precautions

Do not allow to enter water/drains/sewerage. In case of release into the environment, inform the relevant authorities.

6.3. Methods and material for containment and cleaning up

6.3.1. For containment

_

6.3.2. For cleaning up

Absorb product (with inert material), collect it in special container and dispose it to a licensed hazardous-waste disposal contractor.

6.3.3. Other information

-

6.4. Reference to other sections

See also Sections 8 and 13.

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

7.1.1. Protective measures

Measures to prevent fire

Ensure adequate ventilation. Keep away from sources of ignition - no smoking. Use spark-proof tools. Take precautionary measures against static discharges. Pressurized container; protect from sunlight and do not expose to tempratures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or incandescent material.

Measures to prevent aerosol and dust generation

_

Measures to protect the environment

-

7.1.2. Advice on general occupational hygiene

Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Avoid contact with skin and eyes. Do not breathe vapours/mist.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1. Technical measures and storage conditions

Keep in cool and well ventilated area. Protect from open fire, heat and direct sunlight. Keep away from food, drink and animal feeding stuffs. Keep in tightly closed container.

7.2.2. Packaging materials

-

7.2.3. Requirements for storage rooms and vessels

-

7.2.4. Storage class

-

7.2.5. Further information on storage conditions

-

7.3. Specific end use(s)

Recommendations

-

Print date: 23.8.2019 Page 5 of 13

Product name: 3008 Dashpro Sil

Creation date: 21.10.2013 · Revision: 9.4.2019 · Version: 1



Industrial sector specific solutions

_

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

8.1.1. Occupational exposure limit values

Name (CAS)	Limit values		Short-term exposure limit		Remarks	Biological Tolerance Values	
	ml/m ³ (ppm)	_	ml/m ³ (ppm)	mg/m ³			
Butane (106-97-8)	600	1450	750	1810	Carc, (only applies if Butane contains more than 0.1% of buta-1,3-diene)		
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (-)		1300			AGW (ALVEO); Allg. Staubg.: TRGS 900 2.4 AGS		
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane (-)		1200			AGW (ALVEO); Allg. Staubg.: TRGS 900 2.4 AGS		

8.1.2. Information on monitoring procedures

BS EN 14042:2003 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 482:2012+A1:2015 Workplace exposure. General requirements for the performance of procedures for the measurement of chemical agents. BS EN 689:2018 Workplace exposure. Measurement of exposure by inhalation to chemical agents. Strategy for testing compliance with occupational exposure limit values.

8.1.3. DNEL/DMEL values

No information.

8.1.4. PNEC values

No information.

8.2. Exposure controls

8.2.1. Appropriate engineering control

Substance/mixture related measures to prevent exposure during identified uses

Use good personal hygiene practices – wash hands at breaks and when done working with material. Avoid contact with eyes and skin. Do not breathe vapours/aerosols.

Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration.

8.2.2. Personal protective equipment

Eye and face protection

Safety glasses with side protection (EN 166).

Hand protection

Protective gloves (EN 374). Observe the manufacturer's instructions regarding the use, storage, maintenance and replacement of gloves. In case of damage or at the first signs of wear and tear, change the gloves immediately. The penetration time is determined by the protective glove manufacturer and must be observed.

Appropriate materials

Material	Thickness	Penetration Time	Remark
Nitrile	0,7 mm	240 min	

Skin protection

Cotton protective clothing and shoes that cover the entire foot (EN ISO 20345).

Print date: 23.8.2019 Page 6 of 13

Product name: 3008 Dashpro Sil

Creation date: 21.10.2013 · Revision: 9.4.2019 · Version: 1



Respiratory protection

In case of insufficient ventilation wear suitable respiratory protection. Wear suitable protective breathing mask (EN 136) with filter A2-P2 (EN 14387).

Thermal hazards

_

8.2.3. Environmental exposure controls

_

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

-	Physical state:	liquid
-	Colour:	colourless
-	Odour:	characteristic

Important health, safety and environmental information

-	рН	No information.
-	Melting point/freezing point	No information.
-	Initial boiling point/boiling range	No information.
-	Flash point	No information.
-	Evaporation rate	No information.
-	Flammability (solid, gas)	> 200 °C
-	Explosion limits (vol%)	No information.
-	Vapour pressure	8300 hPa at 20 °C
-	Vapour density	No information.
-	Density	Density : 0,65616 g/cm ³ at 20 °C
-	Solubility	No information.
-	Partition coefficient	No information.
-	Auto-ignition temperature	No information.
-	Decomposition temperature	No information.
-	Viscosity	No information.
-	Explosive properties	Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.
-	Oxidising properties	No information.

9.2. Other information

-	Weight organic solvents	88,8 %
-	Remarks:	

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity

_

10.2. Chemical stability

Product is stable under normal conditions of use, recommended handling and storage conditions.

Print date: 23.8.2019 Page 7 of 13

Product name: 3008 Dashpro Sil

Creation date: 21.10.2013 · Revision: 9.4.2019 · Version: 1



10.3. Possibility of hazardous reactions

-

10.4. Conditions to avoid

Protect from heat, direct sunlight, open fire, sparks.

10.5. Incompatible materials

Not known.

10.6. Hazardous decomposition products

Under normal use conditions no hazardous decomposition products are expected. In case of fire/explosion vapours/gases that pose a health hazard are released.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

(a) Acute toxicity

Name	Exposure route	Туре	Species	Time	Value	Method	Remark
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (-)	oral	LD ₅₀	rat		> 5840 mg/kg		
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (-)	dermal	LD ₅₀	rat		> 2920 mg/kg		
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (-)	inhalation	LC ₅₀	rat	4 h	> 23300 mg/l		
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane (-)	oral	LD ₅₀	rat		> 5840 mg/kg	OECD 401	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane (-)	dermal	LD ₅₀	rat		> 2920 mg/kg	OECD 402	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane (-)	inhalation	LC ₅₀	rat		< 25200 mg/m ³	OECD 403	
isobutane (75-28-5)	inhalation	LC ₅₀	rat	4 h	> 50 mg/l		Literature study
propane (74-98-6)	inhalation	LC ₅₀	rat	4 h	20 mg/l		Literature study
butane (106-97-8)	inhalation	LC ₅₀	rat	4 h	658 mg/l		Literature study
(R)-p-mentha-1,8-diene (5989-27-5)	oral	LD ₅₀	rat		4400 mg/kg		
(R)-p-mentha-1,8-diene (5989-27-5)	dermal	LD ₅₀	rabbit		> 5000 mg/kg		

(b) Skin corrosion/irritation

Additional information: Irritant to skin and mucous membranes.

(c) Serious eye damage/irritation

No information.

(d) Respiratory or skin sensitisation

No information.

(e) (Germ cell) mutagenicity

No information.

Print date: 23.8.2019 Page 8 of 13

Product name: 3008 Dashpro Sil

Creation date: 21.10.2013 · Revision: 9.4.2019 · Version: 1



(f) Carcinogenicity

No information.

(g) Reproductive toxicity

No information.

Summary of evaluation of the CMR properties

No information.

(h) STOT-single exposure

No information.

(i) STOT-repeated exposure

No information.

(i) Aspiration hazard

No information.

SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Acute (short-term) toxicity

For components

Substance (CAS Nr.)	Туре	Value	Exposure time	Species	Organism	Method	Remark
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (-)	EC ₅₀	3 mg/L	48 h	daphnia	Daphnia magna		
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane (-)	EC ₅₀	3 mg/L	48 h	daphnia	Daphnia magna		
(R)-p-mentha-1,8-diene (5989-27-5)	EC ₅₀	0,67 mg/L	48 h	crustacea	Daphnia magna		

12.1.2. Chronic (long-term) toxicity

No information.

12.2. Persistence and degradability

12.2.1. Abiotic degradation, physical- and photo-chemical elimination

No information.

12.2.2. Biodegradation

For product

Туре	Rate	Time	Evaluation	Method	Remark
aerobic			biodegradable		

12.3. Bioaccumulative potential

12.3.1. Partition coefficient

No information.

12.3.2. Bioconcentration factor (BCF)

No information.

12.4. Mobility in soil

12.4.1. Known or predicted distribution to environmental compartments

No information.

Print date: 23.8.2019 Page 9 of 13

Product name: 3008 Dashpro Sil

Creation date: 21.10.2013 · Revision: 9.4.2019 · Version: 1



12.4.2. Surface tension

No information.

12.4.3. Adsorption/Desorption

No information.

12.5. Results of PBT and vPvB assessment

No evaluation.

12.6. Other adverse effects

No information.

12.7. Additional information

For product

Toxic to aquatic organisms: may cause long-term adverse effects in the aquatic environment.

Avoid release to the environment.

Water hazard class 2 (self-assessment): hazardous for water.

Do not allow to reach ground water, water courses or sewage system.

Danger to drinking water if even small quantities leak into ground water.

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

13.1.1. Product / Packaging disposal

Waste chemical

Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste. Do not allow product to reach drains/sewage systems. Do not dispose together with household garbage.

Waste codes / waste designations according to LoW

16 05 04* - gases in pressure containers (including halons) containing dangerous substances

Packaging

Deliver completely emptied containers to approved waste disposal authorities.

Waste codes / waste designations according to LoW

15 01 04 - metallic packaging

13.1.2. Waste treatment-relevant information

-

13.1.3. Sewage disposal-relevant information

-

13.1.4. Other disposal recommendations

-

SECTION 14. TRANSPORT INFORMATION

14.1. UN number

UN 1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

2



Print date: 23.8.2019 Page 10 of 13

Product name: 3008 Dashpro Sil

Creation date: 21.10.2013 · Revision: 9.4.2019 · Version: 1



14.4. Packing group

Not applicable.

14.5. Environmental hazards

Additional labeling: ENVIRONMENTALLY HAZARDOUS

IMDG: MARINE POLLUTANT

14.6. Special precautions for user

Limited quantities

1 L

Tunnel restriction code

(D)

IMDG EmS

F-D, S-U

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Goods may not be carried in bulk in bulk containers, containers or vehicles.

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (including last amendment Commission Regulation (EU) 2015/830)
- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

15.1.1. Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-guideline)

Not applicable.

15.1.2. Ingredients according to Regulation EC 648/2004 on detergents

> 30%: aliphatic hydrocarbons; perfumes (Citral, Limonene)

15.2. Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16. OTHER INFORMATION

Indication of changes

-

Abbreviations and acronyms

ATE - Acute Toxicity Estimate

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

CEN - European Committee for Standardisation

C&L - Classification and Labelling

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

CAS# - Chemical Abstracts Service number

CMR - Carcinogen, Mutagen, or Reproductive Toxicant

CSA - Chemical Safety Assessment

CSR - Chemical Safety Report

DMEL - Derived Minimal Effect Level

DNEL - Derived No Effect Level

DPD - Dangerous Preparations Directive 1999/45/EC

Print date: 23.8.2019 Page 11 of 13



Product name: 3008 Dashpro Sil

Creation date: 21.10.2013 · Revision: 9.4.2019 · Version: 1



DSD - Dangerous Substances Directive 67/548/EEC

DU - Downstream User

EC - European Community

ECHA - European Chemicals Agency

EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS) EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway)

EEC - European Economic Community

EINECS - European Inventory of Existing Commercial Substances

ELINCS - European List of notified Chemical Substances

EN - European Standard

EQS - Environmental Quality Standard

EU - European Union

Euphrac - European Phrase Catalogue

EWC - European Waste Catalogue (replaced by LoW - see below)

GES - Generic Exposure Scenario

GHS - Globally Harmonized System

IATA - International Air Transport Association

ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG - International Maritime Dangerous Goods

IMSBC - International Maritime Solid Bulk Cargoes

IT - Information Technology

IUCLID - International Uniform Chemical Information Database

IUPAC - International Union for Pure Applied Chemistry

JRC - Joint Research Centre

Kow - octanol-water partition coefficient

LC₅₀ - Lethal Concentration to 50 % of a test population

LD₅₀ - Lethal Dose to 50% of a test population (Median Lethal Dose)

LE - Legal Entity

LoW - List of Wastes (see http://ec.europa.eu/environment/waste/framework/list.htm)

LR - Lead Registrant

M/I - Manufacturer / Importer

MS - Member States

MSDS - Material Safety Data Sheet

OC - Operational Conditions

OECD - Organization for Economic Co-operation and Development

OEL - Occupational Exposure Limit

OJ - Official Journal

OR - Only Representative

OSHA - European Agency for Safety and Health at work

PBT - Persistent, Bioaccumulative and Toxic substance

PEC - Predicted Effect Concentration

PNEC(s) - Predicted No Effect Concentration(s)

PPE - Personal Protection Equipment

(Q)SAR - Qualitative Structure Activity Relationship

REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006

RID - Regulations concerning the International Carriage of Dangerous Goods by Rail

RIP - REACH Implementation Project

RMM - Risk Management Measure

SCBA - Self-Contained Breathing Apparatus

SDS - Safety data sheet

SIEF - Substance Information Exchange Forum

SME - Small and Medium sized Enterprises

STOT - Specific Target Organ Toxicity

(STOT) RE - Repeated Exposure

(STOT) SE - Single Exposure

SVHC - Substances of Very High Concern

UN - United Nations

vPvB - Very Persistent and Very Bioaccumulative

Key literature references and sources for data

-

Print date: 23.8.2019 Page 12 of 13

Product name: 3008 Dashpro Sil

Creation date: 21.10.2013 · Revision: 9.4.2019 · Version: 1



List of relevant H phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.



☑ Provided correct labelling of the product

☑ Compliance with the local legislation

☑ Provided correct classification of the product

☑ Provided adequate transport data

© BENS Consulting | www.bens-consulting.com

The information of this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under Section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.

Print date: 23.8.2019 Page 13 of 13