

3025 Underbody Wax

silco[®]

Wax-based underbody protection

A high-performance, wax-based coating that protects against rust and corrosion, ideal for underbody areas like floor panels and wheel arches.

- / Superior corrosion protection
- / Strong hydrophobic barrier against rust from moisture and road salt
- / Versatile application on metal surfaces, with optional primer use
- / Safe for plastics, rubber, and paint
- / Complies with SFS 4087 Standard for reliable performance

www.silco.si



3025 Underbody Wax

Wax-based underbody protection

Product info

3025 Underbody Wax is a high-performance, bitumen-free, wax-based undercoating designed for repairing and enhancing existing underbody protections on vehicles.

It offers superior rust and corrosion resistance by forming a strong hydrophobic barrier that protects against moisture, road salt, and other corrosive elements.

Safe for use on plastics, rubber, and paint, it's ideal for application on underbody areas such as floor panels, wheel arches, and chassis parts. Ensures thorough coverage and lasting protection.

Technical information

Base	Micro cristal wax, petrolatum, solvents, additives
Colour	Black
Coverage	1,4 m ² per 1 liter
Drying time (20°C)	4–6 h (dust dry)
Recommended layer thickness	400 µm wet 200 µm dry
Operating temperature	-30–75 °C
Application temperature	10–25°C

How to use?

1. Surface must be dry and clean, free from dirt, rust, grease ect.; apply an anti-corrosion primer if needed.
2. Shake the can well before use.
3. Use an underbody coating gun or airless sprayer. Set air pressure to 3-6 Bar.
4. Avoid applying on the braking or exhaust systems.
5. **Apply evenly to floor panels, wheel arches, and chassis parts.**
6. Apply additional coats if needed, letting each layer dry.
7. Check for complete coverage, especially in hard-to-reach areas.
8. Clean equipment immediately after use to prevent clogging.
9. **Can only be over sprayed/painted with wax products.**
10. Underbody Wax is only moderately resistant to stone chip and therefore it is recommended to inspect the coating yearly (just before winter season) and to touch up if needed.

Packaging

Cartridge	1 L
Per box	12 pcs