

### Description

High quality, acrylic black matt paint in aerosol to be used as control spray before filler sanding.

### Features & Benefits

Good adhesion to various substrates: metal, wood, glass, ceramics, plastics

High covering power.

Economic in use.




Fast drying.

### Substrate preparation

Apply only on dust-free and dry substrates. Aluminium and zinc coated surfaces should be pretreated with suitable primer. Not suitable for PS, PE, PP and PP/EDPM plastics.

Suitable for wood, glass and ceramics.

### Application data

	<p><b>Mixing ratio</b> The product is ready to use!</p>						
	<p><b>Application</b> Shake can vigorously for 2 min before spraying. Spray to test.</p> <table data-bbox="472 1330 1114 1464"> <tr> <td>Spraying distance</td> <td>15 – 20 cm</td> </tr> <tr> <td>Number of coats/spray passes</td> <td>2</td> </tr> <tr> <td>Dry film thickness (1 spraypass)</td> <td>20 microns</td> </tr> </table> <p>After spraying turn the can upside down and spray until the valve is clean. It is strongly recommended that ready to use products are applied at a temperature higher than 15 °C/59 °F. Can be recoated with itself or other commercial 1K or 2K clear coats.</p>	Spraying distance	15 – 20 cm	Number of coats/spray passes	2	Dry film thickness (1 spraypass)	20 microns
Spraying distance	15 – 20 cm						
Number of coats/spray passes	2						
Dry film thickness (1 spraypass)	20 microns						
	<p><b>Drying</b></p> <table data-bbox="472 1733 1038 1868"> <tr> <td>Dust dry (20 °C/68 °F)</td> <td>10 - 15 min</td> </tr> <tr> <td>Touch dry (20 °C/68 °F)</td> <td>30 - 40 min</td> </tr> <tr> <td>Polishable</td> <td>6 h</td> </tr> </table>	Dust dry (20 °C/68 °F)	10 - 15 min	Touch dry (20 °C/68 °F)	30 - 40 min	Polishable	6 h
Dust dry (20 °C/68 °F)	10 - 15 min						
Touch dry (20 °C/68 °F)	30 - 40 min						
Polishable	6 h						

Prod. Nr.	Description	Volume	Packaging Box
3550	Black	500 ml	12
<b>VOC</b>			
2004/42/IIB(e)(840) <708			
<b>Shelf life</b>			
Min. 48 months from the production date under normal storage conditions and unopened can.			
<b>Additional Information</b>			
<p><b>FOR PROFESSIONAL USE ONLY!</b></p> <p>Always read the instructions.</p> <p><b>IMPORTANT:</b> This product contains hazardous substances at work so it is necessary to always use/wear appropriate protective equipment. For further instructions, check the label on the product and safety data sheet. A person who uses the product for any purpose other than recommended in this technical data sheet, acts at his own risk. It is the user's responsibility to take all necessary steps to fulfil the local legislation.</p> <p>Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public.</p> <p>Information and methods described are based on the best information and practices known to us and serve merely as guidelines for optimal use, without liability to performance, results or fitness for any intended use. We do not accept any responsibility for the behaviour of the product or damage arising from the use of the product. Before using the product, the user must check if this is the latest version.</p> <p>All products mentioned in this data sheet are trademarks owned by Silco.</p>			