

Description

Top quality PE masking film. Its special structure prevents formation of stains on paint due to the residual humidity.

Features & Benefits

- high thickness and resistance to tearing
- excellent adhesion of any kind of paint or fillers
- electrostatically loaded
- holds on the car and holds paint mist
- resistant up to 110 °C/230 °F

Technical Properties

- 4 x 150 m
- thickness 17 µm
- packing 1 pc in a dispenser box, dimensions 17x17x100 cm
- translucent
- upper side of film with the inscription "PAINT THIS SIDE" rolled outside
- gross weight 9,25 kg

Application

Masking film is being used for covering painting object (car, etc) to prevent the spray mist to get in touch with non-paintable surface.

Masking film should be placed in the masking film dispenser or can be also pulled out from the packaging through the dispensing hole. 1 person can place it onto the painting object. Please pay attention before placing the film that the inscription "PAINT THIS SIDE" is on the upper side because of the film properties.

Additional Information

FOR PROFESSIONAL USE ONLY!

IMPORTANT: Products described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public.

Information and methods described are based on the best information and practices known to us and serve merely as guidelines for optimal use, without liability to performance, results or fitness for any intended use. We do not accept any responsibility for the behaviour of the product or damage arising from the use of the product. Before using the product, the user must check if this is the latest version.

All products mentioned in this data sheet are trademarks owned by Silco.