

SAFETY DATA SHEET according to Regulation 1907/2006

Product name: **4110 Etch-prime**

Creation date: **1.3.2011** · Revision: **11.7.2018** · Version: **1**



SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name

4110 Etch-prime



chemius.net/ZTN45

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Etch primer

Uses advised against

No information.

1.3. Details of the supplier of the safety data sheet

Manufacturer

SILCO, D.O.O.

Address: Šentrupert 5 a, 3303 Gomilsko, Slovenia

Phone: +386 3 703 3180

Fax: +386 3 703 3188

E-mail: n.cvilak@silco-automotive.com

Point of contact for safety info: Nejc Cvilak

1.4. Emergency telephone number

Emergency

112

Supplier

+386 3 703 3180

SECTION 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Aerosol 1; H222 Extremely flammable aerosol.

Aerosol 1; H229 Pressurised container: May burst if heated.

Eye Irrit. 2; H319 Causes serious eye irritation.

STOT SE 3; H336 May cause drowsiness or dizziness.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **4110 Etch-prime**

Creation date: **1.3.2011** · Revision: **11.7.2018** · Version: **1**

2.2 Label elements

2.2.1. Labelling according to Regulation (EC) No 1272/2008 [CLP]



Signal word: **Danger**

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700). May produce an allergic reaction.

P251 Do not pierce or burn, even after use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P261 Avoid breathing mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/eye protection/face protection.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P501 Dispose of contents/container in accordance with national regulation.

2.2.2. Contains:

acetone (CAS: 67-64-1, EC: 200-662-2, Index: 606-001-00-8)

n-butyl acetate (CAS: 123-86-4, EC: 204-658-1, Index: 607-025-00-1)

2.2.3. Special provisions

Vapours and air can at inadequate ventilation form an explosive mixture.

2.3. Other hazards

No information.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

For mixtures see 3.2.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **4110 Etch-prime**

Creation date: **1.3.2011** · Revision: **11.7.2018** · Version: **1**

3.2. Mixtures

Name	CAS EC Index	%	Classification according to Regulation (EC) No 1272/2008 (CLP)	Specific Conc. Limits	REACH Registration No.
acetone	67-64-1 200-662-2 606-001-00-8	25-50	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066		01-2119471330-49
isobutane [C, S]	75-28-5 200-857-2 601-004-01-8	10-20	Flam. Gas 1; H220 Press. Gas; H280		-
n-butyl acetate	123-86-4 204-658-1 607-025-00-1	10-20	Flam. Liq. 3; H226 STOT SE 3; H336 EUH066		01-2119485493-29
butane [C]	106-97-8 203-448-7 601-004-00-0	2,5-10	Flam. Gas 1; H220 Press. Gas; H280		-
propane	74-98-6 200-827-9 601-003-00-5	2,5-10	Flam. Gas 1; H220 Press. Gas; H280		-
xylene [C]	1330-20-7 215-535-7 601-022-00-9	2,5-10	Flam. Liq. 3; H226 Acute Tox. 4; H312 Skin Irrit. 2; H315 Acute Tox. 4; H332		02-2119752448-30
trizinc bis(orthophosphate)	7779-90-0 231-944-3 030-011-00-6	0,1-1	Aquatic Acute 1; H400 Aquatic Chronic 1; H410		-
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700)	25068-38-6 500-033-5 603-074-00-8	0,1-1	Skin Irrit. 2; H315 Skin Sens. 1; H317 Eye Irrit. 2; H319 Aquatic Chronic 2; H411	Skin Irrit. 2; - H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 %	-

Notes for substances:

C	Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
S	This substance may not require a label according to Article 17 (see section 1.3 of Annex I) (Table 3.1). This substance may not require a label according to Article 23 of Directive 67/548/EEC (see section 8 of Annex VI to that Directive) (Table 3.2).

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

General notes

Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency.

Following inhalation

Remove patient to fresh air - move out of dangerous area. If victim is not breathing give artificial respiration. If symptoms develop and persist, seek medical attention.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **4110 Etch-prime**

Creation date: **1.3.2011** · Revision: **11.7.2018** · Version: **1**

Following skin contact

Take off all contaminated clothing. Wash affected skin areas thoroughly with plenty of water and soap. If symptoms develop and persist, seek medical attention.

Following eye contact

Immediately flush eyes with running water, keeping eyelids apart. Consult a physician immediately!

Following ingestion

Consult a physician. Show the physician the safety data sheet or label. Rinse mouth thoroughly with water. Do not induce vomiting without prior consultation with a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation

Vapours may cause drowsiness and dizziness.

Skin contact

Prolonged and repeated exposure may cause redness, itching and cracking of the skin in sensitive people.

Eye contact

Redness, tearing, pain.

Ingestion

Causes nausea/vomiting and diarrhoea.

4.3. Indication of any immediate medical attention and special treatment needed

-

SECTION 5. FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media

Foam.
Fire extinguishing powder.
Carbon dioxide (CO₂).

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

-

5.3. Advice for firefighters

Protective actions

Cool containers at risk with water spray. If possible remove containers from endangered area. Vapours can form explosive mixtures with air.

Special protective equipment for firefighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment

Use personal protective equipment (Section 8).

Emergency procedures

Ensure adequate ventilation. Keep away from sources of ignition and/or heat; No smoking!

6.1.2. For emergency responders

-

6.2. Environmental precautions

Do not allow product to reach water/drains/sewage systems or permeable soil.

6.3. Methods and material for containment and cleaning up

6.3.1. For containment

-

6.3.2. For cleaning up

Collect the spray cans and hand them over to an authorized waste disposal contractor. Absorb product (with inert material), collect it in special container and dispose it to a licensed hazardous-waste disposal contractor.

6.3.3. Other information

-

6.4. Reference to other sections

See also Sections 8 and 13.

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

7.1.1. Protective measures

Measures to prevent fire

Ensure adequate ventilation. Keep away from sources of ignition - no smoking. Use spark-proof tools. Take precautionary measures against static discharges. Pressurized container; protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray onto open flame or glowing body.

Measures to prevent aerosol and dust generation

-

Measures to protect the environment

-

7.1.2. Advice on general occupational hygiene

Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Avoid contact with skin and eyes. Do not breathe vapours/mist.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1. Technical measures and storage conditions

Keep in cool and well ventilated area. Protect from open fire, heat and direct sunlight. Keep away from food, drink and animal feeding stuffs.

7.2.2. Packaging materials

-

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **4110 Etch-prime**

Creation date: **1.3.2011** · Revision: **11.7.2018** · Version: **1**

7.2.3. Requirements for storage rooms and vessels

-

7.2.4. Storage class

-

7.2.5. Further information on storage conditions

-

7.3. Specific end use(s)

Recommendations

-

Industrial sector specific solutions

-

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

8.1.1. Occupational exposure limit values

Name (CAS)	Limit values		Short-term exposure limit		Remarks	Biological Tolerance Values
	ml/m ³ (ppm)	mg/m ³	ml/m ³ (ppm)	mg/m ³		
Acetone (67-64-1)	500	1210	1500	3620		
Butane (106-97-8)	600	1450	750	1810	Carc, (only applies if Butane contains more than 0.1% of buta-1,3-diene)	
Butyl acetate (123-86-4)	150	724	200	966		
Xylene, o-,m-,p- or mixed isomers (1330-20-7)	50	220	100	441	Sk, BMGV	650 mmol methyl hippuric acid/mol creatinine in urine - Post shift
xylene (1330-20-7)	100	440				

8.1.2. Information on monitoring procedures

BS EN 14042:2003 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 482:2012+A1:2015 Workplace exposure. General requirements for the performance of procedures for the measurement of chemical agents. BS EN 689:2018 Workplace exposure. Measurement of exposure by inhalation to chemical agents. Strategy for testing compliance with occupational exposure limit values.

8.1.3. DNEL/DMEL values

No information.

8.1.4. PNEC values

No information.

8.2. Exposure controls

8.2.1. Appropriate engineering control

Substance/mixture related measures to prevent exposure during identified uses

Use good personal hygiene practices – wash hands at breaks and when done working with material.

Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **4110 Etch-prime**

Creation date: **1.3.2011** · Revision: **11.7.2018** · Version: **1**

8.2.2. Personal protective equipment

Eye and face protection

Tight fitting protective goggles (EN 166).

Hand protection

Protective gloves (EN 374). Observe the manufacturer's instructions regarding the use, storage, maintenance and replacement of gloves. In case of damage or at the first signs of wear and tear, change the gloves immediately.

Appropriate materials

Material	Thickness	Penetration Time	Remark
Butyl rubber	0,7 mm	60 min	

Skin protection

Cotton protective clothing and shoes that cover the entire foot (EN ISO 20345).

Respiratory protection

At elevated concentrations of vapours/aerosols in the air wear a mask (EN 140) with filter A2-P2 (EN 14387).

Thermal hazards

-

8.2.3. Environmental exposure controls

-

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

-	Physical state:	liquid
-	Colour:	according to specification
-	Odour:	like acetone

Important health, safety and environmental information

-	pH	No information.
-	Melting point/freezing point	No information.
-	Initial boiling point/boiling range	> 35 °C
-	Flash point	> 0 °C
-	Evaporation rate	No information.
-	Flammability (solid, gas)	> 200 °C
-	Explosion limits (vol%)	No information.
-	Vapour pressure	No information.
-	Vapour density	No information.
-	Density	Density: 0,79 g/cm ³ at 20 °C
-	Solubility	No information.
-	Partition coefficient	No information.
-	Auto-ignition temperature	No information.
-	Decomposition temperature	No information.
-	Viscosity	No information.
-	Explosive properties	Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.
-	Oxidising properties	No information.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **4110 Etch-prime**

Creation date: **1.3.2011** · Revision: **11.7.2018** · Version: **1**

9.2. Other information

-	Weight organic solvents	83,2 %
-	Remarks:	

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity

-

10.2. Chemical stability

Product is stable under normal conditions of use, recommended handling and storage conditions.

10.3. Possibility of hazardous reactions

-

10.4. Conditions to avoid

Protect from heat, direct sunlight, open fire, sparks.

10.5. Incompatible materials

Strong acids. Strong oxidising agents.

10.6. Hazardous decomposition products

Under normal use conditions no hazardous decomposition products are expected. In case of fire/explosion vapours/gases that pose a health hazard are released.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

(a) Acute toxicity

Name	Exposure route	Type	Species	Time	Value	Method	Remark
acetone (67-64-1)	oral	LD ₅₀	rat		5800 mg/kg		
acetone (67-64-1)	dermal	LD ₅₀	rabbit		20000 mg/kg		
acetone (67-64-1)	inhalation	LC ₅₀	rat	4 h	76 mg/l		
isobutane (75-28-5)	inhalation	LC ₅₀	rat	4 h	= 658 mg/l		Literature study
n-butyl acetate (123-86-4)	oral	LD ₅₀	rat		13100 mg/kg		
n-butyl acetate (123-86-4)	dermal	LD ₅₀	rabbit		> 5000 mg/kg		
n-butyl acetate (123-86-4)	inhalation	LC ₅₀	rat	4 h	> 21 mg/l		
butane (106-97-8)	inhalation	LC ₅₀	rat	4 h	658 mg/l		Literature study
propane (74-98-6)	inhalation	LC ₅₀	rat	4 h	513 mg/l		Literature study
xylene (1330-20-7)	oral	LD ₅₀	rat		4300 mg/kg		
xylene (1330-20-7)	dermal	LD ₅₀	rabbit		2000 mg/kg		
xylene (1330-20-7)	inhalation	LC ₅₀	rat	4 h	21,7 mg/l		
trizinc bis(orthophosphate) (7779-90-0)	oral	LD ₅₀	rat		> 5000 mg/kg		

(b) Skin corrosion/irritation

No information.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **4110 Etch-prime**

Creation date: **1.3.2011** · Revision: **11.7.2018** · Version: **1**

(c) Serious eye damage/irritation

Additional information: Irritating to eyes.

(d) Respiratory or skin sensitisation

No information.

(e) (Germ cell) mutagenicity

No information.

(f) Carcinogenicity

No information.

(g) Reproductive toxicity

No information.

Summary of evaluation of the CMR properties

No information.

(h) STOT-single exposure

No information.

(i) STOT-repeated exposure

No information.

(j) Aspiration hazard

No information.

SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Acute (short-term) toxicity

For components

Substance (CAS Nr.)	Type	Value	Exposure time	Species	Organism	Method	Remark
acetone (67-64-1)	EC ₅₀	8800 mg/L	48 h	crustacea			
xylene (1330-20-7)	EC ₅₀	165 mg/L	48 h	crustacea			

12.1.2. Chronic (long-term) toxicity

No information.

12.2. Persistence and degradability

12.2.1. Abiotic degradation, physical- and photo-chemical elimination

No information.

12.2.2. Biodegradation

No information.

12.3. Bioaccumulative potential

12.3.1. Partition coefficient

No information.

12.3.2. Bioconcentration factor (BCF)

No information.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **4110 Etch-prime**

Creation date: **1.3.2011** · Revision: **11.7.2018** · Version: **1**

12.4. Mobility in soil

12.4.1. Known or predicted distribution to environmental compartments

No information.

12.4.2. Surface tension

No information.

12.4.3. Adsorption/Desorption

No information.

12.5. Results of PBT and vPvB assessment

No evaluation.

12.6. Other adverse effects

No information.

12.7. Additional information

For product

Do not allow to reach ground water, water courses or sewage system.

Water hazard class 2 (self-assessment): hazardous for water.

Danger to drinking water if even small quantities leak into ground water.

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

13.1.1. Product / Packaging disposal

Waste chemical

Recycle or dispose according to official regulations: to leave it to authorized collector/remover/transformer of hazardous waste.

Waste codes / waste designations according to LoW

16 05 04* - gases in pressure containers (including halons) containing dangerous substances

Packaging

Deliver completely emptied containers to approved waste disposal authorities.

Waste codes / waste designations according to LoW

15 01 04 - metallic packaging

13.1.2. Waste treatment-relevant information

-

13.1.3. Sewage disposal-relevant information

-

13.1.4. Other disposal recommendations

-

SECTION 14. TRANSPORT INFORMATION

14.1. UN number

UN 1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

2



SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **4110 Etch-prime**

Creation date: **1.3.2011** · Revision: **11.7.2018** · Version: **1**

14.4. Packing group

Not applicable.

14.5. Environmental hazards

NO.

14.6. Special precautions for user

Limited quantities

1 L

Tunnel restriction code

(D)

IMDG flashpoint

0 °C, c.c.

IMDG EmS

F-D, S-U

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Goods may not be carried in bulk in bulk containers, containers or vehicles.

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (including last amendment Commission Regulation (EU) 2015/830)
- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

15.1.1. Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-guideline)

EU limit values and category: B(e) 840 g/l. VOC Content: 656 g/l

15.2. Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16. OTHER INFORMATION

Indication of changes

-

Abbreviations and acronyms

ATE - Acute Toxicity Estimate
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
CEN - European Committee for Standardisation
C&L - Classification and Labelling
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
CAS# - Chemical Abstracts Service number
CMR - Carcinogen, Mutagen, or Reproductive Toxicant
CSA - Chemical Safety Assessment
CSR - Chemical Safety Report
DMEL - Derived Minimal Effect Level
DNEL - Derived No Effect Level
DPD - Dangerous Preparations Directive 1999/45/EC
DSD - Dangerous Substances Directive 67/548/EEC
DU - Downstream User

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **4110 Etch-prime**

Creation date: **1.3.2011** · Revision: **11.7.2018** · Version: **1**

EC - European Community
ECHA - European Chemicals Agency
EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS)
EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway)
EEC - European Economic Community
EINECS - European Inventory of Existing Commercial Substances
ELINCS - European List of notified Chemical Substances
EN - European Standard
EQS - Environmental Quality Standard
EU - European Union
Euphrac - European Phrase Catalogue
EWC - European Waste Catalogue (replaced by LoW – see below)
GES - Generic Exposure Scenario
GHS - Globally Harmonized System
IATA - International Air Transport Association
ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG - International Maritime Dangerous Goods
IMSBC - International Maritime Solid Bulk Cargoes
IT - Information Technology
IUCLID - International Uniform Chemical Information Database
IUPAC - International Union for Pure Applied Chemistry
JRC - Joint Research Centre
Kow - octanol-water partition coefficient
LC₅₀ - Lethal Concentration to 50 % of a test population
LD₅₀ - Lethal Dose to 50% of a test population (Median Lethal Dose)
LE - Legal Entity
LoW - List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)
LR - Lead Registrant
M/I - Manufacturer / Importer
MS - Member States
MSDS - Material Safety Data Sheet
OC - Operational Conditions
OECD - Organization for Economic Co-operation and Development
OEL - Occupational Exposure Limit
OJ - Official Journal
OR - Only Representative
OSHA - European Agency for Safety and Health at work
PBT - Persistent, Bioaccumulative and Toxic substance
PEC - Predicted Effect Concentration
PNEC(s) - Predicted No Effect Concentration(s)
PPE - Personal Protection Equipment
(Q)SAR - Qualitative Structure Activity Relationship
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
RIP - REACH Implementation Project
RMM - Risk Management Measure
SCBA - Self-Contained Breathing Apparatus
SDS - Safety data sheet
SIEF - Substance Information Exchange Forum
SME - Small and Medium sized Enterprises
STOT - Specific Target Organ Toxicity
(STOT) RE - Repeated Exposure
(STOT) SE - Single Exposure
SVHC - Substances of Very High Concern
UN - United Nations
vPvB - Very Persistent and Very Bioaccumulative

Key literature references and sources for data

-

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **4110 Etch-prime**

Creation date: **1.3.2011** · Revision: **11.7.2018** · Version: **1**

List of relevant H phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.



- ☒ Provided correct labelling of the product
- ☒ Compliance with the local legislation
- ☒ Provided correct classification of the product
- ☒ Provided adequate transport data

© BENS Consulting | www.bens-consulting.com

The information of this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under Section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.