

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **4540 Rust Solvent MoS2**

Creation date: **10.8.2008** · Revision: **27.6.2018** · Version: **1**

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name

4540 Rust Solvent MoS2



chemius.net/WYA12

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Rust Remover Spray.

Uses advised against

No information.

1.3. Details of the supplier of the safety data sheet

Manufacturer

SILCO, D.O.O.

Address: Šentrupert 5 a, 3303 Gomilsko, Slovenia

Phone: +386 3 703 3180

Fax: +386 3 703 3188

E-mail: n.cvilak@silco-automotive.com

Point of contact for safety info: Nejc Cvilak

1.4. Emergency telephone number

Emergency

112

Supplier

+386 3 703 3180

SECTION 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Aerosol 1; H222 Extremely flammable aerosol.

Aerosol 1; H229 Pressurised container: May burst if heated.

Asp. Tox. 1; H304 May be fatal if swallowed and enters airways.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: 4540 Rust Solvent MoS2

Creation date: 10.8.2008 · Revision: 27.6.2018 · Version: 1

2.2 Label elements

2.2.1. Labelling according to Regulation (EC) No 1272/2008 [CLP]



Signal word: **Danger**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

EUH066 Repeated exposure may cause skin dryness or cracking.

P251 Do not pierce or burn, even after use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P501 Dispose of contents/container in accordance with national regulation.

2.2.2. Contains:

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics (EC: 918-481-9)

distillates (petroleum), hydrotreated light naphthenic (CAS: 64742-53-6, EC: 265-156-6, Index: 649-466-00-2)

2.2.3. Special provisions

Vapours and air can at inadequate ventilation form an explosive mixture.

2.3. Other hazards

No information.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Product description

Substances: >30% aliphatic hydrocarbons; 5 % or over but less than 15 %: aromatic hydrocarbons

3.1. Substances

For mixtures see 3.2.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: 4540 Rust Solvent MoS2

Creation date: 10.8.2008 · Revision: 27.6.2018 · Version: 1

3.2. Mixtures

Name	CAS EC Index	%	Classification according to Regulation (EC) No 1272/2008 (CLP)	Specific Conc. Limits	REACH Registration No.
hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics	- 918-481-9 -	25-50	Asp. Tox. 1; H304 EUH066		01-2119457273-39
isobutane [C, S]	75-28-5 200-857-2 601-004-00-0	20-25	Flam. Gas 1; H220 Press. Gas; H280		01-2119485395-27
distillates (petroleum), hydrotreated light naphthenic [L]	64742-53-6 265-156-6 649-466-00-2	10-20	Asp. Tox. 1; H304		01-2119480375-34
propane	74-98-6 200-827-9 601-003-00-5	10-20	Flam. Gas 1; H220 Press. Gas; H280		01-2119486944-21
butane [C]	106-97-8 203-448-7 601-004-00-0	2,5-10	Flam. Gas 1; H220 Press. Gas; H280		01-2119474691-32
2-butoxyethanol	111-76-2 203-905-0 603-014-00-0	1-2,5	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute Tox. 4; H332		01-2119475108-36

Notes for substances:

C	Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
L	The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 "Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method", Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.
S	This substance may not require a label according to Article 17 (see section 1.3 of Annex I) (Table 3.1). This substance may not require a label according to Article 23 of Directive 67/548/EEC (see section 8 of Annex VI to that Directive) (Table 3.2).

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

General notes

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency.

Following inhalation

Leave contaminated area - breathe fresh air. If symptoms develop and persist, seek medical attention.

Following skin contact

Immediately remove contaminated clothing. Wash affected skin areas thoroughly with plenty of water and soap. If symptoms develop and persist, seek medical attention.

Following eye contact

Immediately flush eyes with running water, keeping eyelids apart. If irritation persists, seek professional medical attention.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **4540 Rust Solvent MoS2**

Creation date: **10.8.2008** · Revision: **27.6.2018** · Version: **1**

Following ingestion

Do not induce vomiting! Immediately consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation

Vapours are narcotic.
Coughing, sneezing, nasal discharge, labored breathing.
Intoxication, vertigo, headache, nausea.

Skin contact

Prolonged and repeated exposure may cause redness, itching and cracking of the skin in sensitive people.
Dermatitis.
Repeated exposure may cause dry skin or cracked skin.

Eye contact

Contact with eyes can cause irritation (redness, tearing, pain).

Ingestion

Aspiration into the lungs causes coughing, shortness of breath and may lead to chemical pneumonia.

4.3. Indication of any immediate medical attention and special treatment needed

-

SECTION 5. FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂).
Fire extinguishing powder.
Foam.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

In case of a fire toxic gases can be generated; do not inhale gases/smoke.

5.3. Advice for firefighters

Protective actions

In case of fire or heating do not breathe fumes/vapours. Prolonged heating can cause an explosion. Vapours are heavier than air and spread along floor. Vapours may form explosive mixtures with the air. Cool the endangered containers with water spray.

Special protective equipment for firefighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

Additional information

Contaminated firefighting water must be disposed of in accordance with the regulations; do not allow to reach the sewage system.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment

Use personal protective equipment (Section 8).

Emergency procedures

Keep away from sources of ignition and/or heat; No smoking! Ensure adequate ventilation. Prevent access to unprotected personnel. Do not breathe vapour or mist.

6.1.2. For emergency responders

Use personal protective equipment.

6.2. Environmental precautions

Do not allow product to reach water/drains/sewage systems or permeable soil. If accidental large entry into water or ground occurs, inform responsible authorities.

6.3. Methods and material for containment and cleaning up

6.3.1. For containment

-

6.3.2. For cleaning up

Collect the spray cans and hand them over to an authorized waste disposal contractor. Absorb product (with inert material), collect it in special container and dispose it to a licensed hazardous-waste disposal contractor.

6.3.3. Other information

-

6.4. Reference to other sections

See also Sections 8 and 13.

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

7.1.1. Protective measures

Measures to prevent fire

Ensure adequate ventilation. Keep away from sources of ignition - no smoking. Protect from open fire and other sources of ignition or heat. Pressurized container; protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Take precautionary measures against static discharges. Use spark-proof tools. Vapours and air form explosive mixtures. Do not spray on a naked flame or incandescent material.

Measures to prevent aerosol and dust generation

Ensure good ventilation and extraction.

Measures to protect the environment

-

7.1.2. Advice on general occupational hygiene

Use good personal hygiene practices – wash hands at breaks and when done working with material. Refer to instructions on label and regulations for safety and health at work. Do not eat, drink or smoke while working. Avoid contact with skin and eyes. Do not breathe vapours/mist.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: 4540 Rust Solvent MoS2

Creation date: 10.8.2008 · Revision: 27.6.2018 · Version: 1

7.2. Conditions for safe storage, including any incompatibilities

7.2.1. Technical measures and storage conditions

Keep in well closed containers. Do not store in hallways and/or staircases. Do not expose to sun and temperatures exceeding 50°C. Keep container in a well ventilated place. Keep away from food, drink and animal feeding stuffs. Follow safe storage practices for packed compressed gas as described by the Compressed Gas Association or the relevant agency in the country where the product is used.

7.2.2. Packaging materials

-

7.2.3. Requirements for storage rooms and vessels

Keep only in original container.

7.2.4. Storage class

-

7.2.5. Further information on storage conditions

-

7.3. Specific end use(s)

Recommendations

-

Industrial sector specific solutions

-

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

8.1.1. Occupational exposure limit values

Name (CAS)	Limit values		Short-term exposure limit		Remarks	Biological Tolerance Values
	ml/m ³ (ppm)	mg/m ³	ml/m ³ (ppm)	mg/m ³		
Butane (106-97-8)	600	1450	750	1810	Carc, (only applies if Butane contains more than 0.1% of buta-1,3-diene)	
2-Butoxyethanol (111-76-2)	25	123	50	246	Sk, BMGV	240 mmol butoxyacetic acid/mol creatinine in urine - Post shift

8.1.2. Information on monitoring procedures

BS EN 14042:2003 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 482:2012+A1:2015 Workplace exposure. General requirements for the performance of procedures for the measurement of chemical agents. BS EN 689:2018 Workplace exposure. Measurement of exposure by inhalation to chemical agents. Strategy for testing compliance with occupational exposure limit values.

8.1.3. DNEL/DMEL values

No information.

8.1.4. PNEC values

No information.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: 4540 Rust Solvent MoS2

Creation date: 10.8.2008 · Revision: 27.6.2018 · Version: 1

8.2. Exposure controls

8.2.1. Appropriate engineering control

Substance/mixture related measures to prevent exposure during identified uses

Use good personal hygiene practices – wash hands at breaks and when done working with material. Avoid contact with eyes and skin. Do not breathe vapours/aerosols. Do not eat, drink or smoke while working. Keep away from foodstuffs, beverages and feed.

Organisational measures to prevent exposure

Remove all contaminated clothes immediately and wash them before reuse.

Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration.

8.2.2. Personal protective equipment

Eye and face protection

Tight fitting protective goggles (EN 166).

Hand protection

Protective gloves (EN 374). Observe the manufacturer's instructions regarding the use, storage, maintenance and replacement of gloves. In case of damage or at the first signs of wear and tear, change the gloves immediately.

Appropriate materials

Material	Thickness	Penetration Time	Remark
Nitrile	≥ 0,45 mm	≥ 240 min	

Skin protection

Cotton protective clothing and shoes that cover the entire foot (EN ISO 20345).

Respiratory protection

Not needed under normal use and adequate ventilation. In case of insufficient ventilation wear suitable respiratory protection. In case of insufficient ventilation wear mask with filter AX (EN 14387). In case of intensive or longer exposure use self-contained breathing apparatus (EN 137).

Thermal hazards

-

8.2.3. Environmental exposure controls

-

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

-	Physical state:	liquid
-	Colour:	yellowish
-	Odour:	solvent like

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: 4540 Rust Solvent MoS2

Creation date: 10.8.2008 · Revision: 27.6.2018 · Version: 1

Important health, safety and environmental information

-	pH	No information.
-	Melting point/freezing point	No information.
-	Initial boiling point/boiling range	No information.
-	Flash point	No information.
-	Evaporation rate	No information.
-	Flammability (solid, gas)	> 200 °C
-	Explosion limits (vol%)	No information.
-	Vapour pressure	No information.
-	Vapour density	No information.
-	Density	Density: 0,69291 g/cm ³ at 20 °C
-	Solubility	Water: Insoluble
-	Partition coefficient	No information.
-	Auto-ignition temperature	No information.
-	Decomposition temperature	No information.
-	Viscosity	No information.
-	Explosive properties	Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.
-	Oxidising properties	No information.

9.2. Other information

-	Weight organic solvents	85,5 %
-	Remarks:	Vapour pressure: 7,1 at 50 °C

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity

-

10.2. Chemical stability

Product is stable under normal conditions of use, recommended handling and storage conditions.

10.3. Possibility of hazardous reactions

The product is stable under recommended storage and handling conditions.

10.4. Conditions to avoid

No special precautions required. Consider the directions for use and storage. Protect from heat, direct sunlight, open fire, sparks.

10.5. Incompatible materials

-

10.6. Hazardous decomposition products

Under normal use conditions no hazardous decomposition products are expected. In case of fire/explosion vapours/gases that pose a health hazard are released.

Aldehydes. Carbon dioxide; Carbon monoxide.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: 4540 Rust Solvent MoS2

Creation date: 10.8.2008 · Revision: 27.6.2018 · Version: 1

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

(a) Acute toxicity

Name	Exposure route	Type	Species	Time	Value	Method	Remark
For product	oral	LD ₅₀	rat		75999 mg/kg		ATE
For product	dermal	LD ₅₀	rabbit		20540 mg/kg		ATE
For product	inhalation	LC ₅₀		4 h	125 mg/l		ATE
hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics (-)	oral	LD ₅₀	rat		> 2000 mg/kg		
hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics (-)	dermal	LD ₅₀	rat		> 2000 mg/kg		
isobutane (75-28-5)	inhalation	LC ₅₀	rat	4 h	> 50 mg/l		
propane (74-98-6)	inhalation	LC ₅₀	rat	4 h	20 mg/l		
butane (106-97-8)	inhalation	LC ₅₀	rat	4 h	658 mg/l		
2-butoxyethanol (111-76-2)	oral	LD ₅₀	rat		1480 mg/kg		
2-butoxyethanol (111-76-2)	dermal	LD ₅₀	rabbit		400 mg/kg		
2-butoxyethanol (111-76-2)	inhalation	LC ₅₀		4 h	11 mg/l		ATEi

(b) Skin corrosion/irritation

Additional information: May cause skin irritation.

(c) Serious eye damage/irritation

No information.

(d) Respiratory or skin sensitisation

No information.

(e) (Germ cell) mutagenicity

No information.

(f) Carcinogenicity

No information.

(g) Reproductive toxicity

No information.

Summary of evaluation of the CMR properties

No information.

(h) STOT-single exposure

No information.

(i) STOT-repeated exposure

Additional information: Repeated exposure may cause skin dryness or cracking.

(j) Aspiration hazard

No information.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: 4540 Rust Solvent MoS2

Creation date: 10.8.2008 · Revision: 27.6.2018 · Version: 1

SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Acute (short-term) toxicity

For components

Substance (CAS Nr.)	Type	Value	Exposure time	Species	Organism	Method	Remark
hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics (-)	EC ₅₀	> 1000 mg/L	48 h	<i>Daphnia</i>			

12.1.2. Chronic (long-term) toxicity

No information.

12.2. Persistence and degradability

12.2.1. Abiotic degradation, physical- and photo-chemical elimination

No information.

12.2.2. Biodegradation

No information.

12.3. Bioaccumulative potential

12.3.1. Partition coefficient

No information.

12.3.2. Bioconcentration factor (BCF)

No information.

12.4. Mobility in soil

12.4.1. Known or predicted distribution to environmental compartments

No information.

12.4.2. Surface tension

No information.

12.4.3. Adsorption/Desorption

No information.

12.5. Results of PBT and vPvB assessment

No evaluation.

12.6. Other adverse effects

No information.

12.7. Additional information

For product

Water hazard class 1 (self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: 4540 Rust Solvent MoS2

Creation date: 10.8.2008 · Revision: 27.6.2018 · Version: 1

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

13.1.1. Product / Packaging disposal

Waste chemical

Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste. Do not dispose together with household garbage. Do not allow product to reach drains/sewage systems.

Waste codes / waste designations according to LoW

16 05 04* - gases in pressure containers (including halons) containing dangerous substances

Packaging

Deliver completely emptied containers to approved waste disposal authorities.

Waste codes / waste designations according to LoW

15 01 04 - metallic packaging

13.1.2. Waste treatment-relevant information

-

13.1.3. Sewage disposal-relevant information

-

13.1.4. Other disposal recommendations

-

SECTION 14. TRANSPORT INFORMATION

14.1. UN number

UN 1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

2

14.4. Packing group

Not applicable.

14.5. Environmental hazards

NO.

14.6. Special precautions for user

Limited quantities

1 L

Tunnel restriction code

(D)

IMDG EmS

F-D, S-U

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Goods may not be carried in bulk in bulk containers, containers or vehicles.



SAFETY DATA SHEET according to Regulation 1907/2006



Product name: 4540 Rust Solvent MoS2

Creation date: 10.8.2008 · Revision: 27.6.2018 · Version: 1

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (including last amendment Commission Regulation (EU) 2015/830)
- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

15.1.1. Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-guideline)

Not applicable.

15.1.2. Ingredients according to Regulation EC 648/2004 on detergents

≥ 30%: aliphatic hydrocarbons; < 5%: aromatic hydrocarbons

15.2. Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16. OTHER INFORMATION

Indication of changes

-

Abbreviations and acronyms

ATE - Acute Toxicity Estimate
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
CEN - European Committee for Standardisation
C&L - Classification and Labelling
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
CAS# - Chemical Abstracts Service number
CMR - Carcinogen, Mutagen, or Reproductive Toxicant
CSA - Chemical Safety Assessment
CSR - Chemical Safety Report
DMEL - Derived Minimal Effect Level
DNEL - Derived No Effect Level
DPD - Dangerous Preparations Directive 1999/45/EC
DSD - Dangerous Substances Directive 67/548/EEC
DU - Downstream User
EC - European Community
ECHA - European Chemicals Agency
EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS)
EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway)
EEC - European Economic Community
EINECS - European Inventory of Existing Commercial Substances
ELINCS - European List of notified Chemical Substances
EN - European Standard
EQS - Environmental Quality Standard
EU - European Union
Euphrac - European Phrase Catalogue
EWC - European Waste Catalogue (replaced by LoW – see below)
GES - Generic Exposure Scenario
GHS - Globally Harmonized System
IATA - International Air Transport Association
ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG - International Maritime Dangerous Goods
IMSBC - International Maritime Solid Bulk Cargoes
IT - Information Technology
IUCLID - International Uniform Chemical Information Database

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **4540 Rust Solvent MoS2**

Creation date: **10.8.2008** · Revision: **27.6.2018** · Version: **1**

IUPAC - International Union for Pure Applied Chemistry
JRC - Joint Research Centre
Kow - octanol-water partition coefficient
LC₅₀ - Lethal Concentration to 50 % of a test population
LD₅₀ - Lethal Dose to 50% of a test population (Median Lethal Dose)
LE - Legal Entity
LoW - List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)
LR - Lead Registrant
M/I - Manufacturer / Importer
MS - Member States
MSDS - Material Safety Data Sheet
OC - Operational Conditions
OECD - Organization for Economic Co-operation and Development
OEL - Occupational Exposure Limit
OJ - Official Journal
OR - Only Representative
OSHA - European Agency for Safety and Health at work
PBT - Persistent, Bioaccumulative and Toxic substance
PEC - Predicted Effect Concentration
PNEC(s) - Predicted No Effect Concentration(s)
PPE - Personal Protection Equipment
(Q)SAR - Qualitative Structure Activity Relationship
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
RIP - REACH Implementation Project
RMM - Risk Management Measure
SCBA - Self-Contained Breathing Apparatus
SDS - Safety data sheet
SIEF - Substance Information Exchange Forum
SME - Small and Medium sized Enterprises
STOT - Specific Target Organ Toxicity
(STOT) RE - Repeated Exposure
(STOT) SE - Single Exposure
SVHC - Substances of Very High Concern
UN - United Nations
vPvB - Very Persistent and Very Bioaccumulative

Key literature references and sources for data

-

List of relevant H phrases

H220 Extremely flammable gas.
H280 Contains gas under pressure; may explode if heated.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
EUH066 Repeated exposure may cause skin dryness or cracking.



- Provided correct labelling of the product
- Compliance with the local legislation
- Provided correct classification of the product
- Provided adequate transport data

© BENS Consulting | www.bens-consulting.com

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **4540 Rust Solvent MoS2**

Creation date: **10.8.2008** · Revision: **27.6.2018** · Version: **1**

The information of this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under Section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.