

### Description

One component adhesion promoter in aerosol for plastic substrates. Appropriate for most of the types of plastic being used in automotive industry like bumpers, trims etc.)




### Features & Benefits

Excellent adhesion.  
Slightly dyed for easier assessment of application.  
Quick drying.

### Substrate preparation

Clean, dry, and degrease the surface with a suitable anti-silicone cleaner. Eventually sand the surface with P600 grit and remove the dust thoroughly.

### Application data

	<p><b>Mixing ratio</b> The product is ready to use!</p>				
	<p><b>Application</b> Shake can thoroughly until the mixing balls move freely (3 min). Number of coats: 2 coats Spraying distance: 20 - 25 cm Flash-off: 3 - 5 min Dry film thickness: 1 - 2 microns After spraying turn the can upside down and spray until the valve is clean. It is strongly recommended that ready to use products are applied at a temperature higher than 15 °C/59 °F.</p>				
	<p><b>Drying</b></p> <table data-bbox="454 1635 1029 1736"> <tbody> <tr> <td>Touch dry (20 °C/68 °F)</td> <td>10 - 15 min</td> </tr> <tr> <td>Recoatable (20 °C/68 °F)</td> <td>15 - 20 min</td> </tr> </tbody> </table>	Touch dry (20 °C/68 °F)	10 - 15 min	Recoatable (20 °C/68 °F)	15 - 20 min
Touch dry (20 °C/68 °F)	10 - 15 min				
Recoatable (20 °C/68 °F)	15 - 20 min				
Prod. Nr.	Description	Volume	Packaging Box		
4940	Transparent/ Silver	400 ml	12		

### VOC

2004/42/II B(e) (840) <840

### Shelf life

Min. 60 months from the production date under normal storage conditions and unopened can.

### Additional Information

#### FOR PROFESSIONAL USE ONLY!

Always read the instructions.

**IMPORTANT:** This product contains hazardous substances at work so it is necessary to always use/wear appropriate protective equipment. For further instructions, check the label on the product and safety data sheet. A person who uses the product for any purpose other than recommended in this technical data sheet, acts at his own risk. It is the user's responsibility to take all necessary steps to fulfil the local legislation.

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public.

Information and methods described are based on the best information and practices known to us and serve merely as guidelines for optimal use, without liability to performance, results or fitness for any intended use. We do not accept any responsibility for the behaviour of the product or damage arising from the use of the product. Before using the product, the user must check if this is the latest version.

All products mentioned in this data sheet are trademarks owned by Silco.