

Description

One-component, permanently elastic sealing and bonding mastic based on the newest generation of high-quality hybrid polymers.

Features & Benefits

- three different applications: bonding, brush application
- excellent reproduction of all original structures
- strong adhesion to almost every surface (steel, galvanized steel, Al, plastic etc.) without any primer
- fast curing under the influence of air humidity
- silicone, isocyanate, solvents free
- UV resistant; over paintable wet-on-wet

Technical Properties

- cartridge 290 ml
- packing 12 pcs / box
- storing conditions (dark and dry, between 5 °C/41 °F and 25 °C/77 °F)
- colors: white, grey, black

Application

Clean surfaces completely of grease, dust and dirt. Good bonding can be reached on a high number of varnishing systems, metals, glass, mirror, ceramic and on several plastics. According to the high number of different undergrounds, bond tests should be performed beforehand.

Apply the material with a proper dispensing system and use it within the skin formation time. The amount of used material should be adapted to the max. strength and movement of the gaps. A fixing of the bonding until curing is recommended. The curing depends on the thickness, the temperature and humidity.

Shelf life

Min. 15 months from the production date under normal storage conditions and unopened can.

Additional Information

FOR PROFESSIONAL USE ONLY!

IMPORTANT: Products described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public.

Information and methods described are based on the best information and practices known to us and serve merely as guidelines for optimal use, without liability to performance, results or fitness for any intended use. We do not accept any responsibility for the behaviour of the product or damage arising from the use of the product. Before using the product, the user must check if this is the latest version.

All products mentioned in this data sheet are trademarks owned by Silco.