Technical Data Sheet



5090 Cleaner - Activator

Ver.: 2020-1

Description

Surface Cleaner/Activator. It is used to clean and at the same time to prepare the substrate (painted surface, ceramic coating on windshield) for the application of Silco Fast 30.

Features & Benefits

- can be used as cleaning agent and adhesion promotor for PU sealants, hybrid sealants (MS or SPUR) or silicones
- transparent
- extremely low viscosity

Substrate preparation

Surfaces to be treated must be clean, dry and grease-free.

Application data



Mixing ratio

The product is ready to use!

Thoroughly shake the bottle before use!

Application

Apply with application brush (Prod. Nr. 5701) in the temperature range between $15 \, ^{\circ}\text{C/59} \, ^{\circ}\text{F}$ and $30 \, ^{\circ}\text{C/86} \, ^{\circ}\text{F}$ and wiped just after evaporation of the solvent i.e. 30 to 60 seconds after application.

Close the bottle immediately after use because this product is very sensitive to humidity.

Drying time



Drying time at 20 °C/68 °F: 30 s

Sealant application: within 10-60 min

Prod. Nr.	Description	Volume	Packaging Box
5090-0,03	transparent	30 ml	2
5090-0,25	transparent	250 ml	1

SILCO d.o.o., Šentrupert 5a, 3303 Gomilsko, Slovenija	
Tel.: +386 (0)3 703 31 80 / Fax.: +386 (0)3 703 31 88	Page 1
E-mail: info@silco-automotive.com / www.silco-automotive.com	

Technical Data Sheet



5090 Cleaner - Activator

Ver.: 2020-1

Shelf life

Min. 12 months from the production date under normal storage conditions at temperature between 5°C and 30 °C/86 °F and unopened cartridge.

Max 1 month after first opening in the original hermetically sealed packaging between 5 °C/41 °F and 30 °C/86 °F.

Additional Information

FOR PROFESSIONAL USE ONLY!

Always read the instructions.

IMPORTANT: This product contains hazardous substances at work so it is necessary to always use/wear appropriate protective equipment. For further instructions, check the label on the product and safety data sheet. A person who uses the product for any purpose other than recommended in this technical data sheet, acts at his own risk. It is the user's responsibility to take all necessary steps to fulfil the local legislation.

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public.

Information and methods described are based on the best information and practices known to us and serve merely as guidelines for optimal use, without liability to performance, results or fitness for any intended use. We do not accept any responsibility for the behaviour of the product or damage arising from the use of the product. Before using the product, the user must check if this is the latest version.

All products mentioned in this data sheet are trademarks owned by Silco.