Product name: 6055 Fade Out Spray Creation date: 25.2.2013 · Revision: 13.11.2018 · Version: 1

# SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

## 1.1. Product identifier

Product name

## 6055 Fade Out Spray

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Thinner.

Uses advised against

No information.

## 1.3. Details of the supplier of the safety data sheet

#### <u>Manufacturer</u>

SILCO, D.O.O. Address: Šentrupert 5 a, 3303 Gomilsko, Slovenia Phone: +386 3 703 3180 Fax: +386 3 703 3188 E-mail: n.cvilak@silco-automotive.com Point of contact for safety info: Nejc Cvilak

#### 1.4. Emergency telephone number

Emergency

112

<u>Supplier</u>

+386 3 703 3180

## SECTION 2. HAZARDS IDENTIFICATION

## 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Aerosol 1; H222 Extremely flammable aerosol. Aerosol 1; H229 Pressurised container: May burst if heated.

STOT SE 3; H336 May cause drowsiness or dizziness.



chemius.net/DI344



Product name: 6055 Fade Out Spray Creation date: 25.2.2013 · Revision: 13.11.2018 · Version: 1



#### 2.2 Label elements

2.2.1. Labelling according to Regulation (EC) No 1272/2008 [CLP]



#### Signal word: Danger

- H222 Extremely flammable aerosol.
- H229 Pressurised container: May burst if heated.
- H336 May cause drowsiness or dizziness.
- EUH066 Repeated exposure may cause skin dryness or cracking.
- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P260 Do not breathe spray.
- P410 + P412 Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122°F.
- P501 Dispose of contents/container in accordance with national regulation.

#### 2.2.2. Contains:

n-butyl acetate (CAS: 123-86-4, EC: 204-658-1, Index: 607-025-00-1)

#### 2.2.3. Special provisions

Without adequate ventilation, explosive vapors may accumulate.

#### 2.3. Other hazards

No information.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Product description

Mineral oils contain <0,1 % benzene.

#### 3.1. Substances

For mixtures see 3.2.

#### 3.2. Mixtures

Name CAS % EC Index		%	Classification according to Regulation (EC) No 1272/2008 (CLP)	Specific Conc. Limits	REACH Registration No.		
dimethyl ether 115-10-6 50-<75 204-065-8 603-019-00-8		50-<75	Flam. Gas 1; H220 Press. Gas; H280		01-2119472128-37		
n-butyl acetate	123-86-4 204-658-1 607-025-00-1	20-<25	Flam. Liq. 3; H226 STOT SE 3; H336 EUH066		01-2119485493-29		
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7	12,5-<20	Flam. Liq. 3; H226		01-2119475791-29		



## SECTION 4. FIRST AID MEASURES

## 4.1. Description of first aid measures

#### <u>General notes</u>

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency.

#### Following inhalation

Remove patient to fresh air - move out of dangerous area. If symptoms develop and persist, seek medical attention.

#### Following skin contact

Take off all contaminated clothing. Areas of the body that have come into contact with the product must be rinsed with water. If symptoms develop and persist, seek medical attention. Wash contaminated clothes and shoes before reuse.

#### Following eye contact

Immediately flush eyes with running water, keeping eyelids apart. If irritation persists, seek professional medical attention.

#### Following ingestion

Do not induce vomiting without prior consultation with a doctor. Remove to fresh air. Drink plenty of water in small sips. Consult a physician. Show the physician the safety data sheet or label.

#### 4.2. Most important symptoms and effects, both acute and delayed

#### Inhalation

Vapours may cause drowsiness and dizziness. Excessive exposure to spray mist, fog, or vapours may cause respiratory irritation. Coughing, sneezing, nasal discharge, labored breathing.

#### Skin contact

Contact with skin may cause irritation (redness, itching).

## Eye contact

Contact with eyes can cause irritation (redness, tearing, pain).

#### Ingestion

May cause abdominal discomfort. May cause nausea/vomiting and diarrhea. Irritates mucous membranes in the mouth, throat, esophagus and in gastrointestinal area.

#### 4.3. Indication of any immediate medical attention and special treatment needed

## SECTION 5. FIREFIGHTING MEASURES

#### 5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO<sub>2</sub>).

```
Fire extinguishing powder.
```

Water spray. Extinguish large fires with water spray or alcohol-resistant foam. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

#### Unsuitable extinguishing media

Water. Full water jet.

#### 5.2. Special hazards arising from the substance or mixture

### Hazardous combustion products

In case of a fire toxic gases can be generated; do not inhale gases/smoke. In the event of fire the following can be generated: carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>).



#### 5.3. Advice for firefighters

#### Protective actions

In case of fire do not breathe fumes/gases. No action shall be taken involving any personal risk or without suitable training. Prolonged heating can cause an explosion. Cool containers at risk with water spray. If possible remove containers from endangered area.

#### Special protective equipment for firefighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

#### **Protective equipment**

Use personal protective equipment (Section 8). Use personal safety breathing equipment.

#### Emergency procedures

Ensure adequate ventilation. Keep away from sources of ignition and/or heat; No smoking! Prevent access to unprotected personnel. Prevent access to unauthorised personnel. Avoid contact with skin and eyes. Do not breathe vapour or mist.

#### 6.1.2. For emergency responders

Use personal protective equipment.

#### 6.2. Environmental precautions

Do not allow product to reach water/drains/sewage systems or permeable soil. If accidental large entry into water or ground occurs, inform responsible authorities.

#### 6.3. Methods and material for containment and cleaning up

#### 6.3.1. For containment

Stem the spill if this does not pose risks.

#### 6.3.2. For cleaning up

Ventilate the permises. Collect the spray cans and hand them over to an authorized waste disposal contractor. Large spill: Absorb product (with inert material), collect it in special container and dispose it to a licensed hazardous-waste disposal contractor. Dispose in accordance with applicable regulations (see Section 13).

#### 6.3.3. Other information

#### 6.4. Reference to other sections

See also Sections 8 and 13.

## SECTION 7. HANDLING AND STORAGE

#### 7.1. Precautions for safe handling

#### 7.1.1. Protective measures

#### Measures to prevent fire

Ensure adequate ventilation. Keep away from sources of ignition - no smoking. Use spark-proof tools. Take precautionary measures against static discharges. Protect from open fire and other sources of ignition or heat. Vapours and air form explosive mixtures.

#### Measures to prevent aerosol and dust generation

Ensure good ventilation and extraction.

#### Measures to protect the environment

-

#### Product name: 6055 Fade Out Spray

Creation date: 25.2.2013 · Revision: 13.11.2018 · Version: 1



## 7.1.2. Advice on general occupational hygiene

Wear suitable protective equipment; see Section 8. Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Avoid contact with skin and eyes. Do not breathe vapours/mist.

#### 7.2. Conditions for safe storage, including any incompatibilities

## 7.2.1. Technical measures and storage conditions

Store in accordance with local regulations. Keep in well closed containers. Keep in cool and well ventilated area. Protect from open fire, heat and direct sunlight. Keep away from food, drink and animal feeding stuffs.

#### 7.2.2. Packaging materials

#### 7.2.3. Requirements for storage rooms and vessels

Do not store in unlabelled containers.

7.2.4. Storage class

7.2.5. Further information on storage conditions

## 7.3. Specific end use(s)

Recommendations

Industrial sector specific solutions

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1. Control parameters

8.1.1. Occupational exposure limit values

Name (CAS)	Limit values		Short-term exposure limit		Remarks	<b>Biological Tolerance Values</b>
	ml/m <sup>3</sup> (ppm)	mg/m <sup>3</sup>	ml/m <sup>3</sup> (ppm)	mg/m <sup>3</sup>		
Butyl acetate (123-86-4)	150	724	200	966		
Dimethyl ether (115-10-6)	400	766	500	958		
1-Methoxypropyl acetate (108-65-6)	50	274	100	548	Sk	

### 8.1.2. Information on monitoring procedures

BS EN 14042:2003 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 482:2012+A1:2015 Workplace exposure. General requirements for the performance of procedures for the measurement of chemical agents. BS EN 689:2018 Workplace exposure. Measurement of exposure by inhalation to chemical agents. Strategy for testing compliance with occupational exposure limit values.

#### 8.1.3. DNEL/DMEL values

No information.

### 8.1.4. PNEC values

No information.

#### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering control

#### Substance/mixture related measures to prevent exposure during identified uses

Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Avoid contact with eyes and skin. Do not breathe vapours/aerosols.



#### Organisational measures to prevent exposure

Remove all contaminated clothes immediately and wash them before reuse.

#### Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration. Keep away from food, drink and animal feeding stuffs.

#### 8.2.2. Personal protective equipment

#### Eye and face protection

No requirements under normal use conditions.

#### Hand protection

Use chemical resistant gloves classified according to standard EN 374. Observe the manufacturer's instructions regarding the use, storage, maintenance and replacement of gloves. In case of damage or at the first signs of wear and tear, change the gloves immediately. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. The product consists of various substances, therefore the resistance of gloves can not be calculated and has to be tested before use. The penetration time is determined by the protective glove manufacturer and must be observed.

#### Appropriate materials

Material	Thickness	Penetration Time	Remark
Butyl rubber	≥ 0,4 mm	480 min	acetone
Butyl rubber	≥ 0,4 mm	60 min	n-butyl acetate
Butyl rubber	≥ 0,4 mm	170 min	ethyl acetate
Butyl rubber	≥ 0,4 mm	42 min	xylene

#### Skin protection

Cotton protective clothing and shoes that cover the entire foot (EN ISO 20345).

#### **Respiratory protection**

Not needed under normal use and adequate ventilation. In case of insufficient ventilation wear suitable respiratory protection. In case of insufficient ventilation wear mask with filter AX (EN 14387). 'High/elevated concentrations' means that the occupational exposure limit values have been exceeded. In case of intensive or longer exposure use self-contained breathing apparatus (EN 137).

#### Thermal hazards

#### 8.2.3. Environmental exposure controls

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1. Information on basic physical and chemical properties

-	Physical state:	liquid; aerosol
-	Colour:	according to specification
-	Odour:	characteristic



Important health, safety and environmental information

-	рН	No information.						
•	Melting point/freezing point	No information.						
-	Initial boiling point/boiling range	No information.						
-	Flash point	No information.						
-	Evaporation rate	No information.						
-	Flammability (solid, gas)	No information.						
-	Explosion limits (vol%)	1,2 – 18,6 vol %						
-	Vapour pressure	5200 hPa at 20 °C						
-	Vapour density	No information.						
-	Density	Density: 0,76 g/cm <sup>3</sup> at 20 °C						
-	Solubility	Water: insoluble						
-	Partition coefficient	No information.						
•	Auto-ignition temperature	235 °C						
-	Decomposition temperature	No information.						
-	Viscosity	No information.						
-	Explosive properties	No information.						
	Oxidising properties	No information.						

#### 9.2. Other information

-	Weight organic solvents	99 %
-	Solid contents	1,4 %
-	Remarks:	

## SECTION 10. STABILITY AND REACTIVITY

#### 10.1. Reactivity

No data available.

#### 10.2. Chemical stability

Product is stable under normal conditions of use, recommended handling and storage conditions.

## 10.3. Possibility of hazardous reactions

There are no known hazardous reactions.

#### 10.4. Conditions to avoid

Protect from heat, direct sunlight, open fire, sparks.

## 10.5. Incompatible materials

Not known.

#### 10.6. Hazardous decomposition products

Under normal use conditions no hazardous decomposition products are expected. In case of fire/explosion vapours/gases that pose a health hazard are released.

Product name: 6055 Fade Out Spray Creation date: 25.2.2013 · Revision: 13.11.2018 · Version: 1



## SECTION 11. TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

(a) Acute toxicity

Name	Exposure route	Туре	Species	Time	Value	Method	Remark	
n-butyl acetate (123-86-4)	inhalation	$LC_{50}$	rat	4 h	23,4 mg/l	OECD 403		
n-butyl acetate (123-86-4)	oral	$LD_{50}$	rat		10800 mg/kg			
n-butyl acetate (123-86-4)	dermal	$LD_{50}$	rabbit		> 17600 mg/kg			
2-methoxy-1-methylethyl acetate (108-65-6)	oral	$LD_{50}$	rat		8530 mg/kg			
2-methoxy-1-methylethyl acetate (108-65-6)	dermal	$LD_{50}$	rabbit		> 5000 mg/kg			
2-methoxy-1-methylethyl acetate (108-65-6)	inhalation	$LC_{50}$	rat	4 h	> 10000 mg/m <sup>3</sup>			
Additional information: The product is not classified for acute toxicity.								

(b) Skin corrosion/irritation

Additional information: The product is not classified as irritating to skin and eyes.

(c) Serious eye damage/irritation

No information.

(d) Respiratory or skin sensitisation

Additional information: The product is not classified as sensitising.

(e) (Germ cell) mutagenicity

No information.

(f) Carcinogenicity

No information.

(g) Reproductive toxicity

No information.

Summary of evaluation of the CMR properties

The product is not classified as carcinogenic, mutagenic or toxic for reproduction.

(h) STOT-single exposure

Additional information: May cause drowsiness or dizziness.

(i) STOT-repeated exposure

Additional information: STOT RE (repeated exposure): Not classified.

(j) Aspiration hazard

Additional information: Aspiration hazard: Not classified.

Product name: 6055 Fade Out Spray Creation date: 25.2.2013 · Revision: 13.11.2018 · Version: 1



## SECTION 12. ECOLOGICAL INFORMATION

### 12.1. Toxicity

### 12.1.1. Acute (short-term) toxicity

For components

Substance (CAS Nr.)	Туре	Value	Exposure time	Species	Organism	Method	Remark
dimethyl ether (115-10-6)		155 mg/L	96 h	algae			
	$LC_{50}$	> 4000 mg/L	48 h	Daphnia			
	$LC_{50}$	> 4000 mg/L	96 h	fish			
2-methoxy-1-methylethyl acetate (108-65-6)	$EC_{50}$	> 500 mg/L	48 h	Daphnia			
	$LC_{50}$	100 – 180 mg/L	96 h	fish	Oncorhynchus mykiss		

### 12.1.2. Chronic (long-term) toxicity

No information.

## 12.2. Persistence and degradability

12.2.1. Abiotic degradation, physical- and photo-chemical elimination

No information.

### 12.2.2. Biodegradation

No information.

#### 12.3. Bioaccumulative potential

## 12.3.1. Partition coefficient

No information.

## 12.3.2. Bioconcentration factor (BCF)

No information.

### 12.4. Mobility in soil

### 12.4.1. Known or predicted distribution to environmental compartments

No information.

### 12.4.2. Surface tension

No information.

### 12.4.3. Adsorption/Desorption

No information.

## 12.5. Results of PBT and vPvB assessment

No evaluation.

#### 12.6. Other adverse effects

No information.

#### 12.7. Additional information

### For product

Water hazard class 1 (self-assessment): slightly hazardous for water. Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

Product name: 6055 Fade Out Spray Creation date: 25.2.2013 · Revision: 13.11.2018 · Version: 1



## **SECTION 13. DISPOSAL CONSIDERATIONS**

#### 13.1. Waste treatment methods

13.1.1. Product / Packaging disposal

#### Waste chemical

Do not dispose together with household garbage. Do not allow product to reach drains/sewage systems. Dispose of in accordance with applicable waste disposal regulation. Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste.

#### Waste codes / waste designations according to LoW

08 01 11\* - waste paint and varnish containing organic solvents or other dangerous substances

#### Packaging

Cleaned uncontaminated packaging may be taken for recycling. Dispose of in accordance with applicable waste disposal regulation. Deliver completely emptied containers to approved waste disposal authorities.

#### Waste codes / waste designations according to LoW

15 01 04 - metallic packaging

#### 13.1.2. Waste treatment-relevant information

#### 13.1.3. Sewage disposal-relevant information

#### 13.1.4. Other disposal recommendations

## **SECTION 14. TRANSPORT INFORMATION**

#### 14.1. UN number

UN 1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

2

14.4. Packing group

Not applicable.

14.5. Environmental hazards

NO.

- 14.6. Special precautions for user
  - Limited quantities

1 L

**Tunnel restriction code** 

(D)

#### IMDG EmS

F-D, S-U

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Goods may not be carried in bulk in bulk containers, containers or vehicles.



Product name: 6055 Fade Out Spray Creation date: 25.2.2013 · Revision: 13.11.2018 · Version: 1



## SECTION 15. REGULATORY INFORMATION

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (including last amendment Commission Regulation (EU) 2015/830)

- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

# 15.1.1. Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-guideline)

Not applicable.

15.1.2. Special instructions

Seveso III, P3a: flammable aerosols.

#### 15.2. Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## SECTION 16. OTHER INFORMATION

Indication of changes

-

#### Abbreviations and acronyms

- ATE Acute Toxicity Estimate
- ADR European Agreement concerning the International Carriage of Dangerous Goods by Road
- ADN European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
- CEN European Committee for Standardisation
- C&L Classification and Labelling
- CLP Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
- CAS# Chemical Abstracts Service number
- CMR Carcinogen, Mutagen, or Reproductive Toxicant
- CSA Chemical Safety Assessment
- CSR Chemical Safety Report
- DMEL Derived Minimal Effect Level
- DNEL Derived No Effect Level
- DPD Dangerous Preparations Directive 1999/45/EC
- DSD Dangerous Substances Directive 67/548/EEC
- DU Downstream User
- EC European Community
- ECHA European Chemicals Agency
- EC-Number EINECS and ELINCS Number (see also EINECS and ELINCS)
- EEA European Economic Area (EU + Iceland, Liechtenstein and Norway)
- EEC European Economic Community
- EINECS European Inventory of Existing Commercial Substances
- ELINCS European List of notified Chemical Substances
- EN European Standard
- EQS Environmental Quality Standard
- EU European Union
- Euphrac European Phrase Catalogue
- EWC European Waste Catalogue (replaced by LoW see below)
- GES Generic Exposure Scenario
- GHS Globally Harmonized System
- IATA International Air Transport Association
- ICAO-TI Technical Instructions for the Safe Transport of Dangerous Goods by Air
- IMDG International Maritime Dangerous Goods
- IMSBC International Maritime Solid Bulk Cargoes
- IT Information Technology
- IUCLID International Uniform Chemical Information Database

Product name: 6055 Fade Out Spray Creation date: 25.2.2013 · Revision: 13.11.2018 · Version: 1




IUPAC - International Union for Pure Applied Chemistry JRC - Joint Research Centre Kow - octanol-water partition coefficient LC50 - Lethal Concentration to 50 % of a test population LD<sub>50</sub> - Lethal Dose to 50% of a test population (Median Lethal Dose) LE - Legal Entity LoW - List of Wastes (see http://ec.europa.eu/environment/waste/framework/list.htm) LR - Lead Registrant M/I - Manufacturer / Importer MS - Member States MSDS - Material Safety Data Sheet **OC** - Operational Conditions OECD - Organization for Economic Co-operation and Development **OEL - Occupational Exposure Limit** OJ - Official Journal **OR** - Only Representative OSHA - European Agency for Safety and Health at work PBT - Persistent, Bioaccumulative and Toxic substance PEC - Predicted Effect Concentration PNEC(s) - Predicted No Effect Concentration(s) PPE - Personal Protection Equipment (Q)SAR - Qualitative Structure Activity Relationship REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006 RID - Regulations concerning the International Carriage of Dangerous Goods by Rail **RIP - REACH Implementation Project** RMM - Risk Management Measure SCBA - Self-Contained Breathing Apparatus SDS - Safety data sheet SIEF - Substance Information Exchange Forum SME - Small and Medium sized Enterprises STOT - Specific Target Organ Toxicity (STOT) RE - Repeated Exposure (STOT) SE - Single Exposure SVHC - Substances of Very High Concern **UN - United Nations** vPvB - Very Persistent and Very Bioaccumulative

Key literature references and sources for data

List of relevant H phrases

- H220 Extremely flammable gas.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.



### Product name: 6055 Fade Out Spray Creation date: 25.2.2013 · Revision: 13.11.2018 · Version: 1



The information of this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under Section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.