

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **6065 Polyester Putty Hardener**

Creation date: **25.2.2013** · Revision: **12.8.2019** · Version: **1**

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name

6065 Polyester Putty Hardener



chemius.net/DVBf2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Hardener

Uses advised against

No information.

1.3. Details of the supplier of the safety data sheet

Manufacturer

SILCO, D.O.O.

Address: Šentrupert 5 a, 3303 Gomilsko, Slovenia

Phone: +386 3 703 3180

Fax: +386 3 703 3188

E-mail: n.cvilak@silco-automotive.com

Point of contact for safety info: Nejc Cvilak

1.4. Emergency telephone number

Emergency

112

Supplier

+386 3 703 3180

SECTION 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Org. Perox. EF; H242 Heating may cause a fire.

Skin Sens. 1; H317 May cause an allergic skin reaction.

Eye Irrit. 2; H319 Causes serious eye irritation.

Aquatic Acute 1; H400 Very toxic to aquatic life.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **6065 Polyester Putty Hardener**

Creation date: **25.2.2013** · Revision: **12.8.2019** · Version: **1**

2.2 Label elements

2.2.1. Labelling according to Regulation (EC) No 1272/2008 [CLP]



Signal word: **Warning**

H242 Heating may cause a fire.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H400 Very toxic to aquatic life.

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P411 + P235 Store at temperatures not exceeding 30 °C. Keep cool.

P501 Dispose of contents/container in accordance with national regulation.

2.2.2. Contains:

dibenzoyl peroxide (CAS: 94-36-0, EC: 202-327-6, Index: 617-008-00-0)

2.2.3. Special provisions

Special hazards are not known or expected.

2.3. Other hazards

No information.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

For mixtures see 3.2.

3.2. Mixtures

Name	CAS EC Index	%	Classification according to Regulation (EC) No 1272/2008 (CLP)	Specific Conc. Limits	REACH Registration No.
dibenzoyl peroxide	94-36-0 202-327-6 617-008-00-0	45-52	Org. Perox. B; H241 Skin Sens. 1; H317 Eye Irrit. 2; H319 Aquatic Acute 1; H400		01-2119511472-50
Dimethyl phthalate	131-11-3 205-011-6 -	25-35	not classified		01-2119437229-36

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

General notes

Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **6065 Polyester Putty Hardener**

Creation date: **25.2.2013** · Revision: **12.8.2019** · Version: **1**

Following inhalation

Remove patient to fresh air - move out of dangerous area. If symptoms occur, seek medical advice.

Following skin contact

Take off all contaminated clothing. Wash affected skin areas thoroughly with plenty of water and soap. If symptoms persist seek medical attention.

Following eye contact

Immediately flush eyes with running water, keeping eyelids apart. If irritation does not stop, seek professional medical treatment!

Following ingestion

Do not induce vomiting! Rinse mouth thoroughly with water. Immediately consult a doctor. Show the physician the safety data sheet or label.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation

Excessive exposure to spray mist, fog, or vapours may cause respiratory irritation.

Skin contact

Causes irritation of mucous membrane.

May cause sensitisation by skin contact (symptoms: itching, redness, rashes).

Eye contact

Redness, tearing, pain.

Ingestion

Irritates mucous membranes in the mouth, throat, esophagus and in gastrointestinal area.

4.3. Indication of any immediate medical attention and special treatment needed

-

SECTION 5. FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media

Fire extinguishing powder.

Carbon dioxide (CO₂).

Water spray. Extinguish large fires with water spray or alcohol-resistant foam. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

In the event of fire the following can be generated: carbon monoxide (CO), carbon dioxide (CO₂). Benzoic acid, benzene, fenil benzoat;

5.3. Advice for firefighters

Protective actions

In case of fire or heating do not breathe fumes/vapours. Cool containers at risk with water spray. If possible remove containers from endangered area.

Special protective equipment for firefighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **6065 Polyester Putty Hardener**

Creation date: **25.2.2013** · Revision: **12.8.2019** · Version: **1**

Additional information

Contaminated firefighting water must be disposed of in accordance with the regulations; do not allow to reach the sewage system.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment

Use personal protective equipment (Section 8).

Emergency procedures

Ensure adequate ventilation. Keep away from sources of ignition and/or heat; No smoking! Prevent access to unprotected personnel. Prevent access to unauthorised personnel. Do not use open fire and keep away all sources of ignition.

6.1.2. For emergency responders

-

6.2. Environmental precautions

Do not allow product to reach water/drains/sewage systems or permeable soil. If accidental large entry into water or ground occurs, inform responsible authorities.

6.3. Methods and material for containment and cleaning up

6.3.1. For containment

-

6.3.2. For cleaning up

Take up mechanically and collect in suitable container and dispose according to current regulations.

6.3.3. Other information

-

6.4. Reference to other sections

See also Sections 8 and 13.

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

7.1.1. Protective measures

Measures to prevent fire

Ensure adequate ventilation. Keep away from sources of ignition - no smoking. Use spark-proof tools. Take precautionary measures against static discharges. Protect from open fire and other sources of ignition or heat.

Measures to prevent aerosol and dust generation

-

Measures to protect the environment

-

7.1.2. Advice on general occupational hygiene

Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Avoid contact with skin and eyes. Do not breathe vapours/mist.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **6065 Polyester Putty Hardener**

Creation date: **25.2.2013** · Revision: **12.8.2019** · Version: **1**

7.2. Conditions for safe storage, including any incompatibilities

7.2.1. Technical measures and storage conditions

Keep in cool and well ventilated area. Protect from open fire, heat and direct sunlight. Keep away from food, drink and animal feeding stuffs. Store below 30°C. Keep in tightly closed container. Keep away from reducing agents. Do not store together with heavy metals. Keep away from acids. Keep away from bases.

7.2.2. Packaging materials

-

7.2.3. Requirements for storage rooms and vessels

-

7.2.4. Storage class

-

7.2.5. Further information on storage conditions

-

7.3. Specific end use(s)

Recommendations

-

Industrial sector specific solutions

-

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

8.1.1. Occupational exposure limit values

Name (CAS)	Limit values		Short-term exposure limit		Remarks	Biological Tolerance Values
	ml/m ³ (ppm)	mg/m ³	ml/m ³ (ppm)	mg/m ³		
Dibenzoyl peroxide (94-36-0)	-	5	-	-		
Dimethyl phthalate (131-11-3)	-	5	-	10		

8.1.2. Information on monitoring procedures

BS EN 14042:2003 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 482:2012+A1:2015 Workplace exposure. General requirements for the performance of procedures for the measurement of chemical agents. BS EN 689:2018 Workplace exposure. Measurement of exposure by inhalation to chemical agents. Strategy for testing compliance with occupational exposure limit values.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **6065 Polyester Putty Hardener**

Creation date: **25.2.2013** · Revision: **12.8.2019** · Version: **1**

8.1.3. DNEL/DMEL values

For components

Name	Type	Exposure route	Exposure frequency	Value	Remark
dibenzoyl peroxide (94-36-0)	Consumer	oral	long term (systemic effects)	1,65 mg/kg	
dibenzoyl peroxide (94-36-0)	Consumer	dermal	long term (systemic effects)	3,3 mg/kg	
dibenzoyl peroxide (94-36-0)	Worker	dermal	long term (systemic effects)	6,6 mg/kg	
dibenzoyl peroxide (94-36-0)	Consumer	inhalation	long term (systemic effects)	2,9 mg/m ³	
dibenzoyl peroxide (94-36-0)	Worker	inhalation	long term (systemic effects)	11,75 mg/m ³	
Dimethyl phthalate (131-11-3)	Consumer	oral	long term (systemic effects)	25 mg/kg	
Dimethyl phthalate (131-11-3)	Consumer	dermal	long term (systemic effects)	60 mg/kg	
Dimethyl phthalate (131-11-3)	Worker	dermal	long term (systemic effects)	100 mg/kg	
Dimethyl phthalate (131-11-3)	Consumer	inhalation	long term (systemic effects)	86,96 mg/m ³	
Dimethyl phthalate (131-11-3)	Worker	inhalation	long term (systemic effects)	293,86 mg/m ³	

8.1.4. PNEC values

For components

Name	Exposure route	Value	Remark
dibenzoyl peroxide (94-36-0)	water treatment plant	0,35 mg/L	
dibenzoyl peroxide (94-36-0)	fresh water sediment	0,338 mg/kg	
dibenzoyl peroxide (94-36-0)	marine water sediment	0,0338 mg/kg	
dibenzoyl peroxide (94-36-0)	soil	0,0758 mg/kg	
dibenzoyl peroxide (94-36-0)	fresh water	0,602 mg/L	
dibenzoyl peroxide (94-36-0)	water, intermittent release	0,602 mg/L	
dibenzoyl peroxide (94-36-0)	marine water	0,0602 mg/L	
Dimethyl phthalate (131-11-3)	water treatment plant	4 mg/L	
Dimethyl phthalate (131-11-3)	fresh water sediment	1,403 mg/kg	
Dimethyl phthalate (131-11-3)	fresh water	0,192 mg/L	
Dimethyl phthalate (131-11-3)	water, intermittent release	0,39 mg/L	
Dimethyl phthalate (131-11-3)	marine water	0,0192 mg/L	

8.2. Exposure controls

8.2.1. Appropriate engineering control

Substance/mixture related measures to prevent exposure during identified uses

Use good personal hygiene practices – wash hands at breaks and when done working with material. Avoid contact with eyes and skin. Do not breathe vapours/aerosols. Keep away from direct sun-light or other heat sources and sources of ignition. Handle in accordance with good industrial hygiene and safety practice.

Organisational measures to prevent exposure

Remove all contaminated clothes immediately and wash them before reuse.

Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration.

8.2.2. Personal protective equipment

Eye and face protection

Safety glasses with side protection (EN 166).

Hand protection

Protective gloves (EN 374). Observe the manufacturer's instructions regarding the use, storage, maintenance and replacement of gloves. In case of damage or at the first signs of wear and tear, change the gloves immediately. The penetration time is determined by the protective glove manufacturer and must be observed.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: 6065 Polyester Putty Hardener

Creation date: 25.2.2013 · Revision: 12.8.2019 · Version: 1

Appropriate materials

Material	Thickness	Penetration Time	Remark
Nitrile			
Neoprene			

Skin protection

Cotton protective clothing and shoes that cover the entire foot (EN ISO 20345).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory protection.

Thermal hazards

-

8.2.3. Environmental exposure controls

-

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

- Physical state:	solid
- Colour:	according to specification
- Odour:	characteristic

Important health, safety and environmental information

- pH	No information.
- Melting point/freezing point	No information.
- Initial boiling point/boiling range	No information.
- Flash point	> 60 °C
- Evaporation rate	No information.
- Flammability (solid, gas)	No information.
- Explosion limits (vol%)	No information.
- Vapour pressure	No information.
- Vapour density	No information.
- Density	Density: 1,1 g/cm ³ at 20 °C
- Solubility	Water: Insoluble
- Partition coefficient	No information.
- Auto-ignition temperature	No information.
- Decomposition temperature	50 °C
- Viscosity	No information.
- Explosive properties	No information.
- Oxidising properties	No information.

9.2. Other information

- Remarks:	
------------	--

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **6065 Polyester Putty Hardener**
Creation date: **25.2.2013** · Revision: **12.8.2019** · Version: **1**

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity

-

10.2. Chemical stability

Product is stable under normal conditions of use, recommended handling and storage conditions.

10.3. Possibility of hazardous reactions

-

10.4. Conditions to avoid

Protect from heat, direct sunlight, open fire, sparks. SADT=50°C Do not store above 50°C.

10.5. Incompatible materials

Heavy metals.
Strong acids. Accelerators;
Strong bases.
Oxidants. Reducing agents.

10.6. Hazardous decomposition products

Under normal use conditions no hazardous decomposition products are expected. In case of fire/explosion vapours/gases that pose a health hazard are released. Benzoic acid, benzene, fenil benzoat;

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

(a) Acute toxicity

Name	Exposure route	Type	Species	Time	Value	Method	Remark
dibenzoyl peroxide (94-36-0)	oral	LD ₅₀	rat		5000 mg/kg		
dibenzoyl peroxide (94-36-0)	inhalation	LC ₅₀	rat	4 h	24,3 mg/l		vapour
Dimethyl phthalate (131-11-3)	oral	LD ₅₀	rat		2400 mg/kg		
Dimethyl phthalate (131-11-3)	dermal	LD ₅₀	rabbit		10000 mg/kg		
Dimethyl phthalate (131-11-3)	inhalation	LC ₅₀		4 h	9300 mg/l		vapour

(b) Skin corrosion/irritation

No information.

(c) Serious eye damage/irritation

Name	Species	Time	Result	Method	Remark
For product			Irritating to eyes.		

(d) Respiratory or skin sensitisation

Name	Exposure route	Species	Time	Result	Method	Remark
For product	dermal			Sensitizing.		

(e) (Germ cell) mutagenicity

No information.

(f) Carcinogenicity

No information.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **6065 Polyester Putty Hardener**

Creation date: **25.2.2013** · Revision: **12.8.2019** · Version: **1**

(g) Reproductive toxicity

No information.

Summary of evaluation of the CMR properties

No information.

(h) STOT-single exposure

No information.

(i) STOT-repeated exposure

No information.

(j) Aspiration hazard

No information.

SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Acute (short-term) toxicity

For components

Substance (CAS Nr.)	Type	Value	Exposure time	Species	Organism	Method	Remark
dibenzoyl peroxide (94-36-0)	EC ₅₀	0,11 mg/L	48 h	daphnia	<i>Daphnia magna</i>	202 (Daphnia sp. Acute Immobilisation Test)	
	ErC ₅₀	0,0711 mg/L	72 h	algae	<i>Pseudokirchneriella subcapitata</i>	OECD Guideline 201 (Alga, Growth Inhibition Test)	
	LC ₅₀	0,0602 mg/L	96 h	fish	<i>Oncorhynchus mykiss</i>	OECD Guideline 203 (Fish, Acute Toxicity Test)	
Dimethyl phthalate (131-11-3)	LC ₅₀	39 mg/L	96 h	fish			
	ErC ₅₀	259,76 mg/L	72 h	algae			
	LC ₅₀	52 mg/L	48 h	daphnia			

12.1.2. Chronic (long-term) toxicity

No information.

12.2. Persistence and degradability

12.2.1. Abiotic degradation, physical- and photo-chemical elimination

No information.

12.2.2. Biodegradation

For product

Type	Rate	Time	Evaluation	Method	Remark
aerobic			biodegradable		

For components

Substance (CAS Nr.)	Type	Rate	Time	Evaluation	Method	Remark
Dimethyl phthalate (131-11-3)	aerobic			readily biodegradable		

12.3. Bioaccumulative potential

12.3.1. Partition coefficient

No information.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **6065 Polyester Putty Hardener**

Creation date: **25.2.2013** · Revision: **12.8.2019** · Version: **1**

12.3.2. Bioconcentration factor (BCF)

No information.

12.4. Mobility in soil

12.4.1. Known or predicted distribution to environmental compartments

No information.

12.4.2. Surface tension

No information.

12.4.3. Adsorption/Desorption

No information.

12.5. Results of PBT and vPvB assessment

No evaluation.

12.6. Other adverse effects

No information.

12.7. Additional information

For product

Very toxic to aquatic organisms.

Water hazard class 1 (self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

13.1.1. Product / Packaging disposal

Waste chemical

Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste.

Packaging

Deliver completely emptied containers to approved waste disposal authorities.

13.1.2. Waste treatment-relevant information

-

13.1.3. Sewage disposal-relevant information

-

13.1.4. Other disposal recommendations

-

SECTION 14. TRANSPORT INFORMATION

14.1. UN number

UN 3108

14.2. UN proper shipping name

ORGANIC PEROXIDE TYPE E, SOLID (dibenzoyl peroxide)

14.3. Transport hazard class(es)

5.2



SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **6065 Polyester Putty Hardener**

Creation date: **25.2.2013** · Revision: **12.8.2019** · Version: **1**

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Additional labeling: ENVIRONMENTALLY HAZARDOUS

IMDG: MARINE POLLUTANT



14.6. Special precautions for user

Limited quantities

500 g

Tunnel restriction code

(D)

IMDG flashpoint

60 °C, c.c.

IMDG EmS

F-J, S-R

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Goods may not be carried in bulk in bulk containers, containers or vehicles.

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (including last amendment Commission Regulation (EU) 2015/830)

- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

15.1.1. Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-guideline)

Not applicable.

15.2. Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16. OTHER INFORMATION

Indication of changes

-

Abbreviations and acronyms

ATE - Acute Toxicity Estimate

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

CEN - European Committee for Standardisation

C&L - Classification and Labelling

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

CAS# - Chemical Abstracts Service number

CMR - Carcinogen, Mutagen, or Reproductive Toxicant

CSA - Chemical Safety Assessment

CSR - Chemical Safety Report

DMEL - Derived Minimal Effect Level

DNEL - Derived No Effect Level

DPD - Dangerous Preparations Directive 1999/45/EC

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **6065 Polyester Putty Hardener**

Creation date: **25.2.2013** · Revision: **12.8.2019** · Version: **1**

DSD - Dangerous Substances Directive 67/548/EEC
DU - Downstream User
EC - European Community
ECHA - European Chemicals Agency
EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS)
EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway)
EEC - European Economic Community
EINECS - European Inventory of Existing Commercial Substances
ELINCS - European List of notified Chemical Substances
EN - European Standard
EQS - Environmental Quality Standard
EU - European Union
Euphrac - European Phrase Catalogue
EWC - European Waste Catalogue (replaced by LoW – see below)
GES - Generic Exposure Scenario
GHS - Globally Harmonized System
IATA - International Air Transport Association
ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG - International Maritime Dangerous Goods
IMSBC - International Maritime Solid Bulk Cargoes
IT - Information Technology
IUCLID - International Uniform Chemical Information Database
IUPAC - International Union for Pure Applied Chemistry
JRC - Joint Research Centre
Kow - octanol-water partition coefficient
LC₅₀ - Lethal Concentration to 50 % of a test population
LD₅₀ - Lethal Dose to 50% of a test population (Median Lethal Dose)
LE - Legal Entity
LoW - List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)
LR - Lead Registrant
M/I - Manufacturer / Importer
MS - Member States
MSDS - Material Safety Data Sheet
OC - Operational Conditions
OECD - Organization for Economic Co-operation and Development
OEL - Occupational Exposure Limit
OJ - Official Journal
OR - Only Representative
OSHA - European Agency for Safety and Health at work
PBT - Persistent, Bioaccumulative and Toxic substance
PEC - Predicted Effect Concentration
PNEC(s) - Predicted No Effect Concentration(s)
PPE - Personal Protection Equipment
(Q)SAR - Qualitative Structure Activity Relationship
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
RIP - REACH Implementation Project
RMM - Risk Management Measure
SCBA - Self-Contained Breathing Apparatus
SDS - Safety data sheet
SIEF - Substance Information Exchange Forum
SME - Small and Medium sized Enterprises
STOT - Specific Target Organ Toxicity
(STOT) RE - Repeated Exposure
(STOT) SE - Single Exposure
SVHC - Substances of Very High Concern
UN - United Nations
vPvB - Very Persistent and Very Bioaccumulative

Key literature references and sources for data

-

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **6065 Polyester Putty Hardener**

Creation date: **25.2.2013** · Revision: **12.8.2019** · Version: **1**

List of relevant H phrases

- H241 Heating may cause a fire or explosion.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H400 Very toxic to aquatic life.



- Provided correct labelling of the product
- Compliance with the local legislation
- Provided correct classification of the product
- Provided adequate transport data

© BENS Consulting | www.bens-consulting.com

The information of this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under Section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.