Product name: 6075 Fade Out Spray Creation date: 10.9.2019 · Revision: 3.2.2021 · Version: 1

# SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product name

## 6075 Fade Out Spray

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Coating.

Uses advised against

No information.

### 1.3. Details of the supplier of the safety data sheet

### Manufacturer

SILCO, D.O.O. Address: Šentrupert 5 a, 3303 Gomilsko, Slovenia Phone: +386 3 703 3180 Fax: +386 3 703 3188 E-mail: n.cvilak@silco-automotive.com Point of contact for safety info: Nejc Cvilak

### 1.4. Emergency telephone number

112

+386 3 703 3180

## SECTION 2. HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Aerosol 1; H222 Extremely flammable aerosol. Aerosol 1; H229 Pressurised container: May burst if heated. Acute Tox. 4; H302 Harmful if swallowed. Skin Irrit. 2; H315 Causes skin irritation. Eye Dam. 1; H318 Causes serious eye damage. Acute Tox. 4; H332 Harmful if inhaled. STOT SE 3; H336 May cause drowsiness or dizziness.

chemius.net/iWo3d



Product name: 6075 Fade Out Spray Creation date: 10.9.2019 · Revision: 3.2.2021 · Version: 1



### 2.2 Label elements

2.2.1. Labelling according to Regulation (EC) No 1272/2008 [CLP]



Signal word: Danger

- H222 Extremely flammable aerosol.
- H229 Pressurised container: May burst if heated.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P261 Avoid breathing mist/vapours/spray.
- P301 + P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
- P302 + P352 IF ON SKIN: Wash with plenty of water.
- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER/doctor.
- P410 + P412 Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122°F.
- P501 Dispose of contents/container in accordance with national regulation.

### 2.2.2. Contains:

ethyl acetate (CAS: 141-78-6, EC: 205-500-4, Index: 607-022-00-5) cyclohexanone (CAS: 108-94-1, EC: 203-631-1, Index: 606-010-00-7) n-butyl acetate (CAS: 123-86-4, EC: 204-658-1, Index: 607-025-00-1) heptan-2-one (CAS: 110-43-0, EC: 203-767-1, Index: 606-024-00-3)

### 2.2.3. Special provisions

Vapours and air can at inadequate ventilation form an explosive mixture.

### 2.3. Other hazards

The substances in the mixture are not classified as persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB).

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substances

For mixtures see 3.2.

Product name: 6075 Fade Out Spray Creation date: 10.9.2019 · Revision: 3.2.2021 · Version: 1



### 3.2. Mixtures

Name	e CAS % Classification according to Regulation EC (EC) Index No 1272/2008 (CLP)		Specific Conc. Limits	REACH Registration No.	
dimethyl ether [U]	115-10-6 204-065-8 603-019-00-8	50-75	Flam. Gas 1; H220 Press. Gas; H280		01-2119472128-37
ethyl acetate	141-78-6 205-500-4 607-022-00-5	15-20	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066		01-2119475103-46
cyclohexanone	108-94-1 203-631-1 606-010-00-7	10-15	Flam. Liq. 3; H226 Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Dam. 1; H318 Acute Tox. 4; H332		01-2119453616-35
n-butyl acetate	123-86-4 204-658-1 607-025-00-1	0-5	5 Flam. Liq. 3; H226 STOT SE 3; H336		01-2119485493-29
heptan-2-one	110-43-0 203-767-1 606-024-00-3	0-5	Flam. Liq. 3; H226 Acute Tox. 4; H302 Acute Tox. 4; H332		-

### Notes for substances:

When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned:
Press. Gas (Comp.)
Press. Gas (Liq.)
Press. Gas (Ref. Liq.)
Press. Gas (Diss.)
Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

## **SECTION 4. FIRST AID MEASURES**

### 4.1. Description of first aid measures

### General notes

Take off all contaminated clothing immediately. When in doubt or if feeling unwell seek medical assistance. Show the safety data sheet and label to the physician. Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency.

#### Following inhalation

Remove patient to fresh air - move out of dangerous area. If symptoms develop and persist, seek medical attention.

### Following skin contact

Take off all contaminated clothing. Wash affected skin areas thoroughly with plenty of water and soap. If symptoms develop and persist, seek medical attention.

### Following eye contact

Immediately flush eyes with running water, keeping eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Consult a physician immediately!

### Following ingestion

Rinse mouth thoroughly with water. Do not induce vomiting without prior consultation with a doctor. Immediately consult a doctor. Show the physician the safety data sheet or label. Never give anything by mouth to an unconscious person.

Product name: 6075 Fade Out Spray Creation date: 10.9.2019 · Revision: 3.2.2021 · Version: 1



### 4.2. Most important symptoms and effects, both acute and delayed

### Inhalation

#### Harmful.

Excessive exposure to spray mist, fog, or vapours may cause respiratory irritation. Coughing, sneezing, nasal discharge, labored breathing. Vapours may cause drowsiness and dizziness. Symptoms include: headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, unconsciousness.

### Skin contact

Itching, redness, pain.

### Eye contact

On contact with eyes causes serious damage.

Redness, pain, burning sensation, tearing, can cause permanent damage to the eyes.

### Ingestion

Harmful to health. Irritates mucous membranes in the mouth, throat, esophagus and in gastrointestinal area. May cause abdominal discomfort. May cause nausea/vomiting and diarrhea.

### 4.3. Indication of any immediate medical attention and special treatment needed



## **SECTION 5. FIREFIGHTING MEASURES**

### 5.1. Extinguishing media

### Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

No special precautions required.

### 5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

In case of a fire toxic gases can be generated; do not inhale gases/smoke.

### 5.3. Advice for firefighters

### Protective actions

In case of fire or heating do not breathe fumes/vapours. Cool containers at risk with water spray. If possible remove containers from endangered area. Prolonged heating can cause an explosion. In case of fire aerosols can explode and be propelled to considerable distances in different directions.

### Special protective equipment for firefighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

## SECTION 6. ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

### **Protective equipment**

Use personal protective equipment (Section 8).

Product name: 6075 Fade Out Spray Creation date: 10.9.2019 · Revision: 3.2.2021 · Version: 1



### Emergency procedures

Ensure adequate ventilation. Keep away from sources of ignition and/or heat; No smoking! Do not use open fire and keep away all sources of ignition. Prevent access to unprotected personnel. Do not breathe vapour or mist. Avoid contact with skin, eyes and clothing. No action shall be taken involving any personal risk or without suitable training. Prevent access to unauthorised personnel.

### <u>6.1.2. For emergency responders</u>

Use personal protective equipment.

### 6.2. Environmental precautions

The product is an aerosol, which is why leakage of large amounts of product is not expected. If accidental large entry into water or ground occurs, inform responsible authorities.

### 6.3. Methods and material for containment and cleaning up

### 6.3.1. For containment

-

### 6.3.2. For cleaning up

Ventilate the premises. Use spark-proof tools. Collect the spray cans and hand them over to an authorized waste disposal contractor. Release of liquid because of damaged aerosol can (release of large quantities): Absorb product (with inert material), collect it in special container and dispose it to a licensed hazardous-waste disposal contractor. Use neutralizing agent. Dispose in accordance with applicable regulations (see Section 13).

### 6.3.3. Other information

See Section 7: safe handling.

### 6.4. Reference to other sections

See also Sections 8 and 13.

## SECTION 7. HANDLING AND STORAGE

#### 7.1. Precautions for safe handling

### 7.1.1. Protective measures

### Measures to prevent fire

Ensure adequate ventilation. Pressurized container; protect from sunlight and do not expose to tempratures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or incandescent material. Keep away from sources of ignition - no smoking. Take precautionary measures against static discharges. Use spark-proof tools. Do not pierce or burn container, not even after use.

#### Measures to prevent aerosol and dust generation

Use general or local exhaust ventilation to prevent inhaling vapours and aerosols.

### Measures to protect the environment

Avoid release to the environment.

### 7.1.2. Advice on general occupational hygiene

Do not breathe vapours/mist. Do not eat, drink or smoke while working. Avoid contact with skin, eyes and clothes. Wear suitable protective equipment; see Section 8. Use good personal hygiene practices – wash hands at breaks and when done working with material.

### 7.2. Conditions for safe storage, including any incompatibilities

### 7.2.1. Technical measures and storage conditions

Follow safe storage practices for packed compressed gas as described by the Compressed Gas Association or the relevant agency in the country where the product is used. Protect from open fire, heat and direct sunlight. Keep in cool and well ventilated area. Do not expose to sun and temperatures exceeding 50°C. Keep away from food, drink and animal feeding stuffs.

#### 7.2.2. Packaging materials

Store only in original container.

### Product name: 6075 Fade Out Spray Creation date: 10.9.2019 · Revision: 3.2.2021 · Version: 1



### 7.2.3. Requirements for storage rooms and vessels

Do not store in unlabelled containers. Close opened containers after use. Put the containers upright to prevent from leaking.

7.2.4. Storage class

7.2.5. Further information on storage conditions

### 7.3. Specific end use(s)

Recommendations

Industrial sector specific solutions

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

8.1.1. Occupational exposure limit values

Name (CAS)	Limit values		Short-term exposure limit		Remarks	Biological Tolerance Values
	ml/m <sup>3</sup> (ppm)	mg/m <sup>3</sup>	ml/m <sup>3</sup> (ppm)	mg/m <sup>3</sup>		
Heptan-2-one (110-43- 0)	50	237	100	475	Sk	
Ethyl acetate (141-78-6)	200	734	400	1468		
Dimethyl ether (115-10- 6)	400	766	500	958		
Butyl acetate (123-86-4)	150	724	200	966		
Cyclohexanone (108- 94-1)	10	41	20	82	Sk, BMGV	2 mmol cyclohexanol/mol creatinine in urine - Post shift

### 8.1.2. Information on monitoring procedures

BS EN 14042:2003 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 482:2012+A1:2015 Workplace exposure. General requirements for the performance of procedures for the measurement of chemical agents. BS EN 689:2018 Workplace exposure. Measurement of exposure by inhalation to chemical agents. Strategy for testing compliance with occupational exposure limit values.

### 8.1.3. DNEL/DMEL values

No information.

### 8.1.4. PNEC values

No information.

### 8.2. Exposure controls

### 8.2.1. Appropriate engineering control

### Substance/mixture related measures to prevent exposure during identified uses

Handle in accordance with good industrial hygiene and safety practice. Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Avoid contact with skin, eyes and clothes. Do not breathe vapours/aerosols.

### Organisational measures to prevent exposure

Remove all contaminated clothes immediately and wash them before reuse.

Product name: 6075 Fade Out Spray Creation date: 10.9.2019 · Revision: 3.2.2021 · Version: 1



### Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration. Keep away from food, drink and animal feeding stuffs.

### 8.2.2. Personal protective equipment

### Eye and face protection

Tight fitting protective goggles (EN 166).

### Hand protection

Protective gloves (EN 374). Use impermeable protective gloves, resistant to the product / substance / preparation. Observe the manufacturer's instructions regarding the use, storage, maintenance and replacement of gloves. In case of damage or at the first signs of wear and tear, change the gloves immediately. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. The penetration time is determined by the protective glove manufacturer and must be observed.

### Appropriate materials

Material	Thickness	Penetration Time	Remark
nitrile rubber			
Butyl rubber	0,7 mm	> 15 min	

#### Skin protection

Cotton protective clothing and shoes that cover the entire foot (EN ISO 20345).

### **Respiratory protection**

If the concentration limit values are exceeded, it is necessary to wear appropriate respiratory protection. Breathing mask with filter type A1P2.

### Thermal hazards

### 8.2.3. Environmental exposure controls

### Technical measures to prevent exposure

Do not allow product to reach drains, sewage systems or ground water.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

### 9.1. Information on basic physical and chemical properties

F	Physical state:	liquid; aerosol
-	Colour:	according to specification
-	Odour:	characteristic

Product name: 6075 Fade Out Spray Creation date: 10.9.2019 · Revision: 3.2.2021 · Version: 1



Important health, safety and environmental information

-	рН	No information.
-	Melting point/freezing point	No information.
-	Initial boiling point/boiling range	-24,9 °C
-	Flash point	< 0 °C (without propellant gas)
-	Evaporation rate	No information.
-	Flammability (solid, gas)	235 °C
-	Explosion limits (vol%)	3 – 18,6 vol %
-	Vapour pressure	3400 hPa at 20 °C
-	Vapour density	No information.
-	Density	No information.
-	Solubility	Water: insoluble
-	Partition coefficient	No information.
-	Auto-ignition temperature	Not self-igniting.
-	Decomposition temperature	No information.
-	Viscosity	No information.
-	Explosive properties	Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.
-	Oxidising properties	No information.

### 9.2. Other information

-	Weight organic solvents	94,4 % 94,37 % (VOC (EC))
-	Solid contents	14,1 %
-	Remarks:	

## SECTION 10. STABILITY AND REACTIVITY

### 10.1. Reactivity

Extremely flammable aerosol.

### 10.2. Chemical stability

Product is stable under normal conditions of use, recommended handling and storage conditions.

### 10.3. Possibility of hazardous reactions

Vapours and air can form flammable or explosive mixtures.

### 10.4. Conditions to avoid

Protect from heat, direct sunlight, open fire, sparks. Do not store above 50°C.

### 10.5. Incompatible materials

Oxidants.

### 10.6. Hazardous decomposition products

Under normal use conditions no hazardous decomposition products are expected. In case of fire/explosion vapours/gases that pose a health hazard are released.

Product name: 6075 Fade Out Spray Creation date: 10.9.2019 · Revision: 3.2.2021 · Version: 1



## SECTION 11. TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

(a) Acute toxicity

Additional information: Harmful if swallowed. Harmful if inhaled.

(b) Skin corrosion/irritation

Additional information: Causes skin irritation.

(c) Serious eye damage/irritation

### Additional information: Causes serious eye damage.

(d) Respiratory or skin sensitisation

Additional information: The product is not classified as sensitising.

(e) (Germ cell) mutagenicity

No information.

(f) Carcinogenicity

No information.

(g) Reproductive toxicity

No information.

Summary of evaluation of the CMR properties

The product is not classified as carcinogenic, mutagenic or toxic for reproduction.

(h) STOT-single exposure

Additional information: May cause drowsiness or dizziness.

(i) STOT-repeated exposure

Additional information: STOT RE (repeated exposure): Not classified.

(j) Aspiration hazard

Additional information: Aspiration hazard: Not classified.

## SECTION 12. ECOLOGICAL INFORMATION

### 12.1. Toxicity

12.1.1. Acute (short-term) toxicity

No information.

12.1.2. Chronic (long-term) toxicity

No information.

### 12.2. Persistence and degradability

12.2.1. Abiotic degradation, physical- and photo-chemical elimination

No information.

12.2.2. Biodegradation

No information.

Product name: 6075 Fade Out Spray Creation date: 10.9.2019 · Revision: 3.2.2021 · Version: 1



### 12.3. Bioaccumulative potential

12.3.1. Partition coefficient

No information.

12.3.2. Bioconcentration factor (BCF)

No information.

### 12.4. Mobility in soil

12.4.1. Known or predicted distribution to environmental compartments

No information.

### 12.4.2. Surface tension

No information.

### 12.4.3. Adsorption/Desorption

No information.

### 12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

### 12.6. Other adverse effects

No information.

### 12.7. Additional information

### For product

Product is not classified as dangerous for environment. Water hazard class 1 (self-assessment): slightly hazardous for water. Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

## SECTION 13. DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

13.1.1. Product / Packaging disposal

### Waste chemical

Do not dispose together with household garbage. Do not allow product to reach drains/sewage systems. Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste.

### Packaging

Dispose of in accordance with applicable waste disposal regulation. Deliver completely emptied containers to approved waste disposal authorities. Uncleaned containers should not be perforated, cut or welded. Empty containers represent a fire hazard as they may contain flammable product residues and vapour.

### Waste codes / waste designations according to LoW

15 01 10\* - packaging containing residues of or contaminated by dangerous substances

13.1.2. Waste treatment-relevant information

Disposal in accordance with the Rules on the management of waste.

### 13.1.3. Sewage disposal-relevant information

-

13.1.4. Other disposal recommendations

## **SECTION 14. TRANSPORT INFORMATION**

Product name: 6075 Fade Out Spray Creation date: 10.9.2019 · Revision: 3.2.2021 · Version: 1

### 14.1. UN number

UN 1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

2

### 14.4. Packing group

Not applicable.

### 14.5. Environmental hazards

NO.

### 14.6. Special precautions for user

Limited quantities

1 L

Tunnel restriction code

(D)

## IMDG flashpoint

0 °C, c.c.

### IMDG EmS

F-D, S-U

## 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Goods may not be carried in bulk in bulk containers, containers or vehicles.

## SECTION 15. REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (including last amendment Commission Regulation (EU) 2015/830)

- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

### <u>15.1.1. Information according 2004/42/EC about limitation of emissions of volatile organic compounds</u> (VOC-guideline)

Not applicable.

### 15.1.2. Special instructions

Seveso III, P3a: flammable aerosols.

Technical instructions air: class: NK; content: 50-100%.

### 15.2. Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## SECTION 16. OTHER INFORMATION

## Indication of changes

Abbreviations and acronyms







## Product name: 6075 Fade Out Spray

Creation date: 10.9.2019 · Revision: 3.2.2021 · Version: 1



ATE - Acute Toxicity Estimate ADR - Agreement concerning the International Carriage of Dangerous Goods by Road ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways CEN - European Committee for Standardisation C&L - Classification and Labelling CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008 CAS# - Chemical Abstracts Service number CMR - Carcinogen, Mutagen, or Reproductive Toxicant CSA - Chemical Safety Assessment CSR - Chemical Safety Report DMEL - Derived Minimal Effect Level **DNEL - Derived No Effect Level** DPD - Dangerous Preparations Directive 1999/45/EC DSD - Dangerous Substances Directive 67/548/EEC DU - Downstream User EC - European Community ECHA - European Chemicals Agency EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS) EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway) EEC - European Economic Community EINECS - European Inventory of Existing Commercial Substances ELINCS - European List of notified Chemical Substances EN - European Standard EQS - Environmental Quality Standard EU - European Union Euphrac - European Phrase Catalogue EWC - European Waste Catalogue (replaced by LoW - see below) GES - Generic Exposure Scenario GHS - Globally Harmonized System IATA - International Air Transport Association ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air IMDG - International Maritime Dangerous Goods IMSBC - International Maritime Solid Bulk Cargoes IT - Information Technology IUCLID - International Uniform Chemical Information Database IUPAC - International Union for Pure Applied Chemistry JRC - Joint Research Centre Kow - octanol-water partition coefficient LC<sub>50</sub> - Lethal Concentration to 50 % of a test population LD<sub>50</sub> - Lethal Dose to 50% of a test population (Median Lethal Dose) LE - Legal Entity LoW - List of Wastes (see http://ec.europa.eu/environment/waste/framework/list.htm) LR - Lead Registrant M/I - Manufacturer / Importer MS - Member States MSDS - Material Safety Data Sheet **OC** - Operational Conditions OECD - Organization for Economic Co-operation and Development **OEL - Occupational Exposure Limit** OJ - Official Journal **OR** - Only Representative OSHA - European Agency for Safety and Health at work PBT - Persistent, Bioaccumulative and Toxic substance PEC - Predicted Effect Concentration PNEC(s) - Predicted No Effect Concentration(s) PPE - Personal Protection Equipment (Q)SAR - Qualitative Structure Activity Relationship REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006 RID - Regulations concerning the International Carriage of Dangerous Goods by Rail **RIP - REACH Implementation Project** RMM - Risk Management Measure SCBA - Self-Contained Breathing Apparatus SDS - Safety data sheet

Product name: 6075 Fade Out Spray Creation date: 10.9.2019 · Revision: 3.2.2021 · Version: 1




SIEF - Substance Information Exchange Forum SME - Small and Medium sized Enterprises STOT - Specific Target Organ Toxicity (STOT) RE - Repeated Exposure (STOT) SE - Single Exposure SVHC - Substances of Very High Concern UN - United Nations vPvB - Very Persistent and Very Bioaccumulative

Key literature references and sources for data

### List of relevant H phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- EUH066 Repeated exposure may cause skin dryness or cracking.



The information of this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under Section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.