

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **6130 B13 Multi-Green**

Creation date: **30.1.2020** · Revision: **12.11.2020** · Version: **1**

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name

6130 B13 Multi-Green



chemius.net/Wthec

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Putty.

Uses advised against

No information.

1.3. Details of the supplier of the safety data sheet

Manufacturer

SILCO, D.O.O.

Address: Šentrupert 5 a, 3303 Gomilsko, Slovenia

Phone: +386 3 703 3180

Fax: +386 3 703 3188

E-mail: n.cvilak@silco-automotive.com

Point of contact for safety info: Nejc Cvilak

1.4. Emergency telephone number

Emergency

112

Supplier

+386 3 703 3180

SECTION 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Flam. Liq. 3; H226 Flammable liquid and vapour.

Skin Irrit. 2; H315 Causes skin irritation.

Eye Irrit. 2; H319 Causes serious eye irritation.

Repr. 2; H361d Suspected of damaging the unborn child.

STOT RE 1; H372 Causes damage to organs (hearing organs) through prolonged or repeated exposure (inhalation).

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: 6130 B13 Multi-Green

Creation date: 30.1.2020 · Revision: 12.11.2020 · Version: 1

2.2 Label elements

2.2.1. Labelling according to Regulation (EC) No 1272/2008 [CLP]



Signal word: **Danger**

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs (hearing organs) through prolonged or repeated exposure (inhalation).

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P201 Obtain special instructions before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulation.

2.2.2. Contains:

styrene (CAS: 100-42-5, EC: 202-851-5, Index: 601-026-00-0)

2.2.3. Special provisions

Special hazards are not known or expected.

2.3. Other hazards

No information.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

For mixtures see 3.2.

3.2. Mixtures

Name	CAS EC Index	%	Classification according to Regulation (EC) No 1272/2008 (CLP)	Specific Conc. Limits	REACH Registration No.
styrene	100-42-5 202-851-5 601-026-00-0	10-<20	Flam. Liq. 3; H226 Asp. Tox. 1; H304 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute Tox. 4; H332 STOT SE 3; H335 Repr. 2; H361 STOT RE 1; H372 Aquatic Chronic 3; H412		01-2119457861-32

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

General notes

Symptoms of poisoning may even occur after several hours; therefore medical observation is required at least 48 hours after the event. Person giving first aid should properly protect himself. If breathing is difficult or if not breathing provide artificial respiration. Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency. Take off all contaminated clothing immediately.

When it is suspected, that there may still be harmful vapours/fumes present in the air, respiratory protection (mask; self contained breathing apparatus) must be used.

Following inhalation

Remove patient to fresh air - move out of dangerous area. If symptoms occur, seek medical advice. If victim is not breathing give artificial respiration. In case of unconsciousness bring patient into stable side position and seek medical attention. In the event of breathing difficulties, get medical advice/attention immediately.

Following skin contact

Immediately remove contaminated clothing. Wash affected skin areas thoroughly with plenty of water and soap. If symptoms develop and persist, seek medical attention. If irritation of skin persists seek medical attention.

Following eye contact

Immediately flush eyes with running water, keeping eyelids apart. After initial flushing, remove any contact lenses and continue flushing. Seek medical help.

Following ingestion

Do not induce vomiting! Immediately consult a doctor. Show the physician the safety data sheet or label.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation

Excessive exposure to spray mist, fog, or vapours may cause respiratory irritation. Coughing, sneezing, nasal discharge, labored breathing.

Skin contact

Itching, redness, pain.

Eye contact

Redness, tearing, pain.

Ingestion

May cause nausea/vomiting and diarrhea.
May cause abdominal discomfort.

4.3. Indication of any immediate medical attention and special treatment needed

-

SECTION 5. FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂).
Fire extinguishing powder.
Water spray. Fight larger fires with water spray.

Unsuitable extinguishing media

Full water jet.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **6130 B13 Multi-Green**

Creation date: **30.1.2020** · Revision: **12.11.2020** · Version: **1**

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

In case of heating harmful vapours/gases can be generated.

5.3. Advice for firefighters

Protective actions

In case of fire or heating do not breathe fumes/vapours. Cool containers at risk with water spray. If possible remove containers from endangered area.

Special protective equipment for firefighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

Additional information

Contaminated extinguishing agents must be disposed of in accordance with the regulations; do not allow to reach the sewage system.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment

Use personal protective equipment (Section 8). Avoid contact with the eyes and skin. Do not breathe vapours/smoke!

Emergency procedures

Ensure adequate ventilation. Keep away from sources of ignition and/or heat; No smoking! Keep away sources of ignition. Evacuate the danger zone. Prevent access to unprotected personnel. Prevent access to unauthorised personnel.

6.1.2. For emergency responders

Use personal protective equipment.

6.2. Environmental precautions

Do not allow product to reach water/drains/sewage systems or permeable soil. If accidental large entry into water or ground occurs, inform responsible authorities.

6.3. Methods and material for containment and cleaning up

6.3.1. For containment

Stem the spill if this does not pose risks.

6.3.2. For cleaning up

Absorb product (with inert material), collect it in special container and dispose it to a licensed hazardous-waste disposal contractor. Do not use water or water based cleansing agents. Dispose in accordance with applicable regulations (see Section 13).

6.3.3. Other information

See Section 7: safe handling.

6.4. Reference to other sections

See also Sections 8 and 13.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **6130 B13 Multi-Green**
Creation date: **30.1.2020** · Revision: **12.11.2020** · Version: **1**

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

7.1.1. Protective measures

Measures to prevent fire

Ensure adequate ventilation. Keep away from sources of ignition - no smoking. Take precautionary measures against static discharges. Ensure proper grounding of the equipment. Vapours and air form explosive mixtures. Use spark-proof tools.

Measures to prevent aerosol and dust generation

Ensure good ventilation and extraction. Use general or local exhaust ventilation to prevent inhaling vapours and aerosols.

Measures to protect the environment

Do not discharge into drains, surface water and soil. After use immediately close container tightly.

7.1.2. Advice on general occupational hygiene

Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Do not breathe vapours/mist. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1. Technical measures and storage conditions

Store in accordance with local regulations. Keep in cool and well ventilated area. Keep in tightly closed container. Protect from open fire, heat and direct sunlight. Keep away from sources of ignition - no smoking. Keep away from oxidising substances. Store below 30°C. Keep away from food, drink and animal feeding stuffs. Keep unauthorized personnel away.

7.2.2. Packaging materials

Store only in original container.

7.2.3. Requirements for storage rooms and vessels

Do not store in unlabelled containers. Close opened containers after use. Put the containers upright to prevent from leaking. The floor of the storage room must be impermeable and dam spilled liquid.

7.2.4. Storage class

-

7.2.5. Further information on storage conditions

Storage class: storage must comply with the regulations on storage of flammable chemicals.

7.3. Specific end use(s)

Recommendations

-

Industrial sector specific solutions

-

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

8.1.1. Occupational exposure limit values

Name (CAS)	Limit values		Short-term exposure limit		Remarks	Biological Tolerance Values
	ml/m ³ (ppm)	mg/m ³	ml/m ³ (ppm)	mg/m ³		
Styrene (100-42-5)	100	430	250	1080		

8.1.2. Information on monitoring procedures

BS EN 14042:2003 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 482:2012+A1:2015 Workplace exposure. General requirements for the performance of procedures for the measurement of chemical agents. BS EN 689:2018 Workplace exposure. Measurement of exposure by inhalation to chemical agents. Strategy for testing compliance with occupational exposure limit values.

8.1.3. DNEL/DMEL values

For components

Name	Type	Exposure route	Exposure frequency	Value	Remark
styrene (100-42-5)	Worker	inhalation	long term (systemic effects)	85 mg/m ³	
styrene (100-42-5)	Worker	inhalation	short term (systemic effects)	289 mg/m ³	
styrene (100-42-5)	Worker	inhalation	short term (local effects)	306 mg/m ³	
styrene (100-42-5)	Worker	dermal	long term (systemic effects)	406 mg/kg bw/day	
styrene (100-42-5)	Consumer	inhalation	long term (systemic effects)	10,2 mg/m ³	
styrene (100-42-5)	Consumer	inhalation	short term (systemic effects)	174,25 mg/m ³	
styrene (100-42-5)	Consumer	inhalation	short term (local effects)	182,75 mg/m ³	
styrene (100-42-5)	Consumer	dermal	long term (systemic effects)	343 mg/kg bw/day	
styrene (100-42-5)	Consumer	oral	long term (systemic effects)	2,1 mg/kg bw/day	

8.1.4. PNEC values

For components

Name	Exposure route	Value	Remark
styrene (100-42-5)	fresh water	0,028 mg/L	
styrene (100-42-5)	marine water	0,014 mg/L	
styrene (100-42-5)	fresh water sediment	0,614 mg/kg	dry weight
styrene (100-42-5)	marine water sediment	0,307 mg/kg	dry weight
styrene (100-42-5)	soil	0,2 mg/kg	dry weight
styrene (100-42-5)	water treatment plant	5 mg/L	
styrene (100-42-5)	water, intermittent release	0,4 mg/L	fresh water

8.2. Exposure controls

8.2.1. Appropriate engineering control

Substance/mixture related measures to prevent exposure during identified uses

Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Avoid contact with eyes and skin. Do not breathe vapours/aerosols.

Organisational measures to prevent exposure

Remove all contaminated clothes immediately and wash them before reuse. Store protective clothing separate from regular clothing.

Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration. Keep away from food, drink and animal feeding stuffs.

8.2.2. Personal protective equipment

Eye and face protection

Tight fitting protective goggles (EN 166).

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **6130 B13 Multi-Green**

Creation date: **30.1.2020** · Revision: **12.11.2020** · Version: **1**

Hand protection

Before use protect hands with suitable protective cream. Protective gloves (EN 374). Observe the manufacturer's instructions regarding the use, storage, maintenance and replacement of gloves. In case of damage or at the first signs of wear and tear, change the gloves immediately. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. The penetration time is determined by the protective glove manufacturer and must be observed. Unsuitable gloves: Natural rubber, Chloroprene rubber, Nitrile rubber, Butyl rubber, PVC gloves.

Appropriate materials

Material	Thickness	Penetration Time	Remark
Viton (fluorinated rubber)	≥ 0,7 mm	≥ 480 min	EN 374-4

Skin protection

Wear suitable protective clothing. Cotton protective clothing and shoes that cover the entire foot (EN ISO 20345).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory protection. Wear suitable protective breathing mask (EN 136) with filter A2-P2 (EN 14387). For dust/gas/ vapor concentrations above the applicable filter limit, in case of oxygen concentrations below 17% or in vague conditions, autonomous self-contained breathing apparatus should be used, according to standard EN 137, EN 138.

Thermal hazards

-

8.2.3. Environmental exposure controls

-

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

-	Physical state:	liquid; paste
-	Colour:	different colours
-	Odour:	characteristic

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: 6130 B13 Multi-Green

Creation date: 30.1.2020 · Revision: 12.11.2020 · Version: 1

Important health, safety and environmental information

-	pH	No information.
-	Melting point/freezing point	No information.
-	Initial boiling point/boiling range	145 °C
-	Flash point	31 °C
-	Evaporation rate	No information.
-	Flammability (solid, gas)	480 °C
-	Explosion limits (vol%)	1,2 – 8,9 vol %
-	Vapour pressure	6 hPa at 20 °C
-	Vapour density	No information.
-	Density	Density: 1,2 – 1,9 g/cm ³ at 20 °C
-	Solubility	Water: Insoluble
-	Partition coefficient	No information.
-	Auto-ignition temperature	Not self-igniting.
-	Decomposition temperature	No information.
-	Viscosity	No information.
-	Explosive properties	Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.
-	Oxidising properties	No information.

9.2. Other information

-	Weight organic solvents	< 120 g/l
-	Remarks:	

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity

Stable under recommended transport or storage conditions.

10.2. Chemical stability

Product is stable under normal conditions of use, recommended handling and storage conditions.

10.3. Possibility of hazardous reactions

Risk of exothermic polymerization.

10.4. Conditions to avoid

Protect from heat, direct sunlight, open fire, sparks.

10.5. Incompatible materials

Peroxide. Free radicals. Exothermic polymerisation

10.6. Hazardous decomposition products

Under normal use conditions no hazardous decomposition products are expected. In case of fire/explosion vapours/gases that pose a health hazard are released. Decomposition products may include toxic gas.

SAFETY DATA SHEET according to Regulation 1907/2006

Product name: 6130 B13 Multi-Green

Creation date: 30.1.2020 · Revision: 12.11.2020 · Version: 1

SECTION 11. TOXICOLOGICAL INFORMATION**11.1. Information on toxicological effects**(a) Acute toxicity

Name	Exposure route	Type	Species	Time	Value	Method	Remark
styrene (100-42-5)	oral	LD ₅₀	rat		5000 mg/kg		
styrene (100-42-5)	dermal	LD ₅₀	rat		> 2000 mg/kg	OECD 402	
styrene (100-42-5)	inhalation	LC ₅₀	rat	4 h	11,8 mg/l		

Additional information: The product is not classified for acute toxicity.(b) Skin corrosion/irritation**Additional information:** Causes skin irritation.(c) Serious eye damage/irritation**Additional information:** Causes serious eye irritation.(d) Respiratory or skin sensitisation**Additional information:** The product is not classified as sensitising.(e) (Germ cell) mutagenicity

No information.

(f) Carcinogenicity

Name	Exposure route	Type	Species	Time	Value	Result	Method	Remark
styrene (100-42-5)	inhalation (vapours)	NOAEL	rat		4,34 mg/l		OECD 453	5 days per week, 6 h per day

(g) Reproductive toxicity

Name	Reproductive toxicity type	Type	Species	Time	Value	Result	Method	Remark
styrene (100-42-5)	Effects on fertility	NOAEL (parents)	rat		0,65 – 2,2 mg/L		OECD 416	Inhalation (vapour)
styrene (100-42-5)	Effects on fertility	NOAEL (F2)	rat		0,22 mg/L		OECD 416	Inhalation (vapour)
styrene (100-42-5)	Developmental toxicity	NOAEL	rat		2,6 mg/L			Inhalation
styrene (100-42-5)	Teratogenicity	NOAEL	rat		2,6 mg/L			Inhalation
styrene (100-42-5)	Maternal toxicity	LOAEL	rat		1,3 mg/L			Inhalation

Summary of evaluation of the CMR properties

Suspected of damaging the unborn child.

(h) STOT-single exposure

No information.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: 6130 B13 Multi-Green

Creation date: 30.1.2020 · Revision: 12.11.2020 · Version: 1

(i) STOT-repeated exposure

Name	Exposure route	Type	Species	Time	Organ	Value	Result	Method	Remark
styrene (100-42-5)	inhalation (vapours)	NOAEL	rat	13 weeks		0,85 mg/L			6h/day
styrene (100-42-5)	inhalation (vapours)	NOAEL	rat					OECD 453	6h/day

Additional information: Causes damage to the hearing organs through prolonged or repeated exposure if inhaled.

(j) Aspiration hazard

Additional information: Aspiration hazard: Not classified.

SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Acute (short-term) toxicity

For components

Substance (CAS Nr.)	Type	Value	Exposure time	Species	Organism	Method	Remark
styrene (100-42-5)	LC ₅₀	4,02 mg/L	96 h	fish	<i>Pimephales promelas</i>		
	EC ₅₀	4,7 mg/L	48 h	crustacea	<i>Daphnia magna</i>	OECD 202	
	EC ₅₀	4,9 mg/L	72 h	algae	<i>Pseudokirchneriella subcapitata</i>	EPA OTS 797.1050	
	EC ₅₀	ca. 500 mg/L	30 min	bacteria		OECD 209	
	EC ₁₀	0,28 mg/L	96 h	algae	<i>Pseudokirchneriella subcapitata</i>	EPA OTS 797.1050	

12.1.2. Chronic (long-term) toxicity

For components

Substance (CAS Nr.)	Type	Value	Exposure time	Species	Organism	Method	Remark
styrene (100-42-5)	NOEC	1,01 mg/l	21 days	crustacea	<i>Daphnia magna</i>	OECD 211	

12.2. Persistence and degradability

12.2.1. Abiotic degradation, physical- and photo-chemical elimination

No information.

12.2.2. Biodegradation

For components

Substance (CAS Nr.)	Type	Rate	Time	Evaluation	Method	Remark
styrene (100-42-5)	biodegradability	70,9 %	28 days	readily biodegradable	ISO DIN 9408	aerobic, activated sludge

12.3. Bioaccumulative potential

12.3.1. Partition coefficient

For components

Substance (CAS Nr.)	Media	Value	Temperature	pH	Concentration	Method
styrene (100-42-5)	Octanol-water (log Pow)	2,96				

12.3.2. Bioconcentration factor (BCF)

For components

Substance (CAS Nr.)	species	Organism	Value	Duration	Evaluation	Method	Remark
styrene (100-42-5)	BCF	fish	13,5				
styrene (100-42-5)	BCF		74				Calculated value

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **6130 B13 Multi-Green**

Creation date: **30.1.2020** · Revision: **12.11.2020** · Version: **1**

12.4. Mobility in soil

12.4.1. Known or predicted distribution to environmental compartments

No information.

12.4.2. Surface tension

No information.

12.4.3. Adsorption/Desorption

For components

Substance (CAS Nr.)	Type	Criterion	Value	Evaluation	Method	Remark
styrene (100-42-5)	Soil	log KOC	2,55			
styrene (100-42-5)	Soil		352			Koc

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6. Other adverse effects

No information.

12.7. Additional information

For product

Do not allow to reach ground water, water courses or sewage system.

Danger for drinking water if even small quantities leak into ground water.

Water hazard class 2 (self-assessment): hazardous for water.

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

13.1.1. Product / Packaging disposal

Waste chemical

Do not dispose together with household garbage. Do not allow product to reach drains/sewage systems. Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste.

Waste codes / waste designations according to LoW

07 02 08* - other still bottoms and reaction residues

Packaging

Deliver completely emptied containers to approved waste disposal authorities. Dispose of in accordance with applicable waste disposal regulation.

13.1.2. Waste treatment-relevant information

Disposal in accordance with the Rules on the management of waste.

13.1.3. Sewage disposal-relevant information

-

13.1.4. Other disposal recommendations

-

SECTION 14. TRANSPORT INFORMATION

14.1. UN number

UN 1866

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **6130 B13 Multi-Green**

Creation date: **30.1.2020** · Revision: **12.11.2020** · Version: **1**

14.2. UN proper shipping name

RESIN SOLUTION

14.3. Transport hazard class(es)

3

14.4. Packing group

III

14.5. Environmental hazards

NO.

14.6. Special precautions for user

Limited quantities

5 L

Tunnel restriction code

(D/E)

IMDG flashpoint

31 °C, c.c.

IMDG EmS

F-E, S-E



14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Goods may not be carried in bulk in bulk containers, containers or vehicles.

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (including last amendment Commission Regulation (EU) 2015/830)

- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

15.1.1. Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-guideline)

EU limit values and category: B(b) 250 g/l. VOC Content: < 120 g/l

15.1.2. Special instructions

Seveso P5c: FLAMMABLE LIQUIDS.

Observe the regulations on employment and protection against dangerous substances for young people, pregnant women and nursing mothers.

15.2. Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16. OTHER INFORMATION

Indication of changes

-

Abbreviations and acronyms

ATE - Acute Toxicity Estimate

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **6130 B13 Multi-Green**

Creation date: **30.1.2020** · Revision: **12.11.2020** · Version: **1**

CEN - European Committee for Standardisation
C&L - Classification and Labelling
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
CAS# - Chemical Abstracts Service number
CMR - Carcinogen, Mutagen, or Reproductive Toxicant
CSA - Chemical Safety Assessment
CSR - Chemical Safety Report
DMEL - Derived Minimal Effect Level
DNEL - Derived No Effect Level
DPD - Dangerous Preparations Directive 1999/45/EC
DSD - Dangerous Substances Directive 67/548/EEC
DU - Downstream User
EC - European Community
ECHA - European Chemicals Agency
EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS)
EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway)
EEC - European Economic Community
EINECS - European Inventory of Existing Commercial Substances
ELINCS - European List of notified Chemical Substances
EN - European Standard
EQS - Environmental Quality Standard
EU - European Union
Euphrac - European Phrase Catalogue
EWC - European Waste Catalogue (replaced by LoW – see below)
GES - Generic Exposure Scenario
GHS - Globally Harmonized System
IATA - International Air Transport Association
ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG - International Maritime Dangerous Goods
IMSBC - International Maritime Solid Bulk Cargoes
IT - Information Technology
IUCLID - International Uniform Chemical Information Database
IUPAC - International Union for Pure Applied Chemistry
JRC - Joint Research Centre
Kow - octanol-water partition coefficient
LC₅₀ - Lethal Concentration to 50 % of a test population
LD₅₀ - Lethal Dose to 50% of a test population (Median Lethal Dose)
LE - Legal Entity
LoW - List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)
LR - Lead Registrant
M/I - Manufacturer / Importer
MS - Member States
MSDS - Material Safety Data Sheet
OC - Operational Conditions
OECD - Organization for Economic Co-operation and Development
OEL - Occupational Exposure Limit
OJ - Official Journal
OR - Only Representative
OSHA - European Agency for Safety and Health at work
PBT - Persistent, Bioaccumulative and Toxic substance
PEC - Predicted Effect Concentration
PNEC(s) - Predicted No Effect Concentration(s)
PPE - Personal Protection Equipment
(Q)SAR - Qualitative Structure Activity Relationship
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
RIP - REACH Implementation Project
RMM - Risk Management Measure
SCBA - Self-Contained Breathing Apparatus
SDS - Safety data sheet
SIEF - Substance Information Exchange Forum
SME - Small and Medium sized Enterprises
STOT - Specific Target Organ Toxicity

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **6130 B13 Multi-Green**

Creation date: **30.1.2020** · Revision: **12.11.2020** · Version: **1**

(STOT) RE - Repeated Exposure
(STOT) SE - Single Exposure
SVHC - Substances of Very High Concern
UN - United Nations
vPvB - Very Persistent and Very Bioaccumulative

Key literature references and sources for data

-

List of relevant H phrases

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H361 Suspected of damaging fertility or the unborn child .
H372 Causes damage to organs through prolonged or repeated exposure .
H412 Harmful to aquatic life with long lasting effects.



- Provided correct labelling of the product
- Compliance with the local legislation
- Provided correct classification of the product
- Provided adequate transport data

© BENS Consulting | www.bens-consulting.com

The information of this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under Section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.