

# SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **6400 Multi Fiber**

Creation date: **2.10.2010** · Revision: **3.7.2019** · Version: **1**

## SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product name

**6400 Multi Fiber**



chemius.net/jVN62

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Putty.

Uses advised against

No information.

### 1.3. Details of the supplier of the safety data sheet

Manufacturer

SILCO, D.O.O.

Address: Šentrupert 5 a, 3303 Gomilsko, Slovenia

Phone: +386 3 703 3180

Fax: +386 3 703 3188

E-mail: n.cvilak@silco-automotive.com

Point of contact for safety info: Nejc Cvilak

### 1.4. Emergency telephone number

Emergency

112

Supplier

+386 3 703 3180

## SECTION 2. HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Flam. Liq. 3; H226 Flammable liquid and vapour.

Skin Irrit. 2; H315 Causes skin irritation.

Eye Irrit. 2; H319 Causes serious eye irritation.

Repr. 2; H361d Suspected of damaging the unborn child.

STOT RE 1; H372 Causes damage to organs (hearing organs) through prolonged or repeated exposure (inhalation).

# SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **6400 Multi Fiber**

Creation date: **2.10.2010** · Revision: **3.7.2019** · Version: **1**

## 2.2 Label elements

### 2.2.1. Labelling according to Regulation (EC) No 1272/2008 [CLP]



Signal word: **Danger**

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs (hearing organs) through prolonged or repeated exposure (inhalation).

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P201 Obtain special instructions before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe the mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulation.

### 2.2.2. Contains:

styrene (CAS: 100-42-5, EC: 202-851-5, Index: 601-026-00-0)

### 2.2.3. Special provisions

Special hazards are not known or expected.

## 2.3. Other hazards

No information.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substances

For mixtures see 3.2.

### 3.2. Mixtures

Name	CAS EC Index	%	Classification according to Regulation (EC) No 1272/2008 (CLP)	Specific Conc. Limits	REACH Registration No.
styrene	100-42-5 202-851-5 601-026-00-0	10-<20	Flam. Liq. 3; H226 Asp. Tox. 1; H304 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute Tox. 4; H332 STOT SE 3; H335 Repr. 2; H361d STOT RE 1; H372 Aquatic Chronic 3; H412		01-2119457861-32
1-ethylpyrrolidin-2-one	2687-91-4 220-250-6 616-208-00-5	0,1-<0,3	Repr. 1B; H360D		-

# SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **6400 Multi Fiber**

Creation date: **2.10.2010** · Revision: **3.7.2019** · Version: **1**

## SECTION 4. FIRST AID MEASURES

### 4.1. Description of first aid measures

#### General notes

Symptoms of poisoning may even occur after several hours; therefore medical observation is required at least 48 hours after the event. Show the safety data sheet and label to the physician. When in doubt or if feeling unwell seek medical assistance. Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency.

#### Following inhalation

Remove patient to fresh air - move out of dangerous area. Seek medical help immediately. If victim is not breathing give artificial respiration. In case of unconsciousness bring patient into stable side position and seek medical attention. If difficulties with breathing do not stop, search for medical help.

#### Following skin contact

Immediately remove contaminated clothing. Wash affected skin areas thoroughly with plenty of water and soap. If symptoms develop and persist, seek medical attention.

#### Following eye contact

If the patient is wearing contact lenses, remove them immediately. Immediately flush eyes with running water, keeping eyelids apart. Consult a physician immediately!

#### Following ingestion

Do not induce vomiting! Immediately consult a doctor. Show the physician the safety data sheet or label.

### 4.2. Most important symptoms and effects, both acute and delayed

#### Inhalation

Can cause irritation of respiratory system.  
Coughing, sneezing, nasal discharge, labored breathing.

#### Skin contact

Causes irritation of mucous membrane.  
Itching, redness, pain.

#### Eye contact

Redness, tearing, pain.

#### Ingestion

May cause nausea/vomiting and diarrhea.

### 4.3. Indication of any immediate medical attention and special treatment needed

-

## SECTION 5. FIREFIGHTING MEASURES

### 5.1. Extinguishing media

#### Suitable extinguishing media

Carbon dioxide (CO<sub>2</sub>).  
Fire extinguishing powder.  
Water spray. Fight larger fires with water spray.

#### Unsuitable extinguishing media

Full water jet.

### 5.2. Special hazards arising from the substance or mixture

#### Hazardous combustion products

In case of heating harmful vapours/gases can be generated.

# SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **6400 Multi Fiber**

Creation date: **2.10.2010** · Revision: **3.7.2019** · Version: **1**

## 5.3. Advice for firefighters

### Protective actions

Cool containers at risk with water spray. If possible remove containers from endangered area. In case of fire or heating do not breathe fumes/vapours. Cool the endangered containers with water spray.

### Special protective equipment for firefighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

### Additional information

Contaminated firefighting water must be disposed of in accordance with the regulations; do not allow to reach the sewage system.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

##### **Protective equipment**

Use personal protective equipment (Section 8). Avoid contact with the eyes and skin. Do not breathe vapours/smoke!

##### **Emergency procedures**

Ensure adequate ventilation. Keep away from sources of ignition and/or heat; No smoking! Keep away sources of ignition. Prevent access to unprotected personnel. Prevent access to unauthorised personnel.

#### 6.1.2. For emergency responders

Use personal protective equipment.

### 6.2. Environmental precautions

Do not allow product to reach water/drains/sewage systems or permeable soil. If accidental large entry into water or ground occurs, inform responsible authorities.

### 6.3. Methods and material for containment and cleaning up

#### 6.3.1. For containment

Stem the spill if this does not pose risks.

#### 6.3.2. For cleaning up

Absorb product (with inert material), collect it in special container and dispose it to a licensed hazardous-waste disposal contractor. Do not use water or water based cleansing agents.

#### 6.3.3. Other information

-

### 6.4. Reference to other sections

See also Sections 8 and 13.

## SECTION 7. HANDLING AND STORAGE

### 7.1. Precautions for safe handling

#### 7.1.1. Protective measures

##### **Measures to prevent fire**

Ensure adequate ventilation. Keep away from sources of ignition - no smoking. Use spark-proof tools. Take precautionary measures against static discharges. Vapours and air form explosive mixtures.

##### **Measures to prevent aerosol and dust generation**

Use general or local exhaust ventilation to prevent inhaling vapours and aerosols.

# SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **6400 Multi Fiber**

Creation date: **2.10.2010** · Revision: **3.7.2019** · Version: **1**

## Measures to protect the environment

Do not discharge into drains, surface water and soil. After use immediately close container tightly.

### 7.1.2. Advice on general occupational hygiene

Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Do not breathe vapours/mist. Avoid contact with skin and eyes.

## 7.2. Conditions for safe storage, including any incompatibilities

### 7.2.1. Technical measures and storage conditions

Store in accordance with local regulations. Keep in cool and well ventilated area. Protect from open fire, heat and direct sunlight. Keep away from food, drink and animal feeding stuffs. Keep in tightly closed container. Keep away from oxidising substances. Keep away from heat and sources of ignition. Keep away from sources of ignition - no smoking. Store below 30°C.

### 7.2.2. Packaging materials

Store only in original container.

### 7.2.3. Requirements for storage rooms and vessels

Close opened containers after use. Put the containers upright to prevent from leaking. Do not store in unlabelled containers.

### 7.2.4. Storage class

-

### 7.2.5. Further information on storage conditions

-

## 7.3. Specific end use(s)

### Recommendations

-

### Industrial sector specific solutions

-

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### 8.1.1. Occupational exposure limit values

Name (CAS)	Limit values		Short-term exposure limit		Remarks	Biological Tolerance Values
	ml/m <sup>3</sup> (ppm)	mg/m <sup>3</sup>	ml/m <sup>3</sup> (ppm)	mg/m <sup>3</sup>		
Styrene (100-42-5)	100	430	250	1080		

#### 8.1.2. Information on monitoring procedures

BS EN 14042:2003 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 482:2012+A1:2015 Workplace exposure. General requirements for the performance of procedures for the measurement of chemical agents. BS EN 689:2018 Workplace exposure. Measurement of exposure by inhalation to chemical agents. Strategy for testing compliance with occupational exposure limit values.

# SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **6400 Multi Fiber**

Creation date: **2.10.2010** · Revision: **3.7.2019** · Version: **1**

## 8.1.3. DNEL/DMEL values

### For components

Name	Type	Exposure route	Exposure frequency	Value	Remark
styrene (100-42-5)	Worker	inhalation	long term (systemic effects)	85 mg/m <sup>3</sup>	
styrene (100-42-5)	Worker	inhalation	short term (systemic effects)	289 mg/m <sup>3</sup>	
styrene (100-42-5)	Worker	inhalation	short term (local effects)	306 mg/m <sup>3</sup>	
styrene (100-42-5)	Worker	dermal	long term (systemic effects)	406 mg/kg bw/day	
styrene (100-42-5)	Consumer	inhalation	long term (systemic effects)	10,2 mg/m <sup>3</sup>	
styrene (100-42-5)	Consumer	inhalation	short term (systemic effects)	174,25 mg/m <sup>3</sup>	
styrene (100-42-5)	Consumer	inhalation	short term (local effects)	182,75 mg/m <sup>3</sup>	
styrene (100-42-5)	Consumer	dermal	long term (systemic effects)	343 mg/kg bw/day	
styrene (100-42-5)	Consumer	oral	long term (systemic effects)	2,1 mg/kg bw/day	

## 8.1.4. PNEC values

### For components

Name	Exposure route	Value	Remark
styrene (100-42-5)	fresh water	0,028 mg/L	
styrene (100-42-5)	water, intermittent release	0,04 mg/L	fresh water
styrene (100-42-5)	marine water	0,014 mg/L	
styrene (100-42-5)	water treatment plant	5 mg/L	
styrene (100-42-5)	fresh water sediment	0,614 mg/kg	dry weight
styrene (100-42-5)	marine water sediment	0,307 mg/kg	dry weight
styrene (100-42-5)	soil	0,2 mg/kg	dry weight

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering control

#### Substance/mixture related measures to prevent exposure during identified uses

Use good personal hygiene practices – wash hands at breaks and when done working with material. Avoid contact with eyes and skin. Do not breathe vapours/aerosols.

#### Organisational measures to prevent exposure

Remove all contaminated clothes immediately and wash them before reuse. Do not eat, drink or smoke while working.

#### Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration. Keep away from food, drink and animal feeding stuffs.

### 8.2.2. Personal protective equipment

#### Eye and face protection

Tight fitting protective goggles (EN 166).

#### Hand protection

Protective gloves (EN 374). Observe the manufacturer's instructions regarding the use, storage, maintenance and replacement of gloves. In case of damage or at the first signs of wear and tear, change the gloves immediately. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. Unsuitable gloves: Natural rubber, Chloroprene rubber, Nitrile rubber, Butyl rubber, PVC gloves.

#### Appropriate materials

Material	Thickness	Penetration Time	Remark
Viton (fluorinated rubber)	0,7 mm	480 min	EN 374-4

# SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **6400 Multi Fiber**

Creation date: **2.10.2010** · Revision: **3.7.2019** · Version: **1**

## Skin protection

Wear suitable protective clothing. Cotton protective clothing and shoes that cover the entire foot (EN ISO 20345).

## Respiratory protection

Wear suitable protective breathing mask (EN 136) with filter A2-P2 (EN 14387). For dust/gas/ vapor concentrations above the applicable filter limit, in case of oxygen concentrations below 17% or in vague conditions, autonomous self-contained breathing apparatus should be used, according to standard EN 137, EN 138.

## Thermal hazards

-

## 8.2.3. Environmental exposure controls

### Technical measures to prevent exposure

Do not allow product to reach drains, sewage systems or ground water.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

-	<b>Physical state:</b>	liquid
-	<b>Colour:</b>	different colours
-	<b>Odour:</b>	characteristic

### Important health, safety and environmental information

-	<b>pH</b>	No information.
-	<b>Melting point/freezing point</b>	No information.
-	<b>Initial boiling point/boiling range</b>	145 °C
-	<b>Flash point</b>	31 °C
-	<b>Evaporation rate</b>	No information.
-	<b>Flammability (solid, gas)</b>	480 °C
-	<b>Explosion limits (vol%)</b>	1,2 – 8,9 vol %
-	<b>Vapour pressure</b>	6 hPa at 20 °C
-	<b>Vapour density</b>	No information.
-	<b>Density</b>	<b>Density:</b> 1,2 – 1,9 g/cm <sup>3</sup> at 20 °C
-	<b>Solubility</b>	<b>Water:</b> Insoluble
-	<b>Partition coefficient</b>	No information.
-	<b>Auto-ignition temperature</b>	No information.
-	<b>Decomposition temperature</b>	No information.
-	<b>Viscosity</b>	No information.
-	<b>Explosive properties</b>	Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.
-	<b>Oxidising properties</b>	No information.

### 9.2. Other information

-	<b>Remarks:</b>	Does not mix, or mixes poorly with water.
---	-----------------	---

## SECTION 10. STABILITY AND REACTIVITY

### 10.1. Reactivity

Stable under recommended transport or storage conditions.

# SAFETY DATA SHEET according to Regulation 1907/2006



Product name: 6400 Multi Fiber

Creation date: 2.10.2010 · Revision: 3.7.2019 · Version: 1

## 10.2. Chemical stability

Product is stable under normal conditions of use, recommended handling and storage conditions.

## 10.3. Possibility of hazardous reactions

Risk of exothermic polymerization.

## 10.4. Conditions to avoid

Protect from heat, direct sunlight, open fire, sparks.

## 10.5. Incompatible materials

Peroxide. Free radicals.

## 10.6. Hazardous decomposition products

Under normal use conditions no hazardous decomposition products are expected. In case of fire/explosion vapours/gases that pose a health hazard are released. Decomposition products may include toxic gas.

## SECTION 11. TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

#### (a) Acute toxicity

Name	Exposure route	Type	Species	Time	Value	Method	Remark
styrene (100-42-5)	oral	LD <sub>50</sub>	rat		5000 mg/kg		
styrene (100-42-5)	dermal	LD <sub>50</sub>	rat		> 2000 mg/kg	OECD 402	
styrene (100-42-5)	inhalation	LC <sub>50</sub>	rat	4 h	11,8 mg/l		
1-ethylpyrrolidin-2-one (2687-91-4)	oral	LD <sub>50</sub>	rat		3200 mg/kg	OECD 401	
1-ethylpyrrolidin-2-one (2687-91-4)	dermal	LD <sub>50</sub>	rat		> 2000 mg/kg	OECD 402	
1-ethylpyrrolidin-2-one (2687-91-4)	inhalation	LC <sub>50</sub>	rat		> 5,1 mg/l	OECD 403	

**Additional information:** The product is not classified for acute toxicity.

#### (b) Skin corrosion/irritation

**Additional information:** Causes skin and eye irritation.

#### (c) Serious eye damage/irritation

No information.

#### (d) Respiratory or skin sensitisation

**Additional information:** The product is not classified as sensitising.

#### (e) (Germ cell) mutagenicity

No information.

#### (f) Carcinogenicity

Name	Exposure route	Type	Species	Time	Value	Result	Method	Remark
styrene (100-42-5)	inhalation (vapours)	NOAEL	rat		4,34 mg/l		OECD 453	5 days per week, 6 h per day



# SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **6400 Multi Fiber**

Creation date: **2.10.2010** · Revision: **3.7.2019** · Version: **1**

## (g) Reproductive toxicity

Name	Reproductive toxicity type	Type	Species	Time	Value	Result	Method	Remark
styrene (100-42-5)	Effects on fertility	NOAEL (parents)	rat		0,65 mg/L		OECD 416	Inhalation (vapour)
styrene (100-42-5)	Effects on fertility	NOAEL (F2)	rat		0,22 mg/L		OECD 416	Inhalation (vapour)
styrene (100-42-5)	Effects on fertility	NOAEL (parents)	rat		2,2 mg/L		OECD 416	Inhalation (vapour)
styrene (100-42-5)	Developmental toxicity	NOAEL	rat		2,6 mg/L			Inhalation
styrene (100-42-5)	Teratogenicity	NOAEL	rat		2,6 mg/L			Inhalation
styrene (100-42-5)	Maternal toxicity	LOAEL	rat		1,3 mg/L			Inhalation

## Summary of evaluation of the CMR properties

Suspected of damaging the unborn child.

## (h) STOT-single exposure

No information.

## (i) STOT-repeated exposure

Name	Exposure route	Type	Species	Time	Organ	Value	Result	Method	Remark
styrene (100-42-5)	inhalation (vapours)	NOAEL	rat	13 weeks		0,85 mg/L			6h/day
styrene (100-42-5)	inhalation (vapours)	NOAEL	rat			0,8 mg/L		OECD 453	6h/day

**Additional information:** Causes damage to organs through prolonged or repeated exposure.

## (j) Aspiration hazard

**Additional information:** Aspiration hazard: Not classified.

## SECTION 12. ECOLOGICAL INFORMATION

### 12.1. Toxicity

#### 12.1.1. Acute (short-term) toxicity

##### For components

Substance (CAS Nr.)	Type	Value	Exposure time	Species	Organism	Method	Remark
styrene (100-42-5)	EC <sub>10</sub>	0,28 mg/L	96 h	algae	<i>Pseudokirchneriella subcapitata</i>	EPA OTS 797.1050	
	EC <sub>50</sub>	4,7 mg/L	48 h	crustacea	<i>Daphnia magna</i>	OECD 202	
	EC <sub>50</sub>	4,9 mg/L	72 h	algae	<i>Pseudokirchneriella subcapitata</i>	EPA OTS 797.1050	
	EC <sub>50</sub>	ca. 500 mg/L	30 min	activated sludge		OECD 209	
	LC <sub>50</sub>	4,02 mg/L	96 h	fish	<i>Pimephales promelas</i>		
1-ethylpyrrolidin-2-one (2687-91-4)	EC <sub>50</sub>	> 104 mg/L	48 h	<i>Daphnia</i>		OECD 202	
	EC <sub>50</sub>	> 101 mg/L	72 h	algae	<i>Desmodesmus subspicatus</i>	OECD 201	

#### 12.1.2. Chronic (long-term) toxicity

##### For components

Substance (CAS Nr.)	Type	Value	Exposure time	Species	Organism	Method	Remark
styrene (100-42-5)	NOEC	1,01 mg/l	21 days	crustacea	<i>Daphnia magna</i>	OECD 211	
1-ethylpyrrolidin-2-one (2687-91-4)	NOEC	12,5 mg/l	21 days	Daphnia		OECD 211	

# SAFETY DATA SHEET according to Regulation 1907/2006



Product name: 6400 Multi Fiber

Creation date: 2.10.2010 · Revision: 3.7.2019 · Version: 1

## 12.2. Persistence and degradability

### 12.2.1. Abiotic degradation, physical- and photo-chemical elimination

No information.

### 12.2.2. Biodegradation

**For components**

Substance (CAS Nr.)	Type	Rate	Time	Evaluation	Method	Remark
styrene (100-42-5)	biodegradability	70,9 %	28 days	readily biodegradable	ISO DIN 9408	aerobic, activated sludge

## 12.3. Bioaccumulative potential

### 12.3.1. Partition coefficient

**For components**

Substance (CAS Nr.)	Media	Value	Temperature	pH	Concentration	Method
styrene (100-42-5)	log Kow	2,95				

### 12.3.2. Bioconcentration factor (BCF)

**For components**

Substance (CAS Nr.)	Type	Organism	Value	Duration	Evaluation	Method	Remark
styrene (100-42-5)	BCF		74				Calculated value
styrene (100-42-5)	BCF	fish	13,5				

## 12.4. Mobility in soil

### 12.4.1. Known or predicted distribution to environmental compartments

No information.

### 12.4.2. Surface tension

No information.

### 12.4.3. Adsorption/Desorption

**For components**

Substance (CAS Nr.)	Type	Criterion	Value	Evaluation	Method	Remark
styrene (100-42-5)	Soil		352			Koc
styrene (100-42-5)	Soil	log KOC	2,55			

## 12.5. Results of PBT and vPvB assessment

No evaluation.

## 12.6. Other adverse effects

No information.

## 12.7. Additional information

**For product**

Do not allow to reach ground water, water courses or sewage system.  
Danger to drinking water if even small quantities leak into ground water.  
Water hazard class 2 (self-assessment): hazardous for water.

# SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **6400 Multi Fiber**

Creation date: **2.10.2010** · Revision: **3.7.2019** · Version: **1**

## SECTION 13. DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

#### 13.1.1. Product / Packaging disposal

##### Waste chemical

Dispose of in accordance with applicable waste disposal regulation. Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste. Do not dispose together with household garbage.

##### Waste codes / waste designations according to LoW

07 02 08\* - other still bottoms and reaction residues

##### Packaging

Dispose of in accordance with applicable waste disposal regulation. Deliver completely emptied containers to approved waste disposal authorities.

#### 13.1.2. Waste treatment-relevant information

-

#### 13.1.3. Sewage disposal-relevant information

-

#### 13.1.4. Other disposal recommendations

-

## SECTION 14. TRANSPORT INFORMATION

### 14.1. UN number

UN 1866

### 14.2. UN proper shipping name

RESIN SOLUTION

### 14.3. Transport hazard class(es)

3

### 14.4. Packing group

III

### 14.5. Environmental hazards

NO.

### 14.6. Special precautions for user

#### Limited quantities

5 L

#### Tunnel restriction code

(D/E)

#### IMDG flashpoint

31 °C, c.c.

#### IMDG EmS

F-E, S-E



### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Goods may not be carried in bulk in bulk containers, containers or vehicles.

# SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **6400 Multi Fiber**

Creation date: **2.10.2010** · Revision: **3.7.2019** · Version: **1**

## SECTION 15. REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (including last amendment Commission Regulation (EU) 2015/830)
- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

#### 15.1.1. Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-guideline)

EU limit values and category: B(b) 250 g/l. VOC Content: < 250 g/l

### 15.2. Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## SECTION 16. OTHER INFORMATION

### Indication of changes

-

### Abbreviations and acronyms

ATE - Acute Toxicity Estimate  
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road  
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
CEN - European Committee for Standardisation  
C&L - Classification and Labelling  
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008  
CAS# - Chemical Abstracts Service number  
CMR - Carcinogen, Mutagen, or Reproductive Toxicant  
CSA - Chemical Safety Assessment  
CSR - Chemical Safety Report  
DMEL - Derived Minimal Effect Level  
DNEL - Derived No Effect Level  
DPD - Dangerous Preparations Directive 1999/45/EC  
DSD - Dangerous Substances Directive 67/548/EEC  
DU - Downstream User  
EC - European Community  
ECHA - European Chemicals Agency  
EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS)  
EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway)  
EEC - European Economic Community  
EINECS - European Inventory of Existing Commercial Substances  
ELINCS - European List of notified Chemical Substances  
EN - European Standard  
EQS - Environmental Quality Standard  
EU - European Union  
Euphrac - European Phrase Catalogue  
EWC - European Waste Catalogue (replaced by LoW – see below)  
GES - Generic Exposure Scenario  
GHS - Globally Harmonized System  
IATA - International Air Transport Association  
ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air  
IMDG - International Maritime Dangerous Goods  
IMSBC - International Maritime Solid Bulk Cargoes  
IT - Information Technology  
IUCLID - International Uniform Chemical Information Database  
IUPAC - International Union for Pure Applied Chemistry  
JRC - Joint Research Centre  
Kow - octanol-water partition coefficient

# SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **6400 Multi Fiber**

Creation date: **2.10.2010** · Revision: **3.7.2019** · Version: **1**

LC<sub>50</sub> - Lethal Concentration to 50 % of a test population  
LD<sub>50</sub> - Lethal Dose to 50% of a test population (Median Lethal Dose)  
LE - Legal Entity  
LoW - List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)  
LR - Lead Registrant  
M/I - Manufacturer / Importer  
MS - Member States  
MSDS - Material Safety Data Sheet  
OC - Operational Conditions  
OECD - Organization for Economic Co-operation and Development  
OEL - Occupational Exposure Limit  
OJ - Official Journal  
OR - Only Representative  
OSHA - European Agency for Safety and Health at work  
PBT - Persistent, Bioaccumulative and Toxic substance  
PEC - Predicted Effect Concentration  
PNEC(s) - Predicted No Effect Concentration(s)  
PPE - Personal Protection Equipment  
(Q)SAR - Qualitative Structure Activity Relationship  
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006  
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail  
RIP - REACH Implementation Project  
RMM - Risk Management Measure  
SCBA - Self-Contained Breathing Apparatus  
SDS - Safety data sheet  
SIEF - Substance Information Exchange Forum  
SME - Small and Medium sized Enterprises  
STOT - Specific Target Organ Toxicity  
(STOT) RE - Repeated Exposure  
(STOT) SE - Single Exposure  
SVHC - Substances of Very High Concern  
UN - United Nations  
vPvB - Very Persistent and Very Bioaccumulative

## Key literature references and sources for data

-

## List of relevant H phrases

H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H360D May damage the unborn child.  
H361d Suspected of damaging the unborn child.  
H372 Causes damage to organs through prolonged or repeated exposure .  
H412 Harmful to aquatic life with long lasting effects.



- Provided correct labelling of the product
- Compliance with the local legislation
- Provided correct classification of the product
- Provided adequate transport data

© BENS Consulting | [www.bens-consulting.com](http://www.bens-consulting.com)

# SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **6400 Multi Fiber**

Creation date: **2.10.2010** · Revision: **3.7.2019** · Version: **1**

The information of this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under Section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.