

Description

High gloss silver paint for restoring the appearance of wheel rims and decorative wheel covers. Based on nitro resin with high quality aluminium pigments.




Features & Benefits

- very good adhesion to a variety of substrates
- suitable for chrome, metal and plastic parts
- quick drying
- high covering power, economic in use.

Substrate preparation

Surfaces to be treated must be clean, dry, rust-free and grease-free.

Application data

	<p>Mixing ratio The product is ready for use!</p>								
	<p>Application Shake can thoroughly until the mixing balls move freely.</p> <table data-bbox="352 1265 869 1451"> <tr> <td>Number of coats</td> <td>2 – 3</td> </tr> <tr> <td>Spraying distance</td> <td>25 – 30 cm</td> </tr> <tr> <td>Flash-off</td> <td>3 – 5 min</td> </tr> <tr> <td>Dry film thickness</td> <td>30 – 40 microns</td> </tr> </table> <p>After spraying, turn the can upside down and spray until the valve is clean. It is strongly recommended that ready to use product is applied at above 15 °C/59 °F.</p>	Number of coats	2 – 3	Spraying distance	25 – 30 cm	Flash-off	3 – 5 min	Dry film thickness	30 – 40 microns
Number of coats	2 – 3								
Spraying distance	25 – 30 cm								
Flash-off	3 – 5 min								
Dry film thickness	30 – 40 microns								
	<p>Drying</p> <table data-bbox="352 1659 762 1823"> <tr> <td>Dust dry at 20 °C/68 °F</td> <td>10 min</td> </tr> <tr> <td>Touch dry at 20 °C/68 °F</td> <td>60 min</td> </tr> <tr> <td>Through dry at 20 °C/68 °F</td> <td>24 h</td> </tr> </table>	Dust dry at 20 °C/68 °F	10 min	Touch dry at 20 °C/68 °F	60 min	Through dry at 20 °C/68 °F	24 h		
Dust dry at 20 °C/68 °F	10 min								
Touch dry at 20 °C/68 °F	60 min								
Through dry at 20 °C/68 °F	24 h								

Technical Data Sheet



7007 Rim Restore Spray, Silver Wheel Sprayable Paint

Ver.: 2020-1

Prod. Nr.	Description	Volume	Packaging Box
7007	Silver	400 ml	12

VOC

(2004/42/IIIB(e)(840)380

Shelf life

Min. 24 months from the production date under normal storage conditions and unopened can.

Additional Information

FOR PROFESSIONAL USE ONLY!

Always read the instructions.

IMPORTANT: This product contains hazardous substances at work so it is necessary to always use/wear appropriate protective equipment. For further instructions, check the label on the product and safety data sheet. A person who uses the product for any purpose other than recommended in this technical data sheet, acts at his own risk. It is the user's responsibility to take all necessary steps to fulfil the local legislation.

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public.

Information and methods described are based on the best information and practices known to us and serve merely as guidelines for optimal use, without liability to performance, results or fitness for any intended use. We do not accept any responsibility for the behaviour of the product or damage arising from the use of the product. Before using the product, the user must check if this is the latest version.

All products mentioned in this data sheet are trademarks owned by Silco.