

7010 Underbody Bitumen, Bitumen Underbody Protection

Ver.: 2020-1

Description

Underbody bitumen based coating, developed for dip and sag free application that ensures excellent and durable protection against corrosion, stone chip, salt, etc. Can be applied on parts of chassis, under floor panel, inside wheel casting, etc. Avoid application on brake or exhaust system.

Features & Benefits

Excellent barrier formation

Easy to apply

Strong adhesion on raw or painted metal, plastic materials or old underbody protection

Builds protective film against stone chips, salt, noise etc.





Resistant to water, acid, alkaline

Not over-paintable

Substrate preparation

Surfaces to be treated must be clean, dry, rust-free and grease-free.

Application data

	<p>Mixing ratio</p> <p>The product is ready to use! Shake the product before use.</p>
	<p>Spray gun set /air inlet 2 - 5 bar</p>
	<p>Application</p> <p>Number of coats 1 - 2 coats Total dry film build 300 microns Application air temperature 5 - 25°C / 41 – 77 °F</p>
	<p>Drying</p> <p>Dust dry at 20 °C/68 °F 3 - 5 h Touch dry at 20 °C/68 °F 12 - 16 h Fully dry at 20 °C/68 °F 24 h</p>

7010 Underbody Bitumen, Bitumen Underbody Protection

Ver.: 2020-1

Complementary products

Application gun (Prod. Nr. 2006)

Prod. Nr.	Description	Volume	Packaging Box
7010	Black	1 L	12

VOC

2004/42/II B(e)(840) 456

Shelf life

Min. 24 months from the production date under normal storage conditions and unopened can.

Additional Information

FOR PROFESSIONAL USE ONLY!

Always read the instructions.

IMPORTANT: This product contains hazardous substances at work so it is necessary to always use/wear appropriate protective equipment. For further instructions, check the label on the product and safety data sheet. A person who uses the product for any purpose other than recommended in this technical data sheet, acts at his own risk. It is the user's responsibility to take all necessary steps to fulfil the local legislation.

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public.

Information and methods described are based on the best information and practices known to us and serve merely as guidelines for optimal use, without liability to performance, results or fitness for any intended use. We do not accept any responsibility for the behaviour of the product or damage arising from the use of the product. Before using the product, the user must check if this is the latest version.

All products mentioned in this data sheet are trademarks owned by Silco.