

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **7300 M30 Superfast 2K Primer**

Creation date: **16.7.2019** · Revision: **22.7.2019** · Version: **1**

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name

7300 M30 Superfast 2K Primer



chemius.net/FjBbe

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Coating.

Uses advised against

No information.

1.3. Details of the supplier of the safety data sheet

Supplier

SILCO, D.O.O.

Address: Šentrupert 5 a, 3303 Gomilsko, Slovenia

Phone: +386 3 703 3180

Fax: +386 3 703 3188

E-mail: n.cvilak@silco-automotive.com

Point of contact for safety info: Nejc Cvilak

1.4. Emergency telephone number

Emergency

112

Supplier

+386 3 703 3180

SECTION 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Aerosol 1; H222 Extremely flammable aerosol.

Aerosol 1; H229 Pressurised container: May burst if heated.

Skin Irrit. 2; H315 Causes skin irritation.

Eye Irrit. 2; H319 Causes serious eye irritation.

STOT SE 3; H336 May cause drowsiness or dizziness.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **7300 M30 Superfast 2K Primer**

Creation date: **16.7.2019** · Revision: **22.7.2019** · Version: **1**

2.2 Label elements

2.2.1. Labelling according to Regulation (EC) No 1272/2008 [CLP]



Signal word: **Danger**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH018 In use, may form flammable/explosive vapour-air mixture.

EUH208 Contains hexamethylene diisocyanate, oligomers; maleic anhydride. May produce an allergic reaction.

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulation.

2.2.2. Contains:

acetone (CAS: 67-64-1, EC: 200-662-2, Index: 606-001-00-8)

n-butyl acetate (CAS: 123-86-4, EC: 204-658-1, Index: 607-025-00-1)

ethyl acetate (CAS: 141-78-6, EC: 205-500-4, Index: 607-022-00-5)

toluene (CAS: 108-88-3, EC: 203-625-9, Index: 601-021-00-3)

2.2.3. Special provisions

Without adequate ventilation, explosive vapors may accumulate.

2.3. Other hazards

No information.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

For mixtures see 3.2.

SAFETY DATA SHEET according to Regulation 1907/2006Product name: **7300 M30 Superfast 2K Primer**Creation date: **16.7.2019** · Revision: **22.7.2019** · Version: **1****3.2. Mixtures**

Name	CAS EC Index	%	Classification according to Regulation (EC) No 1272/2008 (CLP)	Specific Conc. Limits	REACH Registration No.
dimethyl ether	115-10-6 204-065-8 603-019-00-8	25-<50	Flam. Gas 1; H220 Press. Gas; H280		01-2119472128-37
acetone	67-64-1 200-662-2 606-001-00-8	10-<25	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336		01-2119471330-49
xylene [C]	1330-20-7 215-535-7 601-022-00-9	10-<25	Flam. Liq. 3; H226 Acute Tox. 4; H312 Skin Irrit. 2; H315 Acute Tox. 4; H332		01-2119488216-32
n-butyl acetate	123-86-4 204-658-1 607-025-00-1	2,5-<5	Flam. Liq. 3; H226 STOT SE 3; H336		01-2119485493-29
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7	2,5-<5	Flam. Liq. 3; H226		01-2119475791-29
ethyl acetate	141-78-6 205-500-4 607-022-00-5	1-<2,5	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336		01-2119475103-46
ethylbenzene	100-41-4 202-849-4 601-023-00-4	1-<2,5	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Acute Tox. 4; H332 STOT RE 2; H373		01-2119489370-35
toluene	108-88-3 203-625-9 601-021-00-3	1-<2,5	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Repr. 2; H361d STOT RE 2; H373		01-2119471310-51
2-butoxyethanol	111-76-2 203-905-0 603-014-00-0	1-<2,5	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute Tox. 4; H332		01-2119475108-36
hexamethylene diisocyanate, oligomers	28182-81-2 500-060-2 -	≥0,1-<1	Skin Sens. 1; H317		-
maleic anhydride	108-31-6 203-571-6 607-096-00-9	≥0,1-<1	Acute Tox. 4; H302 Skin Corr. 1B; H314 Skin Sens. 1; H317 Resp. Sens. 1; H334		01-2119472428-31

Notes for substances:

C Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers.
In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

General notes

When in doubt or if feeling unwell seek medical assistance. Show the safety data sheet and label to the physician. Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency.

Following inhalation

Remove patient to fresh air - move out of dangerous area. Obtain professional medical help! If symptoms develop and persist, seek medical attention.

Following skin contact

Take off all contaminated clothing. Areas of the body that have come into contact with the product must be rinsed with water. If symptoms develop and persist, seek medical attention.

Following eye contact

Immediately flush eyes with running water, keeping eyelids apart. If irritation persists, seek professional medical attention.

Following ingestion

Not likely. Do not induce vomiting! In case of doubt or if feeling unwell seek medical help. Show the physician the safety data sheet or label. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation

Vapours may cause drowsiness and dizziness.

Skin contact

Itching, redness, pain.

Eye contact

Redness, tearing, pain.

Ingestion

May cause nausea/vomiting and diarrhea.

May cause abdominal discomfort.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

No special precautions required.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

In case of a fire toxic gases can be generated; do not inhale gases/smoke.

5.3. Advice for firefighters

Protective actions

Cool containers at risk with water spray. If possible remove containers from endangered area. In case of fire aerosols can explode and be propelled to considerable distances in different directions. Prolonged heating can cause an explosion. Vapours can form explosive mixtures with air.

SAFETY DATA SHEET according to Regulation 1907/2006

Product name: **7300 M30 Superfast 2K Primer**
Creation date: **16.7.2019** · Revision: **22.7.2019** · Version: **1**



Special protective equipment for firefighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

Additional information

Contaminated firefighting water and fire residues must be disposed of in accordance with the local regulations.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment

Use personal protective equipment (Section 8).

Emergency procedures

Ensure adequate ventilation. Keep away from sources of ignition and/or heat; No smoking! Prevent access to unprotected personnel. Do not breathe vapour or mist. Avoid contact with skin, eyes and clothing. No action shall be taken involving any personal risk or without suitable training. Prevent access to unauthorised personnel. Evacuate the danger zone. Do not use open fire and keep away all sources of ignition.

6.1.2. For emergency responders

Use personal protective equipment.

6.2. Environmental precautions

In case of release into the environment, inform the relevant authorities.

6.3. Methods and material for containment and cleaning up

6.3.1. For containment

-

6.3.2. For cleaning up

Collect the spray cans and hand them over to an authorized waste disposal contractor. Absorb product (with inert material), collect it in special container and dispose it to a licensed hazardous-waste disposal contractor. Use spark-proof tools. Prevent release into the sewer, water, basements or confined areas. Ventilate the premises.

6.3.3. Other information

See Section 7: safe handling.

6.4. Reference to other sections

See also Sections 8 and 13.

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

7.1.1. Protective measures

Measures to prevent fire

Ensure adequate ventilation. Take precautionary measures against static discharges. Keep away from sources of ignition - no smoking. Use spark-proof tools. Do not spray on a naked flame or incandescent material. Pressurized container; protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Measures to prevent aerosol and dust generation

Use general or local exhaust ventilation to prevent inhaling vapours and aerosols.

Measures to protect the environment

Do not discharge into drains, surface water and soil. After use immediately close container tightly.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **7300 M30 Superfast 2K Primer**

Creation date: **16.7.2019** · Revision: **22.7.2019** · Version: **1**

7.1.2. Advice on general occupational hygiene

Do not eat, drink or smoke while working. Do not breathe vapours/mist. Use good personal hygiene practices – wash hands at breaks and when done working with material.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1. Technical measures and storage conditions

Store in accordance with local regulations. Protect from open fire, heat and direct sunlight. Keep away from food, drink and animal feeding stuffs. Keep away from oxidising substances. Keep away from sources of ignition - no smoking.

7.2.2. Packaging materials

Store only in original container.

7.2.3. Requirements for storage rooms and vessels

Close opened containers after use. Put the containers upright to prevent from leaking. Do not store in unlabelled containers.

7.2.4. Storage class

-

7.2.5. Further information on storage conditions

-

7.3. Specific end use(s)

Recommendations

-

Industrial sector specific solutions

-

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

8.1.1. Occupational exposure limit values

Name (CAS)	Limit values		Short-term exposure limit		Remarks	Biological Tolerance Values
	ml/m ³ (ppm)	mg/m ³	ml/m ³ (ppm)	mg/m ³		
Acetone (67-64-1)	500	1210	1500	3620		
2-Butoxyethanol (111-76-2)	25	123	50	246	Sk, BMGV	240 mmol butoxyacetic acid/mol creatinine in urine - Post shift
Butyl acetate (123-86-4)	150	724	200	966		
Dimethyl ether (115-10-6)	400	766	500	958		
Ethyl acetate (141-78-6)	200	734	400	1468		
Ethylbenzene (100-41-4)	100	441	125	552	Sk	
Maleic anhydride (108-31-6)	-	1	-	3	Sen	
1-Methoxypropyl acetate (108-65-6)	50	274	100	548	Sk	
Toluene (108-88-3)	50	191	100	384	Sk	
Xylene, o-,m-,p- or mixed isomers (1330-20-7)	50	220	100	441	Sk, BMGV	650 mmol methyl hippuric acid/mol creatinine in urine - Post shift

Product name: **7300 M30 Superfast 2K Primer**Creation date: **16.7.2019** · Revision: **22.7.2019** · Version: **1**

8.1.2. Information on monitoring procedures

BS EN 14042:2003 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 482:2012+A1:2015 Workplace exposure. General requirements for the performance of procedures for the measurement of chemical agents. BS EN 689:2018 Workplace exposure. Measurement of exposure by inhalation to chemical agents. Strategy for testing compliance with occupational exposure limit values.

8.1.3. DNEL/DMEL values

No information.

8.1.4. PNEC values

No information.

8.2. Exposure controls

8.2.1. Appropriate engineering control

Substance/mixture related measures to prevent exposure during identified uses

Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Avoid contact with skin, eyes and clothes. Do not breathe vapours/aerosols. Handle in accordance with good industrial hygiene and safety practice.

Organisational measures to prevent exposure

Remove all contaminated clothes immediately and wash them before reuse.

Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration. Keep away from food, drink and animal feeding stuffs.

8.2.2. Personal protective equipment

Eye and face protection

Tight fitting protective goggles (EN 166).

Hand protection

Protective gloves (EN 374). Observe the manufacturer's instructions regarding the use, storage, maintenance and replacement of gloves. In case of damage or at the first signs of wear and tear, change the gloves immediately. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. The penetration time is determined by the protective glove manufacturer and must be observed.

Appropriate materials

Material	Thickness	Penetration Time	Remark
Nitrile			
Butyl rubber	0,7 mm		

Skin protection

Cotton protective clothing and shoes that cover the entire foot (EN ISO 20345).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory protection. Breathing mask with filter type A1P2.

Thermal hazards

-

8.2.3. Environmental exposure controls

Technical measures to prevent exposure

Do not allow product to reach drains, sewage systems or ground water.

SAFETY DATA SHEET according to Regulation 1907/2006

Product name: 7300 M30 Superfast 2K Primer
Creation date: 16.7.2019 · Revision: 22.7.2019 · Version: 1



SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

- Physical state:	liquid; aerosol
- Colour:	according to specification
- Odour:	characteristic

Important health, safety and environmental information

- pH	No information.
- Melting point/freezing point	No information.
- Initial boiling point/boiling range	-24,9 °C
- Flash point	-42 °C (without propellant gas)
- Evaporation rate	No information.
- Flammability (solid, gas)	235 °C
- Explosion limits (vol%)	1,1 – 18,6 vol %
- Vapour pressure	3400 hPa
- Vapour density	No information.
- Density	Density: 1,00227 g/cm ³ at 20 °C
- Solubility	Water: insoluble
- Partition coefficient	No information.
- Auto-ignition temperature	Not self-igniting.
- Decomposition temperature	No information.
- Viscosity	No information.
- Explosive properties	Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.
- Oxidising properties	No information.

9.2. Other information

- Weight organic solvents	86,6 % 86,63 % (VOC)
- Solid contents	11,9 %
- Remarks:	

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity

Stable under recommended transport or storage conditions.

10.2. Chemical stability

Product is stable under normal conditions of use, recommended handling and storage conditions.

10.3. Possibility of hazardous reactions

The product is stable under recommended storage and handling conditions.

10.4. Conditions to avoid

Protect from heat, direct sunlight, open fire, sparks.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: 7300 M30 Superfast 2K Primer

Creation date: 16.7.2019 · Revision: 22.7.2019 · Version: 1

10.5. Incompatible materials

Oxidants.

10.6. Hazardous decomposition products

Under normal use conditions no hazardous decomposition products are expected. In case of fire/explosion vapours/gases that pose a health hazard are released.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

(a) Acute toxicity

Name	Exposure route	Type	Species	Time	Value	Method	Remark
For product	oral	LD ₅₀	rat		71873 mg/kg		ATE
For product	dermal	LD ₅₀	rabbit		19425 mg/kg		ATE
For product	inhalation	LC ₅₀		4 h	267 mg/l		ATE

Additional information: The product is not classified for acute toxicity.

(b) Skin corrosion/irritation

Additional information: Causes skin irritation.

(c) Serious eye damage/irritation

Additional information: Causes serious eye irritation.

(d) Respiratory or skin sensitisation

Additional information: It contains at least one ingredient that can cause sensitisation. Can cause allergic reaction.

(e) (Germ cell) mutagenicity

No information.

(f) Carcinogenicity

No information.

(g) Reproductive toxicity

No information.

Summary of evaluation of the CMR properties

The product is not classified as carcinogenic, mutagenic or toxic for reproduction.

(h) STOT-single exposure

Additional information: May cause drowsiness or dizziness.

(i) STOT-repeated exposure

Additional information: STOT RE (repeated exposure): Not classified.

(j) Aspiration hazard

Additional information: Aspiration hazard: Not classified.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: 7300 M30 Superfast 2K Primer

Creation date: 16.7.2019 · Revision: 22.7.2019 · Version: 1

SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Acute (short-term) toxicity

No information.

12.1.2. Chronic (long-term) toxicity

No information.

12.2. Persistence and degradability

12.2.1. Abiotic degradation, physical- and photo-chemical elimination

No information.

12.2.2. Biodegradation

No information.

12.3. Bioaccumulative potential

12.3.1. Partition coefficient

No information.

12.3.2. Bioconcentration factor (BCF)

No information.

12.4. Mobility in soil

12.4.1. Known or predicted distribution to environmental compartments

No information.

12.4.2. Surface tension

No information.

12.4.3. Adsorption/Desorption

No information.

12.5. Results of PBT and vPvB assessment

No evaluation.

12.6. Other adverse effects

No information.

12.7. Additional information

For product

Water hazard class 2 (self-assessment): hazardous for water.

Do not allow to reach ground water, water courses or sewage system.

Danger to drinking water if even small quantities leak into ground water.

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

13.1.1. Product / Packaging disposal

Waste chemical

Dispose of in accordance with applicable waste disposal regulation. Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste. Do not dispose together with household garbage. Do not allow product to reach drains/sewage systems.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **7300 M30 Superfast 2K Primer**

Creation date: **16.7.2019** · Revision: **22.7.2019** · Version: **1**

Packaging

Dispose of in accordance with applicable waste disposal regulation. Deliver completely emptied containers to approved waste disposal authorities. Empty containers represent a fire hazard as they may contain flammable product residues and vapour. Uncleaned containers should not be perforated, cut or welded.

Waste codes / waste designations according to LoW

15 01 10* - packaging containing residues of or contaminated by dangerous substances

13.1.2. Waste treatment-relevant information

-

13.1.3. Sewage disposal-relevant information

-

13.1.4. Other disposal recommendations

-

SECTION 14. TRANSPORT INFORMATION

14.1. UN number

UN 1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

2

14.4. Packing group

Not applicable.

14.5. Environmental hazards

NO.

14.6. Special precautions for user

Limited quantities

1 L

Tunnel restriction code

(D)

IMDG flashpoint

-42 °C, c.c.

IMDG EmS

F-D, S-U



14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Goods may not be carried in bulk in bulk containers, containers or vehicles.

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (including last amendment Commission Regulation (EU) 2015/830)

- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **7300 M30 Superfast 2K Primer**

Creation date: **16.7.2019** · Revision: **22.7.2019** · Version: **1**

15.1.1. Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-guideline)

EU limit values and category: B(e) 840 g/l. VOC Content: < 840 g/l

15.1.2. Special instructions

Seveso III, P3a: flammable aerosols.

15.2. Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16. OTHER INFORMATION

Indication of changes

-

Abbreviations and acronyms

ATE - Acute Toxicity Estimate
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
CEN - European Committee for Standardisation
C&L - Classification and Labelling
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
CAS# - Chemical Abstracts Service number
CMR - Carcinogen, Mutagen, or Reproductive Toxicant
CSA - Chemical Safety Assessment
CSR - Chemical Safety Report
DMEL - Derived Minimal Effect Level
DNEL - Derived No Effect Level
DPD - Dangerous Preparations Directive 1999/45/EC
DSD - Dangerous Substances Directive 67/548/EEC
DU - Downstream User
EC - European Community
ECHA - European Chemicals Agency
EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS)
EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway)
EEC - European Economic Community
EINECS - European Inventory of Existing Commercial Substances
ELINCS - European List of notified Chemical Substances
EN - European Standard
EQS - Environmental Quality Standard
EU - European Union
Euphrac - European Phrase Catalogue
EWC - European Waste Catalogue (replaced by LoW – see below)
GES - Generic Exposure Scenario
GHS - Globally Harmonized System
IATA - International Air Transport Association
ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG - International Maritime Dangerous Goods
IMSBC - International Maritime Solid Bulk Cargoes
IT - Information Technology
IUCLID - International Uniform Chemical Information Database
IUPAC - International Union for Pure Applied Chemistry
JRC - Joint Research Centre
Kow - octanol-water partition coefficient
LC₅₀ - Lethal Concentration to 50 % of a test population
LD₅₀ - Lethal Dose to 50% of a test population (Median Lethal Dose)
LE - Legal Entity
LoW - List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)
LR - Lead Registrant
M/I - Manufacturer / Importer
MS - Member States

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **7300 M30 Superfast 2K Primer**

Creation date: **16.7.2019** · Revision: **22.7.2019** · Version: **1**

MSDS - Material Safety Data Sheet
OC - Operational Conditions
OECD - Organization for Economic Co-operation and Development
OEL - Occupational Exposure Limit
OJ - Official Journal
OR - Only Representative
OSHA - European Agency for Safety and Health at work
PBT - Persistent, Bioaccumulative and Toxic substance
PEC - Predicted Effect Concentration
PNEC(s) - Predicted No Effect Concentration(s)
PPE - Personal Protection Equipment
(Q)SAR - Qualitative Structure Activity Relationship
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
RIP - REACH Implementation Project
RMM - Risk Management Measure
SCBA - Self-Contained Breathing Apparatus
SDS - Safety data sheet
SIEF - Substance Information Exchange Forum
SME - Small and Medium sized Enterprises
STOT - Specific Target Organ Toxicity
(STOT) RE - Repeated Exposure
(STOT) SE - Single Exposure
SVHC - Substances of Very High Concern
UN - United Nations
vPvB - Very Persistent and Very Bioaccumulative

Key literature references and sources for data

-

List of relevant H phrases

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H336 May cause drowsiness or dizziness.
H361d Suspected of damaging the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure .



- Provided correct labelling of the product
- Compliance with the local legislation
- Provided correct classification of the product
- Provided adequate transport data

© BENS Consulting | www.bens-consulting.com

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **7300 M30 Superfast 2K Primer**

Creation date: **16.7.2019** · Revision: **22.7.2019** · Version: **1**

The information of this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under Section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.