Technical Data Sheet



8015 Tornado, Highly Concentrated Alkaline Pre-

Wash

Ver.: 2021-6

Description

Highly effective alkaline cleaner for insects and traffic film removal from all kinds of surfaces (metal, plastics...). Suitable for automatic car washes and self-service car washes. Recommended use of a nebulizer and high-pressure washer.

Features & Benefits

- pre-washing
- application on a dry vehicle
- insect residue removal
- suitable for extremely hard water
- grease and inert dirt removal from tile and plastic surfaces
- rim and engine bay cleaning, truck washing

Characteristics

Appearance:	Liquid
Colour:	Yellow
Perfume:	Characteristic
Specific weight (20°C):	~ 1.18
pH:	~ 13.1

* Effect on metals: Suitable for steel, chrome, plastic, ceramic, glass, and varnished surfaces

Mixing ratio



1:10 (10%) degreasing, engine cleaning, rim cleaning

1:40 (2.5%) - 1:60 (1,5%) prewashing, depends on level of dirtiness

Applications and method of use

8015 Tornado is used in self-service systems with osmosis water at a concentration of between 1,5 and 2,5% at the exit of the lance. If the product is used in combination with a concentrate nebulizer ranging from 1 to 2% depending on the amount of dirt to be removed.

* Caution: Avoid self-drying of the solution after application.

Prod. Nr.	Description	Volume	Packaging per Pallet
8015-25	/	25 kg	24 pcs

SILCO d.o.o., Šentrupert 5a, 3303 Gomilsko, Slovenija	
Tel.: +386 (0)3 703 31 80 / Fax.: +386 (0)3 703 31 88	Page 1
E-mail: info@silco-automotive.com / www.silco-automotive.com	

Technical Data Sheet



/

Wash

Ver.: 2021-6

8015-5

5 kg

72 pcs

silco

Shelf life

Max. 24 months from the production date under normal storage conditions (+5°C to +40°C) and unopened canister.

Additional Information

FOR PROFESSIONAL USE ONLY!

Always read the instructions.

IMPORTANT: This product contains hazardous substances at work so it is necessary to always use/wear appropriate protective equipment. For further instructions, check the label on the product and safety data sheet. A person who uses the product for any purpose other than recommended in this technical data sheet, acts at his own risk. It is the user's responsibility to take all necessary steps to fulfil the local legislation.

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public.

Information and methods described are based on the best information and practices known to us and serve merely as guidelines for optimal use, without liability to performance, results or fitness for any intended use. We do not accept any responsibility for the behaviour of the product or damage arising from the use of the product. Before using the product, the user must check if this is the latest version.

All products mentioned in this data sheet are trademarks owned by Silco.