SAFETY DATA SHEET according to regulation 1907/2006



Product name: 8022 Magic Foam

Creation date: 26.05.2021, Revision: 27.05.2021, version: 1.1

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product name 8022 Magic Foam



https://my.chemius.net/p/ttb484/en/pd/en

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Cleaning agent.

Uses advised against

No information.

1.3 Details of the supplier of the safety data sheet

Supplier

SILCO, D.O.O.

Šentrupert 5 a

3303 Gomilsko, Slovenia

+386 3 703 3180

n.cvilak@silco-automotive.com

1.4 Emergency Telephone Number

Emergency

112

Supplier

+386 3 703 3180

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Skin Corr. 1A; H314.1A Causes severe skin burns and eye damage.

Eye Dam. 1; H318 Causes serious eye damage.

Muta. 2; H341 Suspected of causing genetic defects.

Carc. 1A; H350.1A May cause cancer.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP]





Signal word: Danger

H314 Causes severe skin burns and eye damage.

H341 Suspected of causing genetic defects.

H350 May cause cancer.

P201 Obtain special instructions before use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/physician.

Contains:

tetrasodium ethylene diamine tetraacetate

1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C8-18(even numbered) and C18 unsaturated acyl) derivs., hydroxides, inner salts

phenolphthalein

Potassium hydroxide

Sodium hydroxide

Special provisions

Restricted to professional users.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

For mixtures see 3.2.

3.2 Mixtures

NAME	CAS EC INDEX REACH	%	CLASSIFICATION ACCORDING TO REGULATION (EC) NO 1272/2008 (CLP)	SPECIFIC CONC. LIMITS	NOTES FOR SUBSTANCES
tetrasodium ethylene diamine tetraacetate	64-02-8 200-573-9 607-428-00-2 01- 2119486762- 27	5 ≤ x < 7	Acute Tox. 4; H302 Eye Dam. 1; H318 Acute Tox. 4; H332 STOT RE 2; H373	/	/
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C8-18(even numbered) and C18 unsaturated acyl) derivs., hydroxides, inner salts	147170-44-3 931-333-8 - 01- 2119489410- 39	3 ≤ x < 4	Eye Dam. 1; H318 Aquatic Chronic 3; H412	Eye Dam. 1; H318; C ≥ 10% Eye Irrit. 2; H319; 4% ≤ C < 10%	/

phenolphthalein	77-09-8 201-004-7 604-076-00-1	2 ≤ x < 3	Muta. 2; H341 Carc. 1B; H350.1B Repr. 2; H361f	Carc. 1B; H350.1B; C ≥ 1%	/
alcohols, C12-14, ethoxylated	68439-50-9 - -	2 ≤ x < 3	Acute Tox. 4; H302 Eye Dam. 1; H318 Aquatic Chronic 3; H412	/	/
Potassium hydroxide	1310-58-3 215-181-3 019-002-00-8 01- 2119487136- 33	1 ≤ x < 2	Met. Corr. 1; H290 Acute Tox. 4; H302 Skin Corr. 1A; H314.1A Eye Dam. 1; H318	Skin Corr. 1A; H314.1A; C ≥ 5% Skin Corr. 1B; H314.1B; 2% ≤ C < 5% Skin Irrit. 2; H315; 0.5% ≤ C < 2% Eye Irrit. 2; H319; 0.5% ≤ C < 2%	/
Sodium hydroxide	1310-73-2 215-185-5 - 01- 2119457892- 27	0,3 ≤x < 0,4	Met. Corr. 1; H290 Skin Corr. 1A; H314.1A Eye Dam. 1; H318	Skin Corr. 1A; H314.1A; C ≥ 5% Skin Corr. 1B; H314.1B; 2% ≤ C < 5% Skin Irrit. 2; H315; 0.5% ≤ C < 2% Eye Irrit. 2; H319; 0.5% ≤ C < 2%	1

SECTION 4: FIRST AID MEASURES

4.1 First aid measures

General notes

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency. Person giving first aid should properly protect himself.

Following inhalation

Remove patient to fresh air - move out of dangerous area. Keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Seek medical help immediately.

Following skin contact

Take off all contaminated clothing. Areas of the body that have come into contact with the product must be rinsed with water. Immediately obtain professional medical help!

Following eye contact

Immediately flush eyes with running water, keeping eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Consult a physician immediately!

Following ingestion

Drink plenty of water in small sips. Do not induce vomiting! Never give anything by mouth to an unconscious person.

Immediately consult a doctor. Show the physician the safety data sheet or label.

4.2 Most important symptoms and effects, both acute and delayed

Following inhalation

Excessive exposure to spray mist, fog, or vapours may cause respiratory irritation.

Following skin contact

Skin burns: Signs/symptoms may include localised redness, swelling, itching, dryness, blistering.

Following eye contact

Causes burns: signs/symptoms include corneal damage, burns, pain, lacrimation, corrosive effects, partial or complete lost of sight.

Following ingestion

May cause nausea/vomiting and diarrhea. May cause abdominal discomfort.

4.3 Indication of any immediate medical attention and special treatment needed

No information.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide. Dry chemical powder. Water spray. Alcohol resistant foam.

Unsuitable extinguishing media

Full water jet.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

In case of a fire toxic gases can be generated; do not inhale gases/smoke.

5.3 Advice for firefighters

Protective actions

In case of fire evacuate the area. In case of fire or heating do not breathe fumes/vapours. No action shall be taken involving any personal risk or without suitable training. Cool the endangered containers with water spray.

Special protective equipment for fire-fighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

Additional information

Contaminated firefighting water must be disposed of in accordance with the regulations; do not allow to reach the sewage system.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Protective equipment

Use personal protective equipment (Section 8).

Precautionary measures

Ensure adequate ventilation.

Emergency procedures

No action shall be taken involving any personal risk or without suitable training. Evacuate the danger zone. Prevent access to unprotected personnel. Do not breathe vapour or mist. Avoid contact with skin, eyes and clothing.

For emergency responders

Use personal protective equipment.

6.2 Environmental precautions

Do not allow product to reach water/drains/sewage systems or permeable soil. If accidental large entry into water or ground occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

For containment

Stem the spill if this does not pose risks.

For cleaning up

Absorb product (with inert material), collect it in special container and dispose it to a licensed hazardous-waste disposal contractor. Make sure the leakage site is well aired. Dispose in accordance with applicable regulations (see Section 13).

OTHER INFORMATION

No information.

6.4 Reference to other sections

See also sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Protective measures

Measures to prevent fire

Ensure adequate ventilation. Ensure proper grounding of the equipment.

Measures to prevent aerosol and dust generation

Use general or local exhaust ventilation to prevent inhaling vapours and aerosols.

Measures to protect the environment

Do not discharge into drains, surface water and soil. After use immediately close container tightly.

Other measures

No information.

Advice on general occupational hygiene

Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Do not breathe vapours/mist. Avoid contact with skin, eyes and clothes. Wear suitable protective equipment; see Section 8. Remove contaminated clothes and wash them before reuse. Before entering areas where food is eaten, remove contaminated clothing and protective equipment. Refer to instructions on label and regulations for safety and health at work.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Store in accordance with local regulations. Keep in a cool, dry and well ventilated place. Keep away from incompatible products (see section 10). Keep away from heat and sources of ignition. Keep away from food, drink and animal feeding stuffs.

Packaging materials

Store only in original container.

Requirements for storage rooms and vessels

Close opened containers after use. Put the containers upright to prevent from leaking. Do not store in unlabelled containers.

Storage class

No information.

Further information on storage conditions No information.

7.3 Specific end use(s)

Recommendations

No information.

Industrial sector specific solutions

No information.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Occupational Exposure limit values

NAME	MG/M ³	ML/M ³	SHORT-TERM VALUE MG/M ³	SHORT-TERM VALUE ML/M ³	REMARK	BIOLOGICAL TOLERANCE VALUES
Potassium hydroxide (1310-58-3)	/	/	2	/	/	/
Sodium hydroxide (1310- 73-2)	/	/	2	/	/	1

Information on monitoring procedures

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 482:2012+A1:2015 Workplace exposure. General requirements for the performance of procedures for the measurement of chemical agents.

DNEL/DMEL values

For product

No information.

For components

NAME	TYPE	EXPOSURE ROUTE	EXP. FREQUENCY	REMARK	VALUE
tetrasodium ethylene diamine tetraacetate	Worker	inhalation	long term local effects	/	1.5 mg/m³
tetrasodium ethylene diamine tetraacetate	Worker	inhalation	short term local effects	/	3 mg/m³
tetrasodium ethylene diamine tetraacetate	Consumer	inhalation	long term local effects	/	0.6 mg/m³
tetrasodium ethylene diamine tetraacetate	Consumer	inhalation	short term local effects	/	1.2 mg/m³
tetrasodium ethylene diamine tetraacetate	Consumer	oral	long term systemic effects	/	25 mg/kg bw/day
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C8- 18(even numbered) and C18 unsaturated acyl) derivs., hydroxides, inner salts	Worker	inhalation	long term systemic effects	/	44 mg/m³
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C8- 18(even numbered) and C18 unsaturated acyl) derivs., hydroxides, inner salts	Worker	dermal	long term systemic effects	/	12.5 mg/kg bw/day

1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C8-18(even numbered) and C18 unsaturated acyl) derivs., hydroxides, inner salts	Consumer	inhalation	long term systemic effects	/	13.04 mg/m³
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C8-18(even numbered) and C18 unsaturated acyl) derivs., hydroxides, inner salts	Consumer	dermal	long term systemic effects	/	7.5 mg/kg bw/day
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C8-18(even numbered) and C18 unsaturated acyl) derivs., hydroxides, inner salts	Consumer	oral	long term systemic effects	/	7.5 mg/kg bw/day
alcohols, C12-14, ethoxylated	Worker	inhalation	long term systemic effects	/	294 mg/m³
alcohols, C12-14, ethoxylated	Worker	dermal	long term systemic effects	/	2080 mg/kg bw/day
alcohols, C12-14, ethoxylated	Consumer	inhalation	long term systemic effects	/	87 mg/m³
alcohols, C12-14, ethoxylated	Consumer	dermal	long term systemic effects	/	1250 mg/kg bw/day
alcohols, C12-14, ethoxylated	Consumer	oral	long term systemic effects	/	25 mg/kg bw/day
Potassium hydroxide	Worker	inhalation	long term local effects	/	1 mg/m³
Potassium hydroxide	Consumer	inhalation	long term local effects	/	1 mg/m³
Sodium hydroxide	Worker	inhalation	long term local effects	/	1 mg/m³
Sodium hydroxide	Consumer	inhalation	long term local effects	/	1 mg/m³

PNEC values

For product

No information.

For components

NAME	EXPOSURE ROUTE	REMARK	VALUE
tetrasodium ethylene diamine tetraacetate	fresh water	/	2.2 mg/L
tetrasodium ethylene diamine tetraacetate	water, intermittent release	/	1.2 mg/L
tetrasodium ethylene diamine tetraacetate	marine water	/	0.22 mg/L
tetrasodium ethylene diamine tetraacetate	water treatment plant	/	43 mg/L
tetrasodium ethylene diamine tetraacetate	soil	dry weight	0.72 mg/kg

1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C8-18(even numbered) and C18 unsaturated acyl) derivs., hydroxides, inner salts	fresh water	/	0.013 mg/L
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C8-18(even numbered) and C18 unsaturated acyl) derivs., hydroxides, inner salts	marine water	/	0.001 mg/L
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C8-18(even numbered) and C18 unsaturated acyl) derivs., hydroxides, inner salts	water treatment plant	/	3000 mg/L
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C8-18(even numbered) and C18 unsaturated acyl) derivs., hydroxides, inner salts	fresh water sediment	dry weight	14.8 mg/kg
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C8-18(even numbered) and C18 unsaturated acyl) derivs., hydroxides, inner salts	marine water sediment	dry weight	1.48 mg/kg
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C8-18(even numbered) and C18 unsaturated acyl) derivs., hydroxides, inner salts	soil	dry weight	0.8 mg/kg
alcohols, C12-14, ethoxylated	fresh water	/	0.074 mg/L
alcohols, C12-14, ethoxylated	water, intermittent release	/	0.004 mg/L
alcohols, C12-14, ethoxylated	marine water	/	0.007 mg/L
alcohols, C12-14, ethoxylated	water, marine, intermittent release	/	0 mg/L
alcohols, C12-14, ethoxylated	water treatment plant	/	10 g/L
alcohols, C12-14, ethoxylated	fresh water sediment	dry weight	66.67 mg/kg
alcohols, C12-14, ethoxylated	marine water sediment	dry weight	6.66 mg/kg
alcohols, C12-14, ethoxylated	soil	dry weight	1 mg/kg

8.2 Exposure controls

Appropriate engineering control

Substance/mixture related measures to prevent exposure during identified uses

Use good personal hygiene practices – wash hands at breaks and when done working with material. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothes. Do not eat, drink or smoke while working. Do not breathe vapours/aerosols. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Structural measures to prevent exposure

No information.

Organisational measures to prevent exposure

Remove all contaminated clothes immediately and wash them before reuse. Keep eyewash bottles or personal eyewash units and emergency showers available.

Technical measures to prevent exposure

Use only in closed systems. The use of adequate technical equipment must always take priority over personal protective equipment. Provide good ventilation and local exhaust in areas with increased concentration. Keep away from food, drink and animal feeding stuffs.

Personal protective equipment

Eye and face protection

Wear tight fitting protective goggles and face protection (EN 166).

Hand protection

Protective gloves (EN 374). Observe the manufacturer's instructions regarding the use, storage, maintenance and replacement of gloves. In case of damage or at the first signs of wear and tear, change the gloves immediately. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. The penetration time is determined by the protective glove manufacturer and must be observed.

Appropriate materials

Skin protection

Wear category II professional long-sleeved overalls and safety footwear (see Regulation (EU) 2016/425 and standard EN ISO 20344). Cotton protective clothing and shoes that cover the entire foot (EN ISO 20345). Protective work clothing resistant to liquid chemicals (EN 14605).

Respiratory protection

At elevated concentrations of vapours/aerosols in the air wear a mask (EN 140) with filter A2-P2 (EN 14387). 'High/elevated concentrations' means that the occupational exposure limit values have been exceeded. For dust/gas/vapor concentrations above the applicable filter limit, in case of oxygen concentrations below 17% or in vague conditions, autonomous self-contained breathing apparatus should be used, according to standard EN 137, EN 138.

Thermal hazards

No information.

Environmental exposure controls

Substance/mixture related measures to prevent exposure

No information.

Instruction measures to prevent exposure

No information.

Organisational measures to prevent exposure

No information.

Technical measures to prevent exposure

Do not allow product to reach drains, sewage systems or ground water.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical state

liquid

Colour

violet

Odour

characteristic

Important health, safety and environmental information

Odour threshold	No information.
рН	12.5
Melting point/Freezing point	No information.
Initial boiling point/boiling range	No information.
Flash point	>60°C
Evaporation rate	No information.
Flammability (solid, gas)	No information.
Explosion limits (vol%)	No information.
Vapour pressure	No information.

Vapour density	No information.
Density / weight	Relative density: 1.04
Solubility	Water: miscible
Partition coefficient	No information.
Auto-ignition temperature	No information.
Decomposition temperature	No information.
Viscosity	No information.
Explosive properties	Product is not explosive.
Oxidising properties	Not oxidising.

9.2 OTHER INFORMATION

Solids content	17.45 % (250 °C)
----------------	------------------

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

Stable under recommended transport or storage conditions.

10.2 Chemical stability

Product is stable under normal conditions of use, recommended handling and storage conditions.

10.3 Possibility of hazardous reactions

The product is stable under recommended storage and handling conditions.

10.4 Conditions to avoid

No special precautions required. Consider the directions for use and storage.

10.5 Incompatible materials

Acids.

10.6 Hazardous decomposition products

Under normal use conditions no hazardous decomposition products are expected. In case of fire/explosion vapours/gases that pose a health hazard are released.

SECTION 11: TOXICOLOGICAL INFORMATION

- 11.1 Information on toxicological effects
 - (a) Acute toxicity

For product

EXPOSURE ROUTE	TYPE	SPECIES	TIME	VALUE	METHOD	REMARK
inhalation	ATE	/	/	> 20 mg/l	/	/
oral	ATE	/	/	> 2000 mg/kg	/	/

For components

NAME	EXPOSURE ROUTE	TYPE	SPECIES	TIME	VALUE	METHOD	REMARK
tetrasodium ethylene diamine tetraacetate	oral	LD ₅₀	rat	/	1780 mg/kg	/	/
tetrasodium ethylene diamine tetraacetate	inhalation	LC ₅₀	rat	4 h	3 mg/l	/	/
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl, N-(C8-18(even numbered) and C18 unsaturated acyl) derivs., hydroxides, inner salts	oral	LD ₅₀	rat	/	> 2430 mg/kg	/	/
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl, N-(C8-18(even numbered) and C18 unsaturated acyl) derivs., hydroxides, inner salts	dermal	LD ₅₀	rat	/	> 2000 mg/kg	/	/
alcohols, C12-14, ethoxylated	oral	LD ₅₀	rat	/	2000 mg/kg	/	/
Potassium hydroxide	oral	LD ₅₀	rat	/	333 mg/kg	/	/
Sodium hydroxide	oral	LD ₅₀	rabbit	/	380 mg/kg	/	1
Sodium hydroxide	dermal	LD ₅₀	rat	/	1350 mg/kg	/	/

Additional information

The product is not classified for acute toxicity.

(b) Skin corrosion/irritation

No information.

Additional information

Causes severe burns and skin damage.

(c) Serious eye damage/irritation

No information.

Additional information

Causes serious eye damage.

(d) Respiratory or skin sensitisation

No information.

Additional information

The product is not classified as sensitising.

(e) (Germ cell) mutagenicity

No information.

(f) Carcinogenicity

No information.

(g) Reproductive toxicity

No information.

Summary of evaluation of the CMR properties

May cause cancer. Suspected of causing genetic defects.

(h) STOT-single exposure

No information.

Additional information

STOT SE (single exposure): Not classified.

(i) STOT-repeated exposure

No information.

Additional information

STOT RE (repeated exposure): Not classified.

(j) Aspiration hazard

No information.

Additional information

Aspiration hazard: Not classified.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Acute (short-term) toxicity

For components

NAME	TYPE	VALUE	EXPOSURE TIME	SPECIES	ORGANISM	METHOD	REMARK
tetrasodium ethylene diamine tetraacetate	LC ₅₀	> 100	96 h	fish	/	/	/
tetrasodium ethylene diamine tetraacetate	EC ₅₀	> 100 mg/L	72 h	algae	1	/	/
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C8-18(even numbered) and C18 unsaturated acyl) derivs., hydroxides, inner salts	EC ₅₀	1.9 mg/L	48 h	crustacea	/	/	/
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C8-18(even numbered) and C18 unsaturated acyl) derivs., hydroxides, inner salts	EC ₅₀	4.66 mg/L	72 h	algae	/	/	/
phenolphthalein	EC ₅₀	> 100 mg/L	48 h	crustacea	1	/	/
phenolphthalein	EC ₅₀	8.9 mg/L	72 h	algae	1	/	/
Sodium hydroxide	EC ₅₀	404 mg/L	72 h	algae	1	/	/

Chronic (long-term) toxicity For components

NAME	TYPE	VALUE	EXPOSURE TIME	SPECIES	ORGANISM	METHOD	REMARK
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C8-18(even numbered) and C18 unsaturated acyl) derivs., hydroxides, inner salts	NOEC	0.135 mg/l	37 days	fish	/	/	/
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C8-18(even numbered) and C18 unsaturated acyl) derivs., hydroxides, inner salts	NOEC	0.3 mg/l	21 days	crustacea	/	/	/
alcohols, C12-14, ethoxylated	NOEC	> 0.1 mg/l	/	fish	/	/	/

alcohols, C12-14, ethoxylated	NOEC	> 0.1 mg/l	/	crustacea	Daphnia	/	/
alcohols, C12-14, ethoxylated	NOEC	> 0.1 mg/l	/	algae	/	/	/

12.2 Persistence and degradability

Abiotic degradation, physical- and photo-chemical elimination

No information.

Biodegradation

For components

NAME	TYPE	RATE	TIME	EVALUATION	METHOD	REMARK
alcohols, C12-14, ethoxylated	-	/	/	readily biodegradable	/	/

12.3 Bioaccumulative potential

Partition coefficient

No information.

Bioconcentration factor (BCF)

No information.

12.4 Mobility in soil

Known or predicted distribution to environmental compartments

No information.

Surface tension

No information.

Adsorption/Desorption

No information.

12.5 Results of PBT and vPvB assessment

The product does not contain any PBT or vPvB substances in percentages greater than 0.1%.

12.6 Other adverse effects

No information.

12.7 Additional information

For product

Do not allow to reach ground water, water courses or sewage system.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product / Packaging disposal

Waste chemical

Dispose of in accordance with applicable waste disposal regulation. Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste. Do not allow product to reach drains/sewage systems.

Waste codes / waste designations according to LoW No information.

Packaging

Dispose of in accordance with applicable waste disposal regulation. Deliver completely emptied containers to approved waste disposal authorities.

Waste codes / waste designations according to LoW No information.

Waste treatment-relevant information No information.

Sewage disposal-relevant information

No information.

Other disposal recommendations No information.

ADR/RID	IMDG	IATA	ADN
	ПМОС	IATA	ADN
14.1 UN number			
UN 3266	UN 3266	UN 3266	UN 3266
14.2 UN proper shipping name			
CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S.	CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S.	CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S.	CORROSIVE LIQUID, BASIC INORGANIC, N.O.S.
14.3 Transport hazard class(es)			
8	8	8	8
14.4 Packing group	8	8	8
	II	II	II
14.5 Environmental hazards			
NO	NO	NO	NO
14.6 Special precautions for user			
Limited quantities 1 L EmS imited quantities F-A, S-B Special provisions 274 Packing Instructions unnel restriction code E) Tank instructions T11 Tank special provisions TP2, TP27		Limited Quantity Packing Instructions Y840 Limited Quantity Net Qty 0.5 L Passenger Packing Instruction Packing Instructions 851 Passenger Packing Instruction Net Qty 1 L	Limited quantities 1 L

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code							
Goods may not be carried in bulk in bulk containers, containers or vehicles.	Goods may not be carried in bulk in bulk containers, containers or vehicles.	Not given/not applicable	Not given/not applicable				

SECTION 15: REGULATORY INFORMATION

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
 - Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)(including last amendment Commission Regulation (EU) 2015/830)
 - Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-guideline) not applicable

Regulation EC 648/2004 on detergents

15% - <30%: anionic surfactants;5% - < 15%: EDTA and salts thereof;< 5%: non-ionic surfactants

Special instructions

Regulation (EC) No. 1907/2006 (REACH) Annex XVII - Terms of restriction: 3. Regulation (EC) No. 1907/2006 (REACH) Annex XVII - Terms of restriction: 28. Observe the regulations on employment and protection against dangerous substances for young people, pregnant women and nursing mothers.

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION

Indication of changes

2.2 Label elements 3.2 Mixtures 8.1 Control parameters 8.2 Exposure controls 11.1 Information on toxicological effects 12.1 Toxicity 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Key literature references and sources for data

No information.

Abbreviations and acronyms

ATE - Acute Toxicity Estimate

ADR - Agreement concerning the International Carriage of Dangerous Goods by Road

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

CEN - European Committee for Standardisation

C&L - Classification and Labelling

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

CAS# - Chemical Abstracts Service number

CMR - Carcinogen, Mutagen, or Reproductive Toxicant

CSA - Chemical Safety Assessment

CSR - Chemical Safety Report

DMEL - Derived Minimal Effect Level

DNEL - Derived No Effect Level

DPD - Dangerous Preparations Directive 1999/45/EC

DSD - Dangerous Substances Directive 67/548/EEC

DU - Downstream User

EC - European Community

ECHA - European Chemicals Agency

EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS)

EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway)

EEC - European Economic Community

EINECS - European Inventory of Existing Commercial Substances

ELINCS - European List of notified Chemical Substances

EN - European Standard

EQS - Environmental Quality Standard

EU - European Union

Euphrac - European Phrase Catalogue

EWC - European Waste Catalogue (replaced by LoW - see below)

GES - Generic Exposure Scenario

GHS - Globally Harmonized System

IATA - International Air Transport Association

ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG - International Maritime Dangerous Goods

IMSBC - International Maritime Solid Bulk Cargoes

IT - Information Technology

IUCLID - International Uniform Chemical Information Database

IUPAC - International Union for Pure Applied Chemistry

JRC - Joint Research Centre

Kow - octanol-water partition coefficient

LC50 - Lethal Concentration to 50 % of a test population

LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose)

LE - Legal Entity

LoW - List of Wastes (see http://ec.europa.eu/environment/waste/framework/list.htm)

LR - Lead Registrant

M/I - Manufacturer / Importer

MS - Member States

MSDS - Material Safety Data Sheet

OC - Operational Conditions

OECD - Organization for Economic Co-operation and Development

OEL - Occupational Exposure Limit

OJ - Official Journal

OR - Only Representative

OSHA - European Agency for Safety and Health at work

PBT - Persistent, Bioaccumulative and Toxic substance

PEC - Predicted Effect Concentration

PNEC(s) - Predicted No Effect Concentration(s)

PPE - Personal Protection Equipment

(Q)SAR - Qualitative Structure Activity Relationship

REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006

RID - Regulations concerning the International Carriage of Dangerous Goods by Rail

RIP - REACH Implementation Project

RMM - Risk Management Measure

SCBA - Self-Contained Breathing Apparatus

SDS - Safety data sheet

SIEF - Substance Information Exchange Forum

SME - Small and Medium sized Enterprises

STOT - Specific Target Organ Toxicity

(STOT) RE - Repeated Exposure

(STOT) SE - Single Exposure

SVHC - Substances of Very High Concern

UN - United Nations

vPvB - Very Persistent and Very Bioaccumulative

List of relevant H phrases

H290 May be corrosive to metals.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H341 Suspected of causing genetic defects.

H350 May cause cancer.

H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.