Technical Data Sheet



8024 DryAid Manual, Drying Aid for Manual Car Wash

Ver.: 2021-6

Description

Concentrated drying aid for a manual car wash. It breaks the surface tension of the water and enables the creation of macro water droplets that are drained from the surface. Drying Aid provides clean and shiny surfaces.

Features & Benefits

clean and shiny surface

Characteristics

Appearance: Liquid
Colour: Red

Perfume: Characteristic

Density (20°C): ~ 0,96 pH: ~ 5,9

* Harmless to all metals and painted surfaces under normal conditions of use

Mixing ratio



1:100 (1%) suitable for self-service tracks

1:50 (2%) suitable for manual drying with hand nebulizer

Applications and method of use

ON SELF-SERVICE TRACKS: to obtain a complete drying of the vehicles, from 20 to 30 grams of product per car is normally used, which is sucked by the metering pumps.

ON MANUAL WASHING: dilute 20 grams of wax in 5 liters of water, distribute the solution evenly on the bodywork wait a few minutes and remove the remaining drops with a suitable skin.

* Caution: Avoid self-drying of the solution after application.

Prod. Nr.	Description	Volume	Packaging per Pallet
8024-10	/	10kg	60 pcs

SILCO d.o.o., Šentrupert 5a, 3303 Gomilsko, Slovenija Tel.: +386 (0)3 703 31 80 / Fax.: +386 (0)3 703 31 88

E-mail: info@silco-automotive.com / www.silco-automotive.com

Technical Data Sheet



8024 DryAid Manual, Drying Aid for Manual Car Wash

Ver.: 2021-6

Shelf life

Max. 24 months from the production date under normal storage conditions (+5°C to +40°C) and unopened canister.

Additional Information

FOR PROFESSIONAL USE ONLY!

Always read the instructions.

IMPORTANT: This product contains hazardous substances at work so it is necessary to always use/wear appropriate protective equipment. For further instructions, check the label on the product and safety data sheet. A person who uses the product for any purpose other than recommended in this technical data sheet acts at his own risk. It is the user's responsibility to take all necessary steps to fulfill the local legislation.

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public.

Information and methods described are based on the best information and practices known to us and serve merely as guidelines for optimal use, without liability to performance, results, or fitness for any intended use. We do not accept any responsibility for the behavior of the product or damage arising from the use of the product. Before using the product, the user must check if this is the latest version.

All products mentioned in this data sheet are trademarks owned by Silco.