

8038 DryAid, Drying Aid with Wax for Automatic Car Wash

Ver.: 2021-6

Description

Effective drying aid for usage in automatic car wash services. It breaks the surface tension of the water and enables the creation of macro droplets. Quality wax provides a clean and long-lasting shiny appearance of the surface. Suitable for automatic car wash services.

Features & Benefits


- clean surface
- long-lasting shiny appearance

Characteristics

Appearance:	Liquid
Colour:	Amber
Perfume:	Characteristic
Density (20°C):	~ 0.95
pH:	~ 4

***Harmless to all metals and painted surfaces under normal conditions of use.**

Mixing ratio



1:100 (1%) – 1:50 (2%) depends on the desired shiny appearance of the surface

Applications and method of use

To obtain a complete drying of motor vehicles, from 15 to 20 grams of product per car is normally used, depending on the size of the vehicle. The product and its "frozen" solutions are usually recovered with slight heating without losing their properties.

*** Caution: Avoid self-drying of the solution after application.**

Prod. Nr.	Description	Volume	Packaging per Pallet
8038-25	/	25kg	24 pcs

8038 DryAid, Drying Aid with Wax for Automatic Car Wash

Ver.: 2021-6

Shelf life

Max. 24 months from the production date under normal storage conditions (+5°C to +40°C) and unopened canister.

Additional Information

FOR PROFESSIONAL USE ONLY!

Always read the instructions.

IMPORTANT: This product contains hazardous substances at work so it is necessary to always use/wear appropriate protective equipment. For further instructions, check the label on the product and safety data sheet. A person who uses the product for any purpose other than recommended in this technical data sheet acts at his own risk. It is the user's responsibility to take all necessary steps to fulfill the local legislation.

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public.

Information and methods described are based on the best information and practices known to us and serve merely as guidelines for optimal use, without liability to performance, results, or fitness for any intended use. We do not accept any responsibility for the behavior of the product or damage arising from the use of the product. Before using the product, the user must check if this is the latest version.

All products mentioned in this data sheet are trademarks owned by Silco.