

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **90.001 UniMix White**

Creation date: **17.6.2016** · Revision: **28.6.2018** · Version: **1**

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name

90.001 UniMix White



chemius.net/i0rd4

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Industrial varnish.

Uses advised against

No information.

1.3. Details of the supplier of the safety data sheet

Manufacturer

SILCO, D.O.O.

Address: Šentrupert 5 a, 3303 Gomilsko, Slovenia

Phone: +386 3 703 3180

Fax: +386 3 703 3188

E-mail: n.cvilak@silco-automotive.com

Point of contact for safety info: Nejc Cvilak

1.4. Emergency telephone number

Emergency

112

Supplier

+386 3 703 3180

SECTION 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Flam. Liq. 3; H226 Flammable liquid and vapour.

Asp. Tox. 1; H304 May be fatal if swallowed and enters airways.

Skin Irrit. 2; H315 Causes skin irritation.

Eye Irrit. 2; H319 Causes serious eye irritation.

STOT SE 3; H335 May cause respiratory irritation.

STOT SE 3; H336 May cause drowsiness or dizziness.

STOT RE 2; H373 May cause damage to organs through prolonged or repeated exposure.

Aquatic Chronic 3; H412 Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: 90.001 UniMix White

Creation date: 17.6.2016 · Revision: 28.6.2018 · Version: 1

2.2 Label elements

2.2.1. Labelling according to Regulation (EC) No 1272/2008 [CLP]



Signal word: **Danger**

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains poly(oxy-1,2-ethandiyl),.alpha.-[(2z)-3carboxy-1-oxo-2-propenyl]-.omega.-hydroxy-,c9-11-alkyl ethers; 2-butanone oxime; maleic anhydride. May produce an allergic reaction.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P370 + P378 In case of fire: Use powder for extinction.

P501 Dispose of contents/container in accordance with national regulation.

2.2.2. Contains:

n-butyl acetate (CAS: 123-86-4, EC: 204-658-1, Index: 607-025-00-1)

xylene (CAS: 1330-20-7, EC: 215-535-7, Index: 601-022-00-9)

solvent naphtha (petroleum), light arom. (CAS: 64742-95-6, EC: 265-199-0, Index: 649-356-00-4)

naphtha (petroleum), hydrotreated heavy (CAS: 64742-48-9, EC: 265-150-3, Index: 649-327-00-6)

2.2.3. Special provisions

Special hazards are not known or expected.

2.3. Other hazards

No information.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

For mixtures see 3.2.

3.2. Mixtures

Name	CAS EC Index	%	Classification according to Regulation (EC) No 1272/2008 (CLP)	Specific Conc. Limits	REACH Registration No.
aluminium powder (stabilised) [17]	7429-90-5 231-072-3 013-002-00-1	25-30	Flam. Sol. 1; H228 Water-react. 2; H261		-
n-butyl acetate	123-86-4 204-658-1 607-025-00-1	0,5-30	Flam. Liq. 3; H226 STOT SE 3; H336 EUH066		-

SAFETY DATA SHEET according to Regulation 1907/2006

 Product name: **90.001 UniMix White**

 Creation date: **17.6.2016** · Revision: **28.6.2018** · Version: **1**

Name	CAS EC Index	%	Classification according to Regulation (EC) No 1272/2008 (CLP)	Specific Conc. Limits	REACH Registration No.
xylene [C]	1330-20-7 215-535-7 601-022-00-9	5-20	Flam. Liq. 3; H226 Asp. Tox. 1; H304 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute Tox. 4; H332 STOT SE 3; H335 STOT RE 2; H373		-
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7	1-20	Flam. Liq. 3; H226		-
1-methoxy-2-propanol	107-98-2 203-539-1 603-064-00-3	0,02-12,5	Flam. Liq. 3; H226 STOT SE 3; H336		-
solvent naphtha (petroleum), light arom. [P]	64742-95-6 265-199-0 649-356-00-4	0,1-10	Flam. Liq. 3; H226 Asp. Tox. 1; H304 STOT SE 3; H335 STOT SE 3; H336 Aquatic Chronic 2; H411		-
naphtha (petroleum), hydrotreated heavy [P]	64742-48-9 265-150-3 649-327-00-6	7-10	Asp. Tox. 1; H304 STOT SE 3; H336		-
ethylbenzene	100-41-4 202-849-4 601-023-00-4	1-5	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Acute Tox. 4; H332 STOT RE 2; H373 (hearing organs)		-
poly(oxy-1,2-ethandiyl),.alpha.-[(2z)-3carboxy-1-oxo-2-propenyl]-.omega.-hydroxy-,c9-11-alkyl ethers	709014-50-6 - -	0,5-1	Skin Sens. 1; H317		-
butan-2-ol [C]	78-92-2 201-158-5 603-127-00-5	0,08-1	Flam. Liq. 3; H226 Eye Irrit. 2; H319 STOT SE 3; H335 STOT SE 3; H336		-
2-butanone oxime	96-29-7 202-496-6 616-014-00-0	0,1-1	Acute Tox. 4; H312 Skin Sens. 1; H317 Eye Dam. 1; H318 Carc. 2; H351		-
butan-1-ol	71-36-3 200-751-6 603-004-00-6	0,1-0,25	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335 STOT SE 3; H336		-
maleic anhydride	108-31-6 203-571-6 607-096-00-9	0,1-0,25	Acute Tox. 4; H302 Skin Corr. 1B; H314 Skin Sens. 1; H317 Resp. Sens. 1; H334		-
di-isobutyl ketone	108-83-8 203-620-1 606-005-00-X	<0,01	Flam. Liq. 3; H226 STOT SE 3; H335	STOT SE 3; H335: C ≥ 10 %	-

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **90.001 UniMix White**

Creation date: **17.6.2016** · Revision: **28.6.2018** · Version: **1**

Notes for substances:

C	Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
P	The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 (Table 3.1) or the S-phrases (2-)23-24-62 (Table 3.2) shall apply. This note applies only to certain complex oil-derived substances in Part 3.
T	This substance may be marketed in a form which does not have the physical hazards as indicated by the classification in the entry in Part 3. If the results of the relevant method or methods in accordance with Part 2 of Annex I of this Regulation show that the specific form of substance marketed does not exhibit this physical property or these physical hazards, the substance shall be classified in accordance with the result or results of this test or these tests. Relevant information, including reference to the relevant test method(s) shall be included in the safety data sheet.

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

General notes

When in doubt or if feeling unwell seek medical assistance. Show the safety data sheet and label to the physician. Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency. In case of unconsciousness bring patient into stable side position for transport and take care of breathing.

Following inhalation

Remove patient to fresh air - move out of dangerous area. Victim should rest in a warm place. If breathing is irregular or respiratory arrest occurs provide artificial respiration. In case of unconsciousness bring patient into stable side position and seek medical attention. Do not give anything to eat or drink to patient.

Following skin contact

Take off all contaminated clothing. Wash affected skin areas thoroughly with plenty of water and soap. If irritation of skin persists seek medical attention.

Following eye contact

After 5 minutes of rinsing, remove contact lenses, if present, and continue rinsing. Immediately flush eyes with plenty of clean water or physiological saline while keeping eyelids open (at least 15 minutes). If irritation persists, seek professional medical attention.

Following ingestion

Do not induce vomiting! Consult a physician. Show the physician the safety data sheet or label.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation

Excessive exposure to spray mist, fog, or vapours may cause respiratory irritation.
Symptoms include: headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, unconsciousness.

Skin contact

Contact with skin may cause irritation (redness, itching).

Eye contact

Contact with eyes can cause irritation (redness, tearing, pain).

Ingestion

May cause nausea/vomiting and diarrhea.
May cause abdominal discomfort.

Product name: **90.001 UniMix White**

Creation date: **17.6.2016** · Revision: **28.6.2018** · Version: **1**

4.3. Indication of any immediate medical attention and special treatment needed

-

SECTION 5. FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂).
Fire extinguishing powder.
Alcohol-resistant foam.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

Not available.

5.3. Advice for firefighters

Protective actions

Cool products/vessel/containers at risk with water spray jet.

Special protective equipment for firefighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

Additional information

Contaminated firefighting water and fire residues must be disposed of in accordance with the local regulations.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment

Do not breathe vapours/mist. Refer to protective measures listed in Sections 7 and 8. Do not breathe dust. Use personal safety breathing equipment.

Emergency procedures

Ensure adequate ventilation.

6.1.2. For emergency responders

Product has a very low flash point, which represents a great danger of fire or explosion. Large amount of flammable vapours can evaporate when spilled. Vapors may travel long distances along the ground or floor to an ignition source.

6.2. Environmental precautions

Do not allow to enter water/drains/sewerage. Avoid dispersing product in the water and ground. If accidental large entry into water or ground occurs, inform responsible authorities.

6.3. Methods and material for containment and cleaning up

6.3.1. For containment

-

Product name: **90.001 UniMix White**

Creation date: **17.6.2016** · Revision: **28.6.2018** · Version: **1**

6.3.2. For cleaning up

Absorb product (with inert material), collect it in special container and dispose it to a licensed hazardous-waste disposal contractor. Do not absorb spillage with sawdust or other combustible material. Pick up mechanically and remove it in accordance with regulation.

6.3.3. Other information

-

6.4. Reference to other sections

See also Sections 8 and 13.

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

7.1.1. Protective measures

Measures to prevent fire

Ensure adequate ventilation. Keep away from sources of ignition - no smoking. Take precautionary measures against static discharges. Use only explosion-proof devices. Prevent the formation of flammable or explosive concentrations of vapours in the air. Prevent the formation of concentrations of vapours in air above relevant occupational exposure limits. Protect from open fire and other sources of ignition or heat. Only use grounded containers and equipment when transporting / transferring - possible danger of accumulation of electrostatic charges. Antistatic clothes and footwear are recommended. Use spark-proof tools. Vapours are heavier than air and spread along floor. Vapours and air form explosive mixtures. Do not spray onto open flame or glowing body.

Measures to prevent aerosol and dust generation

-

Measures to protect the environment

-

7.1.2. Advice on general occupational hygiene

Do not eat, drink or smoke while working. Use good personal hygiene practices – wash hands at breaks and when done working with material. Avoid contact with skin and eyes. Consider measures required in Section 8 of this safety data sheet. Refer to legal, protective and safety regulations. Refer to instructions on label and regulations for safety and health at work. Do not breathe vapours/mist.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1. Technical measures and storage conditions

Keep in cool and well ventilated area. Do not smoke! Keep unauthorized personnel away. Keep away from oxidising substances. Store away from strong bases. Keep away from food, drink and animal feeding stuffs. Keep in tightly closed container. Keep in a dry place. Protect from cold (prevent freezing). Protect from open fire, heat and direct sunlight. Handle open containers with care. Do not allow product to reach water, drains and sewage systems! Do not expose to temperatures exceeding 50°C.

7.2.2. Packaging materials

-

7.2.3. Requirements for storage rooms and vessels

-

7.2.4. Storage class

-

7.2.5. Further information on storage conditions

-

7.3. Specific end use(s)

Recommendations

-

Product name: 90.001 UniMix White

Creation date: 17.6.2016 · Revision: 28.6.2018 · Version: 1

Industrial sector specific solutions

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

8.1.1. Occupational exposure limit values

Name (CAS)	Limit values		Short-term exposure limit		Remarks	Biological Tolerance Values
	ml/m ³ (ppm)	mg/m ³	ml/m ³ (ppm)	mg/m ³		
Aluminium metal inhalable dust (7429-90-5)	-	10	-	-		
Aluminium metal respirable dust (7429-90-5)	-	4	-	-		
Butan-1-ol (71-36-3)	-	-	50	154	Sk	
Butan-2-ol (78-92-2)	100	308	150	462		
Butyl acetate (123-86-4)	150	724	200	966		
2,6-Dimethylheptan-4-one (108-83-8)	25	148	-	-		
Ethylbenzene (100-41-4)	100	441	125	552	Sk	
Maleic anhydride (108-31-6)	-	1	-	3	Sen	
1-Methoxypropan-2-ol (107-98-2)	100	375	150	560	Sk	
1-Methoxypropyl acetate (108-65-6)	50	274	100	548	Sk	
Xylene, o-,m-,p- or mixed isomers (1330-20-7)	50	220	100	441	Sk, BMGV	650 mmol methyl hippuric acid/mol creatinine in urine - Post shift

8.1.2. Information on monitoring procedures

BS EN 14042:2003 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 482:2012+A1:2015 Workplace exposure. General requirements for the performance of procedures for the measurement of chemical agents. BS EN 689:2018 Workplace exposure. Measurement of exposure by inhalation to chemical agents. Strategy for testing compliance with occupational exposure limit values.

8.1.3. DNEL/DMEL values

No information.

8.1.4. PNEC values

No information.

8.2. Exposure controls

8.2.1. Appropriate engineering control

Substance/mixture related measures to prevent exposure during identified uses

Use good personal hygiene practices – wash hands at breaks and when done working with material. Avoid contact with eyes.

Organisational measures to prevent exposure

Do not eat, drink or smoke while working. Remove all contaminated clothes immediately and wash them before reuse.

Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration.

8.2.2. Personal protective equipment

Eye and face protection

Tight fitting protective goggles (EN 166).

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: 90.001 UniMix White

Creation date: 17.6.2016 · Revision: 28.6.2018 · Version: 1

Hand protection

Protective gloves (EN 374).

Appropriate materials

Material	Thickness	Penetration Time	Remark
Nitrile	0,1 mm	480 min	

Skin protection

Cotton protective clothing and shoes that cover the entire foot (EN ISO 20345).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory protection. Wear suitable protective breathing mask (EN 136) with filter A2-P2 (EN 14387).

Thermal hazards

-

8.2.3. Environmental exposure controls

-

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

-	Physical state:	liquid
-	Colour:	according to specification
-	Odour:	solvent like

Important health, safety and environmental information

-	pH	No information.
-	Melting point/freezing point	No information.
-	Initial boiling point/boiling range	No information.
-	Flash point	> 23 °C
-	Evaporation rate	No information.
-	Flammability (solid, gas)	25 °C
-	Explosion limits (vol%)	0,6 – 20 vol %
-	Vapour pressure	No information.
-	Vapour density	No information.
-	Density	Density: 1,03 – 2,115 g/cm ³
-	Solubility	No information.
-	Partition coefficient	No information.
-	Auto-ignition temperature	No information.
-	Decomposition temperature	No information.
-	Viscosity	No information.
-	Explosive properties	No information.
-	Oxidising properties	No information.

9.2. Other information

-	Remarks:	
---	----------	--

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: 90.001 UniMix White

Creation date: 17.6.2016 · Revision: 28.6.2018 · Version: 1

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity

-

10.2. Chemical stability

Product is stable under normal conditions of use, recommended handling and storage conditions.

10.3. Possibility of hazardous reactions

-

10.4. Conditions to avoid

Vapours and air can form explosive mixtures. Do not store above 50°C.

10.5. Incompatible materials

Oxidants.
Strong bases.
Strong acids.

10.6. Hazardous decomposition products

Under normal use conditions no hazardous decomposition products are expected.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

(a) Acute toxicity

Name	Exposure route	Type	Species	Time	Value	Method	Remark
2-methoxy-1-methylethyl acetate (108-65-6)	oral	LD ₅₀	rat		8500 mg/kg		
butan-1-ol (71-36-3)	dermal	LD ₅₀	rabbit		3400 mg/kg		
butan-1-ol (71-36-3)	inhalation	LC ₅₀	rabbit	4 h	8000 ppmV		gas
butan-1-ol (71-36-3)	oral	LD ₅₀	rat		790 mg/kg		

(b) Skin corrosion/irritation

Additional information: Causes skin and eye irritation.

(c) Serious eye damage/irritation

No information.

(d) Respiratory or skin sensitisation

Additional information: May cause an allergic skin reaction.

(e) (Germ cell) mutagenicity

No information.

(f) Carcinogenicity

No information.

(g) Reproductive toxicity

No information.

Summary of evaluation of the CMR properties

No information.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **90.001 UniMix White**

Creation date: **17.6.2016** · Revision: **28.6.2018** · Version: **1**

(h) STOT-single exposure

Additional information: May cause drowsiness or dizziness.

(i) STOT-repeated exposure

Additional information: May cause damage to organs through prolonged or repeated exposure.

(j) Aspiration hazard

No information.

SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Acute (short-term) toxicity

For components

Substance (CAS Nr.)	Type	Value	Exposure time	Species	Organism	Method	Remark
butan-1-ol (71-36-3)	LC ₅₀	100 mg/L	96 h	fish			

12.1.2. Chronic (long-term) toxicity

No information.

12.2. Persistence and degradability

12.2.1. Abiotic degradation, physical- and photo-chemical elimination

No information.

12.2.2. Biodegradation

No information.

12.3. Bioaccumulative potential

12.3.1. Partition coefficient

No information.

12.3.2. Bioconcentration factor (BCF)

No information.

12.4. Mobility in soil

12.4.1. Known or predicted distribution to environmental compartments

No information.

12.4.2. Surface tension

No information.

12.4.3. Adsorption/Desorption

No information.

12.5. Results of PBT and vPvB assessment

No evaluation.

12.6. Other adverse effects

No information.

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: 90.001 UniMix White

Creation date: 17.6.2016 · Revision: 28.6.2018 · Version: 1

12.7. Additional information

For product

Product is not readily biodegradable.

Avoid release to the environment.

Do not allow to reach ground water, water courses or sewage system.

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

13.1.1. Product / Packaging disposal

Waste chemical

Dispose according to regulations. Do not allow to enter sewers. Any disposal in the environment or discharging into water is prohibited.

Waste codes / waste designations according to LoW

08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances

Packaging

According to regulations.

Waste codes / waste designations according to LoW

15 01 10* - packaging containing residues of or contaminated by dangerous substances

13.1.2. Waste treatment-relevant information

-

13.1.3. Sewage disposal-relevant information

-

13.1.4. Other disposal recommendations

-

SECTION 14. TRANSPORT INFORMATION

14.1. UN number

UN 1263

14.2. UN proper shipping name

PAINT

14.3. Transport hazard class(es)

3

14.4. Packing group

III

14.5. Environmental hazards

NO.

14.6. Special precautions for user

Limited quantities

5 L

Tunnel restriction code

(D/E)



SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **90.001 UniMix White**

Creation date: **17.6.2016** · Revision: **28.6.2018** · Version: **1**

IMDG flashpoint

23 °C, c.c.

IMDG EmS

F-E, S-E

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Goods may not be carried in bulk in bulk containers, containers or vehicles.

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (including last amendment Commission Regulation (EU) 2015/830)

- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

15.1.1. Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-guideline)

Not applicable.

15.2. Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16. OTHER INFORMATION

Indication of changes

-

Abbreviations and acronyms

ATE - Acute Toxicity Estimate
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
CEN - European Committee for Standardisation
C&L - Classification and Labelling
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
CAS# - Chemical Abstracts Service number
CMR - Carcinogen, Mutagen, or Reproductive Toxicant
CSA - Chemical Safety Assessment
CSR - Chemical Safety Report
DMEL - Derived Minimal Effect Level
DNEL - Derived No Effect Level
DPD - Dangerous Preparations Directive 1999/45/EC
DSD - Dangerous Substances Directive 67/548/EEC
DU - Downstream User
EC - European Community
ECHA - European Chemicals Agency
EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS)
EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway)
EEC - European Economic Community
EINECS - European Inventory of Existing Commercial Substances
ELINCS - European List of notified Chemical Substances
EN - European Standard
EQS - Environmental Quality Standard
EU - European Union
Euphrac - European Phrase Catalogue
EWC - European Waste Catalogue (replaced by LoW – see below)
GES - Generic Exposure Scenario
GHS - Globally Harmonized System

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **90.001 UniMix White**

Creation date: **17.6.2016** · Revision: **28.6.2018** · Version: **1**

IATA - International Air Transport Association
ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG - International Maritime Dangerous Goods
IMSBC - International Maritime Solid Bulk Cargoes
IT - Information Technology
IUCLID - International Uniform Chemical Information Database
IUPAC - International Union for Pure Applied Chemistry
JRC - Joint Research Centre
Kow - octanol-water partition coefficient
LC₅₀ - Lethal Concentration to 50 % of a test population
LD₅₀ - Lethal Dose to 50% of a test population (Median Lethal Dose)
LE - Legal Entity
LoW - List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)
LR - Lead Registrant
M/I - Manufacturer / Importer
MS - Member States
MSDS - Material Safety Data Sheet
OC - Operational Conditions
OECD - Organization for Economic Co-operation and Development
OEL - Occupational Exposure Limit
OJ - Official Journal
OR - Only Representative
OSHA - European Agency for Safety and Health at work
PBT - Persistent, Bioaccumulative and Toxic substance
PEC - Predicted Effect Concentration
PNEC(s) - Predicted No Effect Concentration(s)
PPE - Personal Protection Equipment
(Q)SAR - Qualitative Structure Activity Relationship
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
RIP - REACH Implementation Project
RMM - Risk Management Measure
SCBA - Self-Contained Breathing Apparatus
SDS - Safety data sheet
SIEF - Substance Information Exchange Forum
SME - Small and Medium sized Enterprises
STOT - Specific Target Organ Toxicity
(STOT) RE - Repeated Exposure
(STOT) SE - Single Exposure
SVHC - Substances of Very High Concern
UN - United Nations
vPvB - Very Persistent and Very Bioaccumulative

Key literature references and sources for data

-

SAFETY DATA SHEET according to Regulation 1907/2006



Product name: **90.001 UniMix White**

Creation date: **17.6.2016** · Revision: **28.6.2018** · Version: **1**

List of relevant H phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H228 Flammable solid.
- H261 In contact with water releases flammable gases.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer .
- H373 May cause damage to organs through prolonged or repeated exposure .
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.



- Provided correct labelling of the product
- Compliance with the local legislation
- Provided correct classification of the product
- Provided adequate transport data

© BENS Consulting | www.bens-consulting.com

The information of this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under Section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.