Product name: 90.320 Binder UniMix 2K DTM semimatt Creation date: 18.11.2006 · Revision: 3.7.2019 · Version: 1



# SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

## 1.1. Product identifier

Product name

## 90.320 Binder UniMix 2K DTM semimatt

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Industrial coatings.

Uses advised against

No information.

## 1.3. Details of the supplier of the safety data sheet

#### Manufacturer

SILCO, D.O.O.

Address: Šentrupert 5 a, 3303 Gomilsko, Slovenia

Phone: +386 3 703 3180 Fax: +386 3 703 3188

E-mail: n.cvilak@silco-automotive.com Point of contact for safety info: Nejc Cvilak

## 1.4. Emergency telephone number

**Emergency** 

112

Supplier

+386 3 703 3180

## **SECTION 2. HAZARDS IDENTIFICATION**

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Flam. Liq. 3; H226 Flammable liquid and vapour.

Asp. Tox. 1; H304 May be fatal if swallowed and enters airways.

Skin Irrit. 2; H315 Causes skin irritation.

STOT SE 3; H335 May cause respiratory irritation.

chemius.net/oAde6

Product name: 90.320 Binder UniMix 2K DTM semimatt Creation date: 18.11.2006 · Revision: 3.7.2019 · Version: 1



#### 2.2 Label elements

## 2.2.1. Labelling according to Regulation (EC) No 1272/2008 [CLP]







#### Signal word: Danger

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H335 May cause respiratory irritation.

EUH208 Contains dibutyltin dilaurate. May produce an allergic reaction.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301 + P310 + P331 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P403 + P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with national regulation.

#### 2.2.2. Contains:

solvent naphtha (petroleum), light arom. (CAS: 64742-95-6, EC: 265-199-0, Index: 649-356-00-4)

#### 2.2.3. Special provisions

Special hazards are not known or expected.

## 2.3. Other hazards

No information.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

## 3.1. Substances

For mixtures see 3.2.

Print date: 23.8.2019 Page 2 of 13

Product name: 90.320 Binder UniMix 2K DTM semimatt Creation date: 18.11.2006 · Revision: 3.7.2019 · Version: 1



#### 3.2. Mixtures

Name	CAS EC Index	%	Classification according to Regulation (EC) No 1272/2008 (CLP)	Specific Conc. Limits	REACH Registration No.
solvent naphtha (petroleum), light arom. [P]	64742-95-6 265-199-0 649-356-00-4	20-30	Asp. Tox. 1; H304 STOT SE 3; H335		-
xylene <sup>[C]</sup>	1330-20-7 215-535-7 601-022-00-9	1-10	Flam. Liq. 3; H226 Acute Tox. 4; H312 Skin Irrit. 2; H315 Acute Tox. 4; H332		-
n-butyl acetate	123-86-4 204-658-1 607-025-00-1	0-5	Flam. Liq. 3; H226 STOT SE 3; H336 EUH066		-
2-butoxyethyl acetate	112-07-2 203-933-3 607-038-00-2	0-5	Acute Tox. 4; H312 Acute Tox. 4; H332		-
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7	0-5	Flam. Liq. 3; H226		-
ethylbenzene	100-41-4 202-849-4 601-023-00-4	0,1-1	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Acute Tox. 4; H332 STOT RE 2; H373 (hearing organs)		-
dibutyltin dilaurate	77-58-7 201-039-8 -	0-0,1	Skin Corr. 1C; H314 Skin Sens. 1; H317 Eye Dam. 1; H318 Muta. 2; H341 Repr. 1B; H360FD STOT SE 1; H370 Aquatic Acute 1; H400 Aquatic Chronic 1; H410		-

#### Notes for substances:

C Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers.

In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

P The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7).

When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 (Table 3.1) or the S-phrases (2-)23-24-62 (Table 3.2) shall apply.

This note applies only to certain complex oil-derived substances in Part 3.

## **SECTION 4. FIRST AID MEASURES**

### 4.1. Description of first aid measures

## General notes

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency.

### Following inhalation

Remove patient to fresh air - move out of dangerous area. If symptoms develop and persist, seek medical attention.

Print date: 23.8.2019 Page 3 of 13

Product name: 90.320 Binder UniMix 2K DTM semimatt Creation date: 18.11.2006 · Revision: 3.7.2019 · Version: 1



#### Following skin contact

Immediately remove contaminated clothing. Wash affected skin areas thoroughly with plenty of water and soap. If symptoms develop and persist, seek medical attention.

#### Following eye contact

Immediately flush eyes with running water, keeping eyelids apart. If irritation does not stop, seek professional medical treatment!

### Following ingestion

Do not induce vomiting! Immediately consult a doctor. Show the physician the safety data sheet or label.

#### 4.2. Most important symptoms and effects, both acute and delayed

#### Inhalation

Excessive exposure to spray mist, fog, or vapours may cause respiratory irritation.

Negative effects can affect liver, kidney, and central nervous system.

Causes irritation of mucous membrane.

Coughing, sneezing, nasal discharge, labored breathing.

#### Skin contact

Itching, redness, pain.

Repeated or prolonged contact with the product may lead to removal of natural fats from the skin and non-allergic contact dermatitis

May cause sensitisation by skin contact (symptoms: itching, redness, rashes).

#### Eye contact

Contact with eyes can cause irritation (redness, tearing, pain).

#### <u>Ingestion</u>

Aspiration into the lungs causes coughing, shortness of breath and may lead to chemical pneumonia. May cause nausea/vomiting and diarrhea.

## 4.3. Indication of any immediate medical attention and special treatment needed

-

## **SECTION 5. FIREFIGHTING MEASURES**

## 5.1. Extinguishing media

## Suitable extinguishing media

Foam.

Carbon dioxide (CO<sub>2</sub>).

Water spray.

## Unsuitable extinguishing media

Full water jet.

#### 5.2. Special hazards arising from the substance or mixture

## Hazardous combustion products

In case of a fire toxic gases can be generated; do not inhale gases/smoke.

## 5.3. Advice for firefighters

### Protective actions

In case of fire or heating do not breathe fumes/vapours. Prolonged heating can cause an explosion. Cool containers at risk with water spray. If possible remove containers from endangered area.

## Special protective equipment for firefighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

Print date: 23.8.2019 Page 4 of 13

Product name: 90.320 Binder UniMix 2K DTM semimatt Creation date: 18.11.2006 · Revision: 3.7.2019 · Version: 1



#### Additional information

Contaminated firefighting water must be disposed of in accordance with the regulations; do not allow to reach the sewage system.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

#### Protective equipment

Use personal protective equipment (Section 8).

#### **Emergency procedures**

Ensure adequate ventilation. Prevent access to unprotected personnel. Do not breathe vapour or mist. Avoid contact with skin and eyes. Do not use open fire and keep away all sources of ignition.

#### 6.1.2. For emergency responders

Use personal protective equipment.

#### 6.2. Environmental precautions

Do not allow product to reach water/drains/sewage systems or permeable soil. If accidental large entry into water or ground occurs, inform responsible authorities.

### 6.3. Methods and material for containment and cleaning up

#### 6.3.1. For containment

Stem the spill if this does not pose risks.

#### 6.3.2. For cleaning up

Absorb product (with inert material), collect it in special container and dispose it to a licensed hazardous-waste disposal contractor. Prevent product to reach water bodies or sewage systems.

#### 6.3.3. Other information

\_

#### 6.4. Reference to other sections

See also Sections 8 and 13.

## **SECTION 7. HANDLING AND STORAGE**

## 7.1. Precautions for safe handling

## 7.1.1. Protective measures

#### Measures to prevent fire

Ensure adequate ventilation. Keep away from sources of ignition - no smoking. Take precautionary measures against static discharges. Use spark-proof tools.

#### Measures to prevent aerosol and dust generation

\_

#### Measures to protect the environment

\_

## 7.1.2. Advice on general occupational hygiene

Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Do not breathe vapours/mist. Avoid contact with skin, eyes and clothes. Wear suitable protective equipment; see Section 8. Refer to instructions on label and regulations for safety and health at work. Remove contaminated clothes and wash them before reuse.

Print date: 23.8.2019 Page 5 of 13

Product name: 90.320 Binder UniMix 2K DTM semimatt Creation date: 18.11.2006 · Revision: 3.7.2019 · Version: 1



#### 7.2. Conditions for safe storage, including any incompatibilities

## 7.2.1. Technical measures and storage conditions

Keep in cool and well ventilated area. Protect from open fire, heat and direct sunlight. Keep unauthorized personnel away. Keep away from oxidising substances. Store away from strong acids. Store away from strong bases. Do not smoke! Store between: 0°C to +30°C

## 7.2.2. Packaging materials

-

## 7.2.3. Requirements for storage rooms and vessels

Close opened containers after use. Put the containers upright to prevent from leaking.

## 7.2.4. Storage class

-

#### 7.2.5. Further information on storage conditions

-

#### 7.3. Specific end use(s)

Recommendations

-

Industrial sector specific solutions

-

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1. Control parameters

#### 8.1.1. Occupational exposure limit values

Name (CAS)			Short-term exposure limit		Remarks	Biological Tolerance Values
	ml/m <sup>3</sup> (ppm)	mg/m <sup>3</sup>	ml/m <sup>3</sup> (ppm)	mg/m <sup>3</sup>		
2-Butoxyethyl acetate (112-07-2)	20	133	50	332	Sk	
Butyl acetate (123-86-4)	150	724	200	966		
Ethylbenzene (100-41-4)	100	441	125	552	Sk	
1-Methoxypropyl acetate (108-65-6)	50	274	100	548	Sk	
Xylene, o-,m-,p- or mixed isomers (1330-20-7)	50	220	100	441	Sk, BMGV	650 mmol methyl hippuric acid/mol creatinine in urine - Post shift

#### 8.1.2. Information on monitoring procedures

BS EN 14042:2003 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 482:2012+A1:2015 Workplace exposure. General requirements for the performance of procedures for the measurement of chemical agents. BS EN 689:2018 Workplace exposure. Measurement of exposure by inhalation to chemical agents. Strategy for testing compliance with occupational exposure limit values.

## 8.1.3. DNEL/DMEL values

No information.

## 8.1.4. PNEC values

No information.

Print date: 23.8.2019 Page 6 of 13

Product name: 90.320 Binder UniMix 2K DTM semimatt Creation date: 18.11.2006 · Revision: 3.7.2019 · Version: 1



#### 8.2. Exposure controls

## 8.2.1. Appropriate engineering control

#### Substance/mixture related measures to prevent exposure during identified uses

Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Do not breathe vapours/aerosols. Avoid contact with eyes and skin.

#### Organisational measures to prevent exposure

Remove all contaminated clothes immediately and wash them before reuse.

#### Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration.

#### 8.2.2. Personal protective equipment

### Eye and face protection

Safety googles (EN 166).

#### Hand protection

Protective gloves (EN 374). Observe the manufacturer's instructions regarding the use, storage, maintenance and replacement of gloves. In case of damage or at the first signs of wear and tear, change the gloves immediately. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

#### Skin protection

Cotton protective clothing and shoes that cover the entire foot (EN ISO 20345).

#### Respiratory protection

In case of insufficient ventilation wear suitable respiratory protection. Wear suitable protective breathing mask (EN 136) with filter A2-P2 (EN 14387). In case of intensive or longer exposure use self-contained breathing apparatus (EN 137).

#### Thermal hazards

\_

## 8.2.3. Environmental exposure controls

-

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

#### 9.1. Information on basic physical and chemical properties

-	Physical state:	liquid
-	Colour:	according to specification
-	Odour:	solvent like

Print date: 23.8.2019 Page 7 of 13

Product name: 90.320 Binder UniMix 2K DTM semimatt Creation date: 18.11.2006 · Revision: 3.7.2019 · Version: 1



## Important health, safety and environmental information

рН	No information.
Melting point/freezing point	No information.
Initial boiling point/boiling range	No information.
Flash point	25 °C
Evaporation rate	No information.
Flammability (solid, gas)	No information.
Explosion limits (vol%)	No information.
Vapour pressure	No information.
Vapour density	No information.
Density	No information.
Solubility	No information.
Partition coefficient	No information.
Auto-ignition temperature	No information.
Decomposition temperature	No information.
Viscosity	No information.
Explosive properties	No information.
Oxidising properties	No information.
	Melting point/freezing point Initial boiling point/boiling range Flash point Evaporation rate Flammability (solid, gas) Explosion limits (vol%) Vapour pressure Vapour density Density Solubility Partition coefficient Auto-ignition temperature Decomposition temperature Viscosity Explosive properties

#### 9.2. Other information

- Remarks:

## **SECTION 10. STABILITY AND REACTIVITY**

## 10.1. Reactivity

\_

## 10.2. Chemical stability

Product is stable under normal conditions of use, recommended handling and storage conditions.

## 10.3. Possibility of hazardous reactions

\_

#### 10.4. Conditions to avoid

Protect from heat, direct sunlight, open fire, sparks.

## 10.5. Incompatible materials

Oxidants.

## 10.6. Hazardous decomposition products

Under normal use conditions no hazardous decomposition products are expected. In case of fire/explosion vapours/gases that pose a health hazard are released.

## **SECTION 11. TOXICOLOGICAL INFORMATION**

## 11.1. Information on toxicological effects

## (a) Acute toxicity

No information.

Print date: 23.8.2019 Page 8 of 13

Product name: 90.320 Binder UniMix 2K DTM semimatt Creation date: 18.11.2006 · Revision: 3.7.2019 · Version: 1



## (b) Skin corrosion/irritation

Additional information: Causes skin irritation.

(c) Serious eye damage/irritation

No information.

(d) Respiratory or skin sensitisation

Additional information: May cause an allergic skin reaction.

(e) (Germ cell) mutagenicity

No information.

(f) Carcinogenicity

No information.

(g) Reproductive toxicity

No information.

Summary of evaluation of the CMR properties

No information.

(h) STOT-single exposure

Additional information: STOT - single exposure: May cause respiratory irritation.

(i) STOT-repeated exposure

No information.

(i) Aspiration hazard

Additional information: May be fatal if swallowed and enters airways.

## **SECTION 12. ECOLOGICAL INFORMATION**

#### 12.1. Toxicity

12.1.1. Acute (short-term) toxicity

No information.

12.1.2. Chronic (long-term) toxicity

No information.

## 12.2. Persistence and degradability

12.2.1. Abiotic degradation, physical- and photo-chemical elimination

No information.

12.2.2. Biodegradation

No information.

## 12.3. Bioaccumulative potential

12.3.1. Partition coefficient

No information.

12.3.2. Bioconcentration factor (BCF)

No information.

Print date: 23.8.2019 Page 9 of 13

Product name: 90.320 Binder UniMix 2K DTM semimatt Creation date: 18.11.2006 · Revision: 3.7.2019 · Version: 1



#### 12.4. Mobility in soil

## 12.4.1. Known or predicted distribution to environmental compartments

No information.

#### 12.4.2. Surface tension

No information.

#### 12.4.3. Adsorption/Desorption

No information.

#### 12.5. Results of PBT and vPvB assessment

No evaluation.

#### 12.6. Other adverse effects

No information.

#### 12.7. Additional information

## For product

Do not allow to reach ground water, water courses or sewage system.

## **SECTION 13. DISPOSAL CONSIDERATIONS**

#### 13.1. Waste treatment methods

#### 13.1.1. Product / Packaging disposal

#### Waste chemical

Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste. Do not allow product to reach drains/sewage systems.

#### **Packaging**

Deliver completely emptied containers to approved waste disposal authorities. Uncleaned containers are classified as hazardous waste - they should be handled in the same manner as the contents.

## 13.1.2. Waste treatment-relevant information

-

## 13.1.3. Sewage disposal-relevant information

-

## 13.1.4. Other disposal recommendations

-

## **SECTION 14. TRANSPORT INFORMATION**

## 14.1. UN number

UN 1263

#### 14.2. UN proper shipping name

PAINT

#### 14.3. Transport hazard class(es)

3

## 14.4. Packing group

Ш



Product name: 90.320 Binder UniMix 2K DTM semimatt Creation date: 18.11.2006 · Revision: 3.7.2019 · Version: 1



#### 14.5. Environmental hazards

NO.

#### 14.6. Special precautions for user

Limited quantities

5 I

**Tunnel restriction code** 

(D/E)

**IMDG** flashpoint

25 °C, c.c.

**IMDG EmS** 

F-E, S-E

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Goods may not be carried in bulk in bulk containers, containers or vehicles.

## **SECTION 15. REGULATORY INFORMATION**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (including last amendment Commission Regulation (EU) 2015/830)
- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

# 15.1.1. Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-guideline)

Not applicable.

#### 15.1.2. Special instructions

Observe the regulations on employment and protection against dangerous substances for young people, pregnant women and nursing mothers.

## 15.2. Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## **SECTION 16. OTHER INFORMATION**

### Indication of changes

\_

#### Abbreviations and acronyms

ATE - Acute Toxicity Estimate

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

CEN - European Committee for Standardisation

C&L - Classification and Labelling

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

CAS# - Chemical Abstracts Service number

CMR - Carcinogen, Mutagen, or Reproductive Toxicant

CSA - Chemical Safety Assessment

CSR - Chemical Safety Report

DMEL - Derived Minimal Effect Level

DNEL - Derived No Effect Level

DPD - Dangerous Preparations Directive 1999/45/EC

DSD - Dangerous Substances Directive 67/548/EEC

Print date: 23.8.2019 Page 11 of 13

Product name: 90.320 Binder UniMix 2K DTM semimatt Creation date: 18.11.2006 · Revision: 3.7.2019 · Version: 1



DU - Downstream User

EC - European Community

ECHA - European Chemicals Agency

EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS) EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway)

EEC - European Economic Community

EINECS - European Inventory of Existing Commercial Substances

ELINCS - European List of notified Chemical Substances

EN - European Standard

EQS - Environmental Quality Standard

EU - European Union

Euphrac - European Phrase Catalogue

EWC - European Waste Catalogue (replaced by LoW - see below)

GES - Generic Exposure Scenario

GHS - Globally Harmonized System

IATA - International Air Transport Association

ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG - International Maritime Dangerous Goods IMSBC - International Maritime Solid Bulk Cargoes

IT - Information Technology

IUCLID - International Uniform Chemical Information Database

IUPAC - International Union for Pure Applied Chemistry

JRC - Joint Research Centre

Kow - octanol-water partition coefficient

LC<sub>50</sub> - Lethal Concentration to 50 % of a test population

LD<sub>50</sub> - Lethal Dose to 50% of a test population (Median Lethal Dose)

LE - Legal Entity

LoW - List of Wastes (see http://ec.europa.eu/environment/waste/framework/list.htm)

LR - Lead Registrant

M/I - Manufacturer / Importer

MS - Member States

MSDS - Material Safety Data Sheet

OC - Operational Conditions

OECD - Organization for Economic Co-operation and Development

OEL - Occupational Exposure Limit

OJ - Official Journal

OR - Only Representative

OSHA - European Agency for Safety and Health at work

PBT - Persistent, Bioaccumulative and Toxic substance

PEC - Predicted Effect Concentration

PNEC(s) - Predicted No Effect Concentration(s)

PPE - Personal Protection Equipment

(Q)SAR - Qualitative Structure Activity Relationship

REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006

RID - Regulations concerning the International Carriage of Dangerous Goods by Rail

RIP - REACH Implementation Project

RMM - Risk Management Measure

SCBA - Self-Contained Breathing Apparatus

SDS - Safety data sheet

SIEF - Substance Information Exchange Forum

SME - Small and Medium sized Enterprises

STOT - Specific Target Organ Toxicity

(STOT) RE - Repeated Exposure

(STOT) SE - Single Exposure

SVHC - Substances of Very High Concern

UN - United Nations

vPvB - Very Persistent and Very Bioaccumulative

Key literature references and sources for data

-

Print date: 23.8.2019 Page 12 of 13

Product name: 90.320 Binder UniMix 2K DTM semimatt Creation date: 18.11.2006 · Revision: 3.7.2019 · Version: 1



## List of relevant H phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H341 Suspected of causing genetic defects .

H360FD May damage fertility. May damage the unborn child.

H370 Causes damage to organs.

 ${\sf H373}\ {\sf May}$  cause damage to organs through prolonged or repeated exposure .

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.



Provided correct labelling of the product

☑ Compliance with the local legislation

☑ Provided correct classification of the product

© BENS Consulting | www.bens-consulting.com

The information of this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under Section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.

Print date: 23.8.2019 Page 13 of 13