9004 Clear Finish

silco[®]

1K glossy acrylic clear coat

High quality, 1K clear coat in aerosol for spot repair in automotive painting.

- / Quick drying time
- / Smooth flow
- / Economical in use



9004 Clear Finish

1K glossy acrylic clear coat

Drying time

Dust dry (20°C/68°F)	10—15 min
Touch dry (20°C/68°F)	60-90 min
Polish dry (20°C/68°F	6 h
Fully dry (20°C/68°F)	24 h
Flash-off 20°C/68°F	3–5 min

 $^{{}^* \}text{Indicative times subject to hardener and thinner type/application/environment}...$

How to use?

Shake can thoroughly until the mixing balls move freely. Surfaces to be treated must be thoroughly dry. Do not apply this product on the surface coated with synthetic enamels. After spraying, turn the can upside down and spray until the valve is clean. It is strongly recommended that ready to use product is applied at above $15^{\circ}\text{C}/59^{\circ}\text{F}.$

For further and updated information please refer to the TDS published on www.silco.si.

Packaging

9004 Clear Finish

1K glossy acrylic clear coat

Prod. Nr.	Content
9004-0,5	500 ml

Product info

High quality, glossy clear coat in aerosol for spot repair in automotive painting. Suitable also for waterborne base coats. Special formulation enables high durability and anti-yellowing protection.

