# **Technical Data Sheet**



# 9005 Black Finish Spray, Acrylic Black Matt Paint

Ver.: 2021-1

### **Description**

High quality, high performance acrylic black matt paint in aerosol for general use.

## **Features & Benefits**

- Good adhesion on most parts
- High covering power
- Quick drying
- Excellent finish
- Economical in use

### **Substrate preparation**

Surfaces to be treated must be clean, dry and grease-free.

Suitable substrates:

- metallic (aluminium/zinc should be pre-treated with suitable primer)
- wood
- glassware
- plastics (except of PS, PE, PP, EPDM)

Important: do not apply on surface coated with synthetic enamels.

# **Application data**



#### Mixing ratio

The product is ready to use!

# **Application**

Shake can thoroughly until the mixing balls move freely.



Number of coats 2-3

Spraying distance 15 - 20 cmFlash-off 3 - 5 min

Dry film thickness 30 – 40 microns

After spraying, turn the can upside down and spray until the valve is clean.

It is strongly recommended that ready for use product is applied at a temperature above 15 °C/59 °F.

SILCO d.o.o., Šentrupert 5a, 3303 Gomilsko, Slovenija

Tel.: +386 (0)3 703 31 80 / Fax.: +386 (0)3 703 31 88

E-mail: info@silco-automotive.com / www.silco-automotive.com

Page 1

# **Technical Data Sheet**



# 9005 Black Finish Spray, Acrylic Black Matt Paint

Ver.: 2021-1





Dust dry (20 °C/68 °F) 5 - 10 minTouch dry (20 °C/68 °F) 20 - 30 min

Fully dry (20 °C/68 °F) 24 h

Prod. Nr.	Description	Volume	Packaging Box
9005	Black	500 ml	12

### VOC

VOC 2004/42/IIB(e) (840) 820

#### **Shelf life**

Min. 48 months from the production date under normal storage conditions and unopened can.

### **Additional Information**

FOR PROFESSIONAL USE ONLY!

Always read the instructions.

IMPORTANT: This product contains hazardous substances at work so it is necessary to always use/wear appropriate protective equipment. For further instructions, check the label on the product and safety data sheet. A person who uses the product for any purpose other than recommended in this technical data sheet, acts at his own risk. It is the user's responsibility to take all necessary steps to fulfil the local legislation.

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public.

Information and methods described are based on the best information and practices known to us and serve merely as guidelines for optimal use, without liability to performance, results or fitness for any intended use. We do not accept any responsibility for the behaviour of the product or damage arising from the use of the product. Before using the product, the user must check if this is the latest version.

All products mentioned in this data sheet are trademarks owned by Silco.

SILCO d.o.o., Šentrupert 5a, 3303 Gomilsko, Slovenija

Tel.: +386 (0)3 703 31 80 / Fax.: +386 (0)3 703 31 88

E-mail: info@silco-automotive.com / www.silco-automotive.com