Product name: 9008 B-Paint Spray

Creation date: 3.9.2019 · Revision: 22.12.2020 · Version: 1



# SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product name

### 9008 B-Paint Spray

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Paint.

Uses advised against

No information.

### 1.3. Details of the supplier of the safety data sheet

### **Manufacturer**

SILCO, D.O.O.

Address: Šentrupert 5 a, 3303 Gomilsko, Slovenia

Phone: +386 3 703 3180 Fax: +386 3 703 3188

E-mail: n.cvilak@silco-automotive.com Point of contact for safety info: Nejc Cvilak

### 1.4. Emergency telephone number

**Emergency** 

112

<u>Supplier</u>

+386 3 703 3180

### **SECTION 2. HAZARDS IDENTIFICATION**

### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Aerosol 1; H222 Extremely flammable aerosol.

Aerosol 1; H229 Pressurised container: May burst if heated.

Skin Irrit. 2; H315 Causes skin irritation. Eye Irrit. 2; H319 Causes serious eye irritation.

STOT SE 3; H336 May cause drowsiness or dizziness.

chemius.net/QNZ23

Product name: 9008 B-Paint Spray

Creation date: 3.9.2019 · Revision: 22.12.2020 · Version: 1



#### 2.2 Label elements

### 2.2.1. Labelling according to Regulation (EC) No 1272/2008 [CLP]





#### Signal word: Danger

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

P251 Do not pierce or burn, even after use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P410 + P412 Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122°F.

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P261 Avoid breathing vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international regulation.

### 2.2.2. Contains:

acetone (CAS: 67-64-1, EC: 200-662-2, Index: 606-001-00-8) n-butyl acetate (CAS: 123-86-4, EC: 204-658-1, Index: 607-025-00-1) butan-1-ol (CAS: 71-36-3, EC: 200-751-6, Index: 603-004-00-6)

### 2.2.3. Special provisions

Vapours and air can at inadequate ventilation form an explosive mixture.

### 2.3. Other hazards

The substances in the mixture are not classified as persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB).

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

### 3.1. Substances

For mixtures see 3.2.

Print date: 4.1.2021 Page 2 of 13

Product name: 9008 B-Paint Spray

Creation date: 3.9.2019 · Revision: 22.12.2020 · Version: 1



### 3.2. Mixtures

Name	CAS EC Index	%	Classification according to Regulation (EC) No 1272/2008 (CLP)	Specific Conc. Limits	REACH Registration No.
dimethyl ether	115-10-6 204-065-8 603-019-00-8	40-50	Flam. Gas 1A; H220 Press. Gas; H280		-
acetone	67-64-1 200-662-2 606-001-00-8	20-25	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336		01-2119471330-49
nitrocellulose	9004-70-0	15	Expl. 1.1; H201		-
n-butyl acetate	123-86-4 204-658-1 607-025-00-1	5-10	Flam. Liq. 3; H226 STOT SE 3; H336		01-2119485493-29
xylene <sup>[C]</sup>	1330-20-7 215-535-7 601-022-00-9	5-10	Flam. Liq. 3; H226 Acute Tox. 4; H312 Skin Irrit. 2; H315 Acute Tox. 4; H332		01-2119488216-32
butan-1-ol	71-36-3 200-751-6 603-004-00-6	1-2,5	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335 STOT SE 3; H336		-
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7	1-<2,5	Flam. Liq. 3; H226		01-2119475791-29
polypropylene	9003-07-0	1-2,5	not classified		-

### Notes for substances:

C Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers.

In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

### **SECTION 4. FIRST AID MEASURES**

### 4.1. Description of first aid measures

#### General notes

When in doubt or if feeling unwell seek medical assistance. Show the safety data sheet and label to the physician. Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency.

### Following inhalation

Remove patient to fresh air - move out of dangerous area. If symptoms develop and persist, seek medical attention.

### Following skin contact

Take off all contaminated clothing. Wash affected skin areas thoroughly with plenty of water and soap. If symptoms develop and persist, seek medical attention.

### Following eye contact

If the patient is wearing contact lenses, remove them immediately. Immediately flush eyes with running water, keeping eyelids apart. If irritation persists, seek professional medical attention.

Print date: 4.1.2021 Page 3 of 13

Product name: 9008 B-Paint Spray

Creation date: 3.9.2019 · Revision: 22.12.2020 · Version: 1



### Following ingestion

Do not induce vomiting! In case of doubt or if feeling unwell seek medical help. Show the physician the safety data sheet or label. Never give anything by mouth to an unconscious person.

#### 4.2. Most important symptoms and effects, both acute and delayed

#### Inhalation

Vapours may cause drowsiness and dizziness.

Symptoms include: headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, unconsciousness.

#### Skin contact

Itching, redness, pain.

#### Eye contact

Redness, tearing, pain.

### Ingestion

Ingestion is unlikely because it is an aerosol.

Accidental ingestion:

May cause nausea/vomiting and diarrhea.

May cause abdominal discomfort.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5. FIREFIGHTING MEASURES

### 5.1. Extinguishing media

### Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Carbon dioxide. Dry chemical powder. Water spray. Alcohol resistant foam.

### Unsuitable extinguishing media

Full water jet.

### 5.2. Special hazards arising from the substance or mixture

### Hazardous combustion products

In case of a fire toxic gases can be generated; do not inhale gases/smoke.

#### 5.3. Advice for firefighters

### Protective actions

Cool containers at risk with water spray. If possible remove containers from endangered area. In case of fire aerosols can explode and be propelled to considerable distances in different directions. Prolonged heating can cause an explosion. In case of fire or heating do not breathe fumes/vapours.

### Special protective equipment for firefighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

#### Additional information

Contaminated firefighting water and fire residues must be disposed of in accordance with the local regulations.

### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Print date: 4.1.2021 Page 4 of 13

Product name: 9008 B-Paint Spray

Creation date: 3.9.2019 · Revision: 22.12.2020 · Version: 1



### 6.1. Personal precautions, protective equipment and emergency procedures

### 6.1.1. For non-emergency personnel

### Protective equipment

Use personal protective equipment (Section 8).

#### **Emergency procedures**

Ensure adequate ventilation. Keep away from sources of ignition and/or heat; No smoking! Prevent access to unprotected personnel. Do not breathe vapour or mist. Avoid contact with skin, eyes and clothing. No action shall be taken involving any personal risk or without suitable training. Prevent access to unauthorised personnel. Do not use open fire and keep away all sources of ignition.

### 6.1.2. For emergency responders

Use personal protective equipment.

#### 6.2. Environmental precautions

Do not allow product to reach water/drains/sewage systems or permeable soil. If accidental large entry into water or ground occurs, inform responsible authorities.

#### 6.3. Methods and material for containment and cleaning up

### 6.3.1. For containment

\_

### 6.3.2. For cleaning up

Release of liquid because of damaged aerosol can (release of large quantities): Absorb product (with inert material), collect it in special container and dispose it to a licensed hazardous-waste disposal contractor. Collect the spray cans and hand them over to an authorized waste disposal contractor. Dispose in accordance with applicable regulations (see Section 13). Ventilate the premises. Use spark-proof tools.

### 6.3.3. Other information

-

### 6.4. Reference to other sections

See also Sections 8 and 13.

### **SECTION 7. HANDLING AND STORAGE**

### 7.1. Precautions for safe handling

### 7.1.1. Protective measures

#### Measures to prevent fire

Ensure adequate ventilation. Take precautionary measures against static discharges. Keep away from sources of ignition - no smoking. Use spark-proof tools. Do not spray on a naked flame or incandescent material. Pressurized container; protect from sunlight and do not expose to tempratures exceeding 50°C. Do not pierce or burn, even after use.

### Measures to prevent aerosol and dust generation

Use general or local exhaust ventilation to prevent inhaling vapours and aerosols.

#### Measures to protect the environment

Do not discharge into drains, surface water and soil. After use immediately close container tightly.

### 7.1.2. Advice on general occupational hygiene

Do not eat, drink or smoke while working. Do not breathe vapours/mist. Use good personal hygiene practices – wash hands at breaks and when done working with material.

### 7.2. Conditions for safe storage, including any incompatibilities

### 7.2.1. Technical measures and storage conditions

Store in accordance with local regulations. Follow safe storage practices for packed compressed gas as described by the Compressed Gas Association or the relevant agency in the country where the product is used. Protect from open fire, heat and direct sunlight. Keep away from food, drink and animal feeding stuffs. Keep in cool and well ventilated area.

Print date: 4.1.2021 Page 5 of 13

Product name: 9008 B-Paint Spray

Creation date: 3.9.2019 · Revision: 22.12.2020 · Version: 1



### 7.2.2. Packaging materials

Store only in original container.

### 7.2.3. Requirements for storage rooms and vessels

Close opened containers after use. Put the containers upright to prevent from leaking. Do not store in unlabelled containers.

### 7.2.4. Storage class

-

### 7.2.5. Further information on storage conditions

-

### 7.3. Specific end use(s)

Recommendations

-

Industrial sector specific solutions

-

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

### 8.1.1. Occupational exposure limit values

Name (CAS)			Short-term exposure limit		Remarks	Biological Tolerance Values
	ml/m <sup>3</sup> (ppm)	mg/m <sup>3</sup>	ml/m <sup>3</sup> (ppm)	mg/m <sup>3</sup>		
Dimethyl ether (115-10-6)	400	766	500	958		
Butyl acetate (123-86-4)	150	724	200	966		
Butan-1-ol (71-36-3)			50	154	Sk	
Acetone (67-64-1)	500	1210	1500	3620		
1-Methoxypropyl acetate (108-65-6)	50	274	100	548	Sk	
Xylene, o-,m-,p- or mixed isomers (1330-20-7)	50	220	100	441	Sk, BMGV	650 mmol methyl hippuric acid/mol creatinine in urine - Post shift

### 8.1.2. Information on monitoring procedures

BS EN 14042:2003 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 482:2012+A1:2015 Workplace exposure. General requirements for the performance of procedures for the measurement of chemical agents. BS EN 689:2018 Workplace exposure. Measurement of exposure by inhalation to chemical agents. Strategy for testing compliance with occupational exposure limit values.

### 8.1.3. DNEL/DMEL values

No information.

### 8.1.4. PNEC values

No information.

### 8.2. Exposure controls

### 8.2.1. Appropriate engineering control

### Substance/mixture related measures to prevent exposure during identified uses

Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Avoid contact with skin, eyes and clothes. Do not breathe vapours/aerosols. Handle in accordance with good industrial hygiene and safety practice.

Print date: 4.1.2021 Page 6 of 13

Product name: 9008 B-Paint Spray

Creation date: 3.9.2019 · Revision: 22.12.2020 · Version: 1



### Organisational measures to prevent exposure

Remove all contaminated clothes immediately and wash them before reuse.

#### Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration. Keep away from food, drink and animal feeding stuffs.

### 8.2.2. Personal protective equipment

### Eye and face protection

Tight fitting protective goggles (EN 166).

### Hand protection

Protective gloves (EN 374). To choose the appropriate protective gloves, consult the protective glove manufacturer. The penetration time is determined by the protective glove manufacturer and must be observed. Observe the manufacturer's instructions regarding the use, storage, maintenance and replacement of gloves. In case of damage or at the first signs of wear and tear, change the gloves immediately. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

#### Skin protection

Cotton protective clothing and shoes that cover the entire foot (EN ISO 20345).

#### Respiratory protection

In case of insufficient ventilation wear suitable respiratory protection. Wear suitable respiratory protection mask (EN 136:1998) with an AX-P2 combination filter (EN 14387:2004 +A1:2008).

#### Thermal hazards

-

### 8.2.3. Environmental exposure controls

### Technical measures to prevent exposure

Do not allow product to reach drains, sewage systems or ground water.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

-	Physical state:	liquid; aerosol
-	Colour:	according to specification
-	Odour:	characteristic

Print date: 4.1.2021 Page 7 of 13

Product name: 9008 B-Paint Spray

Creation date: 3.9.2019 · Revision: 22.12.2020 · Version: 1



### Important health, safety and environmental information

-	рН	No information.
-	Melting point/freezing point	No information.
-	Initial boiling point/boiling range	< 0 °C
-	Flash point	< 0 °C
-	Evaporation rate	No information.
-	Flammability (solid, gas)	No information.
-	Explosion limits (vol%)	2,6 – 13 vol % (acetone) 3,4 – 27 vol % (dimethylether)
-	Vapour pressure	No information.
-	Vapour density	No information.
-	Density	Relative density: < 1
-	Solubility	Water: Insoluble
-	Partition coefficient	No information.
-	Auto-ignition temperature	ca. 350 °C
-	Decomposition temperature	No information.
-	Viscosity	No information.
-	Explosive properties	Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.
-	Oxidising properties	No information.

### 9.2. Other information

Domarko	
 Remarks:	
 Homans.	

### **SECTION 10. STABILITY AND REACTIVITY**

### 10.1. Reactivity

Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

Product is stable under normal conditions of use, recommended handling and storage conditions.

### 10.3. Possibility of hazardous reactions

The product is stable under recommended storage and handling conditions.

### 10.4. Conditions to avoid

Protect from heat, direct sunlight, open fire, sparks. Do not store above 50°C.

### 10.5. Incompatible materials

Oxidants.

### 10.6. Hazardous decomposition products

Under normal use conditions no hazardous decomposition products are expected. In case of fire/explosion vapours/gases that pose a health hazard are released.

Print date: 4.1.2021 Page 8 of 13

Product name: 9008 B-Paint Spray

Creation date: 3.9.2019 · Revision: 22.12.2020 · Version: 1



### **SECTION 11. TOXICOLOGICAL INFORMATION**

### 11.1. Information on toxicological effects

(a) Acute toxicity

Additional information: The product is not classified for acute toxicity.

(b) Skin corrosion/irritation

Additional information: Causes skin irritation.

(c) Serious eye damage/irritation

Additional information: Causes serious eye irritation.

(d) Respiratory or skin sensitisation

Additional information: The product is not classified as sensitising.

(e) (Germ cell) mutagenicity

No information.

(f) Carcinogenicity

No information.

(g) Reproductive toxicity

No information.

Summary of evaluation of the CMR properties

The product is not classified as carcinogenic, mutagenic or toxic for reproduction.

(h) STOT-single exposure

Additional information: May cause drowsiness or dizziness.

(i) STOT-repeated exposure

Additional information: STOT RE (repeated exposure): Not classified.

(j) Aspiration hazard

Additional information: Aspiration hazard: Not classified.

### **SECTION 12. ECOLOGICAL INFORMATION**

### 12.1. Toxicity

12.1.1. Acute (short-term) toxicity

No information.

12.1.2. Chronic (long-term) toxicity

No information.

### 12.2. Persistence and degradability

12.2.1. Abiotic degradation, physical- and photo-chemical elimination

No information.

12.2.2. Biodegradation

No information.

Print date: 4.1.2021 Page 9 of 13

Product name: 9008 B-Paint Spray

Creation date: 3.9.2019 · Revision: 22.12.2020 · Version: 1



### 12.3. Bioaccumulative potential

12.3.1. Partition coefficient

No information.

12.3.2. Bioconcentration factor (BCF)

No information.

### 12.4. Mobility in soil

12.4.1. Known or predicted distribution to environmental compartments

No information.

12.4.2. Surface tension

No information.

12.4.3. Adsorption/Desorption

No information.

#### 12.5. Results of PBT and vPvB assessment

No evaluation.

#### 12.6. Other adverse effects

No information.

### 12.7. Additional information

#### For product

Product is not classified as dangerous for environment.

Do not allow to reach ground water, water courses or sewage system.

Water hazard class 2 (self-assessment): hazardous for water.

### **SECTION 13. DISPOSAL CONSIDERATIONS**

### 13.1. Waste treatment methods

13.1.1. Product / Packaging disposal

#### Waste chemical

Dispose of in accordance with applicable waste disposal regulation. Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste. Do not allow product to reach drains/sewage systems.

### **Packaging**

Dispose of in accordance with applicable waste disposal regulation. Deliver completely emptied containers to approved waste disposal authorities. Uncleaned containers should not be perforated, cut or welded. Empty containers represent a fire hazard as they may contain flammable product residues and vapour.

### Waste codes / waste designations according to LoW

15 01 10\* - packaging containing residues of or contaminated by dangerous substances

13.1.2. Waste treatment-relevant information

13.1.3. Sewage disposal-relevant information

13.1.4. Other disposal recommendations

### **SECTION 14. TRANSPORT INFORMATION**

Print date: 4.1.2021 Page 10 of 13

Product name: 9008 B-Paint Spray

Creation date: 3.9.2019 · Revision: 22.12.2020 · Version: 1



#### 14.1. UN number

UN 1950

### 14.2. UN proper shipping name

**AEROSOLS** 

#### 14.3. Transport hazard class(es)

2

### 14.4. Packing group

Not applicable.

#### 14.5. Environmental hazards

NO.

### 14.6. Special precautions for user

Limited quantities

1 I

**Tunnel restriction code** 

(D)

**IMDG** flashpoint

0 °C, c.c.

**IMDG EmS** 

F-D, S-U

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Goods may not be carried in bulk in bulk containers, containers or vehicles.

### **SECTION 15. REGULATORY INFORMATION**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (including last amendment Commission Regulation (EU) 2015/830)
- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

# 15.1.1. Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-guideline)

Not applicable.

### 15.1.2. Special instructions

Seveso III, P3a: flammable aerosols.

Water hazard class 2 (self-assessment): hazardous for water.

### 15.2. Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

### SECTION 16. OTHER INFORMATION

Indication of changes

Abbreviations and acronyms

ATE - Acute Toxicity Estimate

Print date: 4.1.2021 Page 11 of 13



Product name: 9008 B-Paint Spray

Creation date: 3.9.2019 · Revision: 22.12.2020 · Version: 1



ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

CEN - European Committee for Standardisation

C&L - Classification and Labelling

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

CAS# - Chemical Abstracts Service number

CMR - Carcinogen, Mutagen, or Reproductive Toxicant

CSA - Chemical Safety Assessment

CSR - Chemical Safety Report

DMEL - Derived Minimal Effect Level

DNEL - Derived No Effect Level

DPD - Dangerous Preparations Directive 1999/45/EC

DSD - Dangerous Substances Directive 67/548/EEC

DU - Downstream User

EC - European Community

ECHA - European Chemicals Agency

EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS)

EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway)

EEC - European Economic Community

EINECS - European Inventory of Existing Commercial Substances

ELINCS - European List of notified Chemical Substances

EN - European Standard

EQS - Environmental Quality Standard

EU - European Union

Euphrac - European Phrase Catalogue

EWC - European Waste Catalogue (replaced by LoW - see below)

GES - Generic Exposure Scenario

GHS - Globally Harmonized System

IATA - International Air Transport Association

ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG - International Maritime Dangerous Goods

IMSBC - International Maritime Solid Bulk Cargoes

IT - Information Technology

IUCLID - International Uniform Chemical Information Database

IUPAC - International Union for Pure Applied Chemistry

JRC - Joint Research Centre

Kow - octanol-water partition coefficient

LC<sub>50</sub> - Lethal Concentration to 50 % of a test population

LD<sub>50</sub> - Lethal Dose to 50% of a test population (Median Lethal Dose)

LE - Legal Entity

LoW - List of Wastes (see http://ec.europa.eu/environment/waste/framework/list.htm)

LR - Lead Registrant

M/I - Manufacturer / Importer

MS - Member States

MSDS - Material Safety Data Sheet

OC - Operational Conditions

OECD - Organization for Economic Co-operation and Development

OEL - Occupational Exposure Limit

OJ - Official Journal

OR - Only Representative

OSHA - European Agency for Safety and Health at work

PBT - Persistent, Bioaccumulative and Toxic substance

PEC - Predicted Effect Concentration

PNEC(s) - Predicted No Effect Concentration(s)

PPE - Personal Protection Equipment

(Q)SAR - Qualitative Structure Activity Relationship

REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006

RID - Regulations concerning the International Carriage of Dangerous Goods by Rail

RIP - REACH Implementation Project

RMM - Risk Management Measure

SCBA - Self-Contained Breathing Apparatus

SDS - Safety data sheet

SIEF - Substance Information Exchange Forum

Print date: 4.1.2021 Page 12 of 13

Product name: 9008 B-Paint Spray

Creation date: 3.9.2019 · Revision: 22.12.2020 · Version: 1



SME - Small and Medium sized Enterprises STOT - Specific Target Organ Toxicity (STOT) RE - Repeated Exposure (STOT) SE - Single Exposure

SVHC - Substances of Very High Concern

**UN - United Nations** 

vPvB - Very Persistent and Very Bioaccumulative

### Key literature references and sources for data

-

### List of relevant H phrases

H201 Explosive; mass explosion hazard.

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.



☑ Provided correct labelling of the product

☑ Compliance with the local legislation

☑ Provided correct classification of the product

☑ Provided adequate transport data

© BENS Consulting | www.bens-consulting.com

The information of this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under Section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.

Print date: 4.1.2021 Page 13 of 13