Product name: 9100 X10 System Clear

Creation date: 2.2.2011 · Revision: 3.7.2019 · Version: 1



SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name

9100 X10 System Clear

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Coating.

Uses advised against

No information.

1.3. Details of the supplier of the safety data sheet

Manufacturer

SILCO, D.O.O.

Address: Šentrupert 5 a, 3303 Gomilsko, Slovenia

Phone: +386 3 703 3180 Fax: +386 3 703 3188

E-mail: n.cvilak@silco-automotive.com Point of contact for safety info: Nejc Cvilak

1.4. Emergency telephone number

Emergency

112

Supplier

+386 3 703 3180

SECTION 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Flam. Liq. 3; H226 Flammable liquid and vapour.

STOT SE 3; H336 May cause drowsiness or dizziness.

Aquatic Chronic 3; H412 Harmful to aquatic life with long lasting effects.

chemius.net/COn72

Product name: 9100 X10 System Clear

Creation date: 2.2.2011 · Revision: 3.7.2019 · Version: 1



2.2 Label elements

2.2.1. Labelling according to Regulation (EC) No 1272/2008 [CLP]





Signal word: Warning

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains hydroxyphenyl-benzotriazole derivate I; Hydroxyphenyl-benzotriazole derivate II; Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate; Dibutyltin dilaurate; isobutyl methacrylate; bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate. May produce an allergic reaction.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P273 Avoid release to the environment.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with national regulation.

2.2.2. Contains:

n-butyl acetate (CAS: 123-86-4, EC: 204-658-1, Index: 607-025-00-1)

2.2.3. Special provisions

Special hazards are not known or expected.

2.3. Other hazards

No information.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

For mixtures see 3.2.

3.2. Mixtures

Name	CAS EC Index	%	Classification according to Regulation (EC) No 1272/2008 (CLP)	Specific Conc. Limits	REACH Registration No.
n-butyl acetate	123-86-4 204-658-1 607-025-00-1	10-30	Flam. Liq. 3; H226 STOT SE 3; H336 EUH066		-
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7	10-20	Flam. Liq. 3; H226		-
2-butoxyethyl acetate	112-07-2 203-933-3 607-038-00-2	1-5	Acute Tox. 4; H312 Acute Tox. 4; H332		-
acetone	67-64-1 200-662-2 606-001-00-8	1-2,5	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066		-
2-methylpropan-2-ol	75-65-0 200-889-7 603-005-00-1	0,1-1	Flam. Liq. 2; H225 Acute Tox. 4; H332		-

Print date: 23.8.2019 Page 2 of 13

Product name: 9100 X10 System Clear

Creation date: 2.2.2011 · Revision: 3.7.2019 · Version: 1



Name	CAS EC Index	%	Classification according to Regulation (EC) No 1272/2008 (CLP)	Specific Conc. Limits	REACH Registration No.
hydroxyphenyl-benzotriazole derivate l	104810-48-2 - -	< 1	Skin Sens. 1; H317 Aquatic Chronic 2; H411		-
Bis(1,2,2,6,6-pentamethyl-4- piperidyl) sebacate	41556-26-7 255-437-1 -	< 1	Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410		-
Hydroxyphenyl-benzotriazole derivate II	104810-47-1 -	< 1	Skin Sens. 1; H317 Aquatic Chronic 2; H411		-
Dibutyltin dilaurate	77-58-7 201-039-8 -	0,1-0,5	Skin Corr. 1B; H314 Skin Sens. 1; H317 Muta. 2; H341 Repr. 1A; H360FD STOT SE 1; H370 STOT RE 1; H372 Aquatic Acute 1; H400 Aquatic Chronic 1; H410		_
Mixture of polytiols	-	0,1-1	Acute Tox. 4; H302 Aquatic Chronic 2; H411		-
isobutyl methacrylate ^[D]	97-86-9 202-613-0 607-113-00-X	0,1-1	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Skin Sens. 1; H317 Eye Irrit. 2; H319 STOT SE 3; H335 Aquatic Acute 1; H400		-
bis(1,2,2,6,6-pentamethyl-4- piperidyl) sebacate	41556-26-7 -	0,01-0,1	Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410		-
2-hydroxyethyl methacrylate ^[D]	868-77-9 212-782-2 607-124-00-X	0,01-0,1	Skin Irrit. 2; H315 Skin Sens. 1; H317 Eye Irrit. 2; H319		-
Methyl 1,2,2,6,6-pentamethyl-4- piperidyl sebacate	82919-37-7 280-060-4 -	0,01-0,1	Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410		-
3-mercaptopropionic acid	107-96-0 203-537-0 -	<0,01	Met. Corr. 1; H290 Acute Tox. 3; H301 Skin Corr. 1A; H314 Eye Dam. 1; H318 Acute Tox. 4; H332		-

Notes for substances:

D Certain substances which are susceptible to spontaneous polymerisation or decomposition are generally placed on the market in a stabilised form. It is in this form that they are listed in Part 3.

However, such substances are sometimes placed on the market in a non-stabilised form. In this case, the supplier must state on the label the name of the substance followed by the words "non-stabilised".

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

General notes

Print date: 23.8.2019

Product name: 9100 X10 System Clear

Creation date: 2.2.2011 · Revision: 3.7.2019 · Version: 1



Following inhalation

Ventilate the premises. Inhale fresh air. Remove patient to fresh air - move out of dangerous area. Seek medical help immediately.

Following skin contact

Immediately remove contaminated clothing. Wash affected skin areas thoroughly with plenty of water and soap. If symptoms develop and persist, seek medical attention.

Following eye contact

Immediately flush eyes with plenty of water, keeping eyelids open.(for at least 10 minutes) If irritation persists, seek professional medical attention.

Following ingestion

Do not induce vomiting! Immediately consult a doctor. Rinse mouth thoroughly with water.

4.2. Most important symptoms and effects, both acute and delayed

<u>Inhalation</u>

_

Skin contact

No data available.

Eye contact

_

<u>Ingestion</u>

-

4.3. Indication of any immediate medical attention and special treatment needed

-

SECTION 5. FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media

Fire extinguishing powder.

Carbon dioxide (CO₂).

Foam.

Water spray.

Unsuitable extinguishing media

No special precautions required.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

-

5.3. Advice for firefighters

Protective actions

In case of fire or heating do not breathe fumes/vapours. Cool containers at risk with water spray. If possible remove containers from endangered area.

Special protective equipment for firefighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

Print date: 23.8.2019 Page 4 of 13

Product name: 9100 X10 System Clear

Creation date: 2.2.2011 · Revision: 3.7.2019 · Version: 1



SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment

Use personal protective equipment (Section 8).

Emergency procedures

Keep away sources of ignition.

6.1.2. For emergency responders

-

6.2. Environmental precautions

Do not allow product to reach water/drains/sewage systems and ground water. If accidental large entry into water or ground occurs, inform responsible authorities.

6.3. Methods and material for containment and cleaning up

6.3.1. For containment

_

6.3.2. For cleaning up

Absorb product (with inert material), collect it in special container and dispose it to a licensed hazardous-waste disposal contractor.

6.3.3. Other information

-

6.4. Reference to other sections

See also Sections 8 and 13.

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

7.1.1. Protective measures

Measures to prevent fire

-

Measures to prevent aerosol and dust generation

-

Measures to protect the environment

-

7.1.2. Advice on general occupational hygiene

Do not breathe vapours/mist. Consider measures required in Section 8 of this safety data sheet. Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1. Technical measures and storage conditions

Keep in cool and well ventilated area. Protect from open fire, heat and direct sunlight.

7.2.2. Packaging materials

.

7.2.3. Requirements for storage rooms and vessels

-

Print date: 23.8.2019 Page 5 of 13

Product name: 9100 X10 System Clear

Creation date: 2.2.2011 · Revision: 3.7.2019 · Version: 1



7.2.4. Storage class

-

7.2.5. Further information on storage conditions

-

7.3. Specific end use(s)

Recommendations

Keep away from incompatible material (see section 10).

Industrial sector specific solutions

-

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

8.1.1. Occupational exposure limit values

Name (CAS)	Limit values		Short-term exposure limit		Remarks	Biological Tolerance Values	
	ml/m ³ (ppm)	mg/m ³	ml/m ³ (ppm)	mg/m ³			
Acetone (67-64-1)	500	1210	1500	3620			
2-Butoxyethyl acetate (112-07-2)	20	133	50	332	Sk		
Butyl acetate (123-86-4)	150	724	200	966			
1-Methoxypropyl acetate (108-65-6)	50	274	100	548	Sk		
2-Methylpropan-2-ol (75-65-0)	100	308	150	462			

8.1.2. Information on monitoring procedures

BS EN 14042:2003 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 482:2012+A1:2015 Workplace exposure. General requirements for the performance of procedures for the measurement of chemical agents. BS EN 689:2018 Workplace exposure. Measurement of exposure by inhalation to chemical agents. Strategy for testing compliance with occupational exposure limit values.

8.1.3. DNEL/DMEL values

No information.

8.1.4. PNEC values

No information.

8.2. Exposure controls

8.2.1. Appropriate engineering control

Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration.

8.2.2. Personal protective equipment

Eye and face protection

Tight fitting protective goggles (EN 166).

Hand protection

Protective gloves (EN 374). (material: butyl-rubber) (material: nitrilerubber)

Skin protection

Cotton protective clothing and shoes that cover the entire foot (EN ISO 20345).

Respiratory protection

Wear suitable protective breathing mask (EN 136) with filter A2-P2 (EN 14387). Filter type CEN/FFP-2(S) or CEN/FFP-3(S).

Print date: 23.8.2019 Page 6 of 13

Product name: 9100 X10 System Clear

Creation date: 2.2.2011 · Revision: 3.7.2019 · Version: 1



Thermal hazards

-

8.2.3. Environmental exposure controls

_

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

-	Physical state:	liquid
-	Colour:	
-	Odour:	

Important health, safety and environmental information

рН	No information.
Melting point/freezing point	No information.
Initial boiling point/boiling range	No information.
Flash point	24 °C
Evaporation rate	No information.
Flammability (solid, gas)	No information.
Explosion limits (vol%)	No information.
Vapour pressure	No information.
Vapour density	No information.
Density	Density : 0,99 - 1,05 g/cm ³
Solubility	No information.
Partition coefficient	No information.
Auto-ignition temperature	No information.
Decomposition temperature	No information.
Viscosity	No information.
Explosive properties	No information.
Oxidising properties	No information.
	Melting point/freezing point Initial boiling point/boiling range Flash point Evaporation rate Flammability (solid, gas) Explosion limits (vol%) Vapour pressure Vapour density Density Solubility Partition coefficient Auto-ignition temperature Decomposition temperature Viscosity Explosive properties

9.2. Other information

-	Solid contents	58,8 %
-	Remarks:	

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity

-

10.2. Chemical stability

Product is stable under normal conditions of use, recommended handling and storage conditions.

10.3. Possibility of hazardous reactions

_

Print date: 23.8.2019 Page 7 of 13

Product name: 9100 X10 System Clear

Creation date: 2.2.2011 · Revision: 3.7.2019 · Version: 1



10.4. Conditions to avoid

Protect from heat, direct sunlight, open fire, sparks.

10.5. Incompatible materials

Oxidants.

Strong acids.

10.6. Hazardous decomposition products

Under normal use conditions no hazardous decomposition products are expected.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

(a) Acute toxicity

Name	Exposure route	Туре	Species	Time	Value	Method	Remark
n-butyl acetate (123-86-4)	oral	LD ₅₀	mouse		6 mg/kg		
n-butyl acetate (123-86-4)	oral	LD ₅₀	rat		10768 mg/kg		
2-methoxy-1-methylethyl acetate (108-65-6)	dermal	LD ₅₀	rat		5000 mg/kg		
2-methoxy-1-methylethyl acetate (108-65-6)	oral	LD ₅₀	rat		8532 mg/kg		
2-butoxyethyl acetate (112-07-2)	dermal	LD ₅₀	rat		1580 mg/kg		

(b) Skin corrosion/irritation

No information.

(c) Serious eye damage/irritation

No information.

(d) Respiratory or skin sensitisation

No information.

(e) (Germ cell) mutagenicity

No information.

(f) Carcinogenicity

No information.

(g) Reproductive toxicity

No information.

Summary of evaluation of the CMR properties

No information.

(h) STOT-single exposure

No information.

(i) STOT-repeated exposure

No information.

(i) Aspiration hazard

No information.

Print date: 23.8.2019 Page 8 of 13

Product name: 9100 X10 System Clear

Creation date: 2.2.2011 · Revision: 3.7.2019 · Version: 1



SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Acute (short-term) toxicity

For components

Substance (CAS Nr.)	Туре	Value	Exposure time	Species	Organism	Method	Remark
n-butyl acetate (123-86-4)	EC ₅₀	32 mg/L	48 h	crustacea			
	LC ₅₀	62 mg/L	96 h	fish			
	LC ₅₀	185 mg/L	96 h	fish			
	LC ₅₀	18 mg/L	96 h	fish			
	LC ₅₀	100 mg/L	96 h	fish			
2-methoxy-1-methylethyl acetate (108-65-6)	LC ₅₀	100 – 180 mg/L	96 h	fish			
	EC ₅₀	500 mg/L	48 h	crustacea			

12.1.2. Chronic (long-term) toxicity

No information.

12.2. Persistence and degradability

12.2.1. Abiotic degradation, physical- and photo-chemical elimination

No information.

12.2.2. Biodegradation

No information.

12.3. Bioaccumulative potential

12.3.1. Partition coefficient

No information.

12.3.2. Bioconcentration factor (BCF)

No information.

12.4. Mobility in soil

12.4.1. Known or predicted distribution to environmental compartments

No information.

12.4.2. Surface tension

No information.

12.4.3. Adsorption/Desorption

No information.

12.5. Results of PBT and vPvB assessment

No evaluation.

12.6. Other adverse effects

No information.

12.7. Additional information

For product

Do not allow to reach ground water, water courses or sewage system.

Print date: 23.8.2019 Page 9 of 13

Product name: 9100 X10 System Clear

Creation date: 2.2.2011 · Revision: 3.7.2019 · Version: 1



SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

13.1.1. Product / Packaging disposal

Waste chemical

Recycle or dispose according to official regulations: to leave it to authorized collector/remover/transformer of hazardous waste.

Packaging

Deliver completely emptied containers to approved waste disposal authorities.

13.1.2. Waste treatment-relevant information

13.1.3. Sewage disposal-relevant information

-

13.1.4. Other disposal recommendations

-

SECTION 14. TRANSPORT INFORMATION

14.1. UN number

UN 1263

14.2. UN proper shipping name

PAINT

14.3. Transport hazard class(es)

3

14.4. Packing group

Ш

14.5. Environmental hazards

NO.

14.6. Special precautions for user

Limited quantities

5 L

Tunnel restriction code

(D/E)

IMDG flashpoint

24 °C, c.c.

IMDG EmS

F-E, <u>S-E</u>

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Goods may not be carried in bulk in bulk containers, containers or vehicles.



Print date: 23.8.2019 Page 10 of 13

Product name: 9100 X10 System Clear

Creation date: 2.2.2011 · Revision: 3.7.2019 · Version: 1



SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (including last amendment Commission Regulation (EU) 2015/830)
- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

15.1.1. Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-quideline)

EU limit values and category: B(d) 420 g/l. VOC Content: 420 g/l

15.2. Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16. OTHER INFORMATION

Indication of changes

.

Abbreviations and acronyms

ATE - Acute Toxicity Estimate

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

CEN - European Committee for Standardisation

C&L - Classification and Labelling

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

CAS# - Chemical Abstracts Service number

CMR - Carcinogen, Mutagen, or Reproductive Toxicant

CSA - Chemical Safety Assessment

CSR - Chemical Safety Report

DMEL - Derived Minimal Effect Level

DNEL - Derived No Effect Level

DPD - Dangerous Preparations Directive 1999/45/EC

DSD - Dangerous Substances Directive 67/548/EEC

DU - Downstream User

EC - European Community

ECHA - European Chemicals Agency

EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS)

EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway)

EEC - European Economic Community

EINECS - European Inventory of Existing Commercial Substances

ELINCS - European List of notified Chemical Substances

EN - European Standard

EQS - Environmental Quality Standard

EU - European Union

Euphrac - European Phrase Catalogue

EWC - European Waste Catalogue (replaced by LoW - see below)

GES - Generic Exposure Scenario

GHS - Globally Harmonized System

IATA - International Air Transport Association

ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG - International Maritime Dangerous Goods

IMSBC - International Maritime Solid Bulk Cargoes

IT - Information Technology

IUCLID - International Uniform Chemical Information Database

IUPAC - International Union for Pure Applied Chemistry

JRC - Joint Research Centre

Kow - octanol-water partition coefficient

Print date: 23.8.2019 Page 11 of 13

Product name: 9100 X10 System Clear

Creation date: 2.2.2011 · Revision: 3.7.2019 · Version: 1



LC₅₀ - Lethal Concentration to 50 % of a test population

LD₅₀ - Lethal Dose to 50% of a test population (Median Lethal Dose)

LE - Legal Entity

LoW - List of Wastes (see http://ec.europa.eu/environment/waste/framework/list.htm)

LR - Lead Registrant

M/I - Manufacturer / Importer

MS - Member States

MSDS - Material Safety Data Sheet

OC - Operational Conditions

OECD - Organization for Economic Co-operation and Development

OEL - Occupational Exposure Limit

OJ - Official Journal

OR - Only Representative

OSHA - European Agency for Safety and Health at work

PBT - Persistent, Bioaccumulative and Toxic substance

PEC - Predicted Effect Concentration

PNEC(s) - Predicted No Effect Concentration(s)

PPE - Personal Protection Equipment

(Q)SAR - Qualitative Structure Activity Relationship

REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006

RID - Regulations concerning the International Carriage of Dangerous Goods by Rail

RIP - REACH Implementation Project

RMM - Risk Management Measure

SCBA - Self-Contained Breathing Apparatus

SDS - Safety data sheet

SIEF - Substance Information Exchange Forum

SME - Small and Medium sized Enterprises

STOT - Specific Target Organ Toxicity

(STOT) RE - Repeated Exposure

(STOT) SE - Single Exposure

SVHC - Substances of Very High Concern

UN - United Nations

vPvB - Very Persistent and Very Bioaccumulative

Key literature references and sources for data

-

List of relevant H phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H290 May be corrosive to metals.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H341 Suspected of causing genetic defects.

H360FD May damage fertility. May damage the unborn child.

H370 Causes damage to organs.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Print date: 23.8.2019 Page 12 of 13

Product name: 9100 X10 System Clear

Creation date: 2.2.2011 · Revision: 3.7.2019 · Version: 1





☑ Provided correct labelling of the product

☑ Provided correct classification of the product

☑ Provided adequate transport data

© BENS Consulting | www.bens-consulting.com

The information of this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under Section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.

Print date: 23.8.2019 Page 13 of 13