Product name: 9122 Hardener

Creation date: 2.2.2011 · Revision: 9.8.2019 · Version: 1



SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name

9122 Hardener

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Hardener

Uses advised against

No information.

1.3. Details of the supplier of the safety data sheet

Manufacturer

SILCO, D.O.O.

Address: Šentrupert 5 a, 3303 Gomilsko, Slovenia

Phone: +386 3 703 3180 Fax: +386 3 703 3188

E-mail: n.cvilak@silco-automotive.com Point of contact for safety info: Nejc Cvilak

1.4. Emergency telephone number

Emergency

112

Supplier

+386 3 703 3180

SECTION 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Flam. Liq. 3; H226 Flammable liquid and vapour.

Skin Sens. 1; H317 May cause an allergic skin reaction.

STOT SE 3; H336 May cause drowsiness or dizziness.

chemius.net/Al43c

Product name: 9122 Hardener

Creation date: 2.2.2011 · Revision: 9.8.2019 · Version: 1



2.2 Label elements

2.2.1. Labelling according to Regulation (EC) No 1272/2008 [CLP]





Signal word: Warning

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

P240 Ground and bond container and receiving equipment.

P272 Contaminated work clothing should not be allowed out of the workplace.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P403 + P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with national regulation.

2.2.2. Contains:

1,6-hexamethylene diisocianate homopolymer (CAS: 28182-81-2, EC: 500-060-2)

n-butyl acetate (CAS: 123-86-4, EC: 204-658-1, Index: 607-025-00-1)

2.2.3. Special provisions

Special hazards are not known or expected.

2.3. Other hazards

No information.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

For mixtures see 3.2.

Print date: 23.8.2019 Page 2 of 13

Product name: 9122 Hardener

Creation date: 2.2.2011 · Revision: 9.8.2019 · Version: 1



3.2. Mixtures

| Name | CAS EC Index | % | Classification according to Regulation (EC) No 1272/2008 (CLP) | Specific Conc. Limits | REACH Registration No. |
|--|--|-------|---|--|---------------------------|
| 1,6-hexamethylene diisocianate homopolymer | 28182-81-2 500-060-2 - | 46-60 | Skin Sens. 1; H317 | | - |
| n-butyl acetate | 123-86-4 204-658-1 607-025-00-1 | 5-40 | Flam. Liq. 3; H226 STOT SE 3; H336 EUH066 | | - |
| 2-methoxy-1-methylethyl acetate | 108-65-6 203-603-9 607-195-00-7 | 15-35 | Flam. Liq. 3; H226 | | - |
| Butylglycol acetate | 112-07-2 203-933-3 607-038-00-2 | 3-20 | Acute Tox. 4; H312 Acute Tox. 4; H332 | | - |
| p-toluenesulphonyl isocyanate | 4083-64-1 223-810-8 615-012-00-7 | <0,5 | Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 STOT SE 3; H335 EUH014 | Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 % STOT SE 3; H335: C ≥ 5 % | - |
| hexamethylene-di-isocyanate | 822-06-0 212-485-8 615-011-00-1 | <0,1 | Skin Irrit. 2; H315 Skin Sens. 1; H317 Eye Irrit. 2; H319 Acute Tox. 3; H331 Resp. Sens. 1; H334 STOT SE 3; H335 | Skin Sens. 1; H317: C ≥ 0,5 % Resp. Sens. 1; H334: C ≥ 0,5 % | - |

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

General notes

Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency.

Following inhalation

Remove patient to fresh air - move out of dangerous area. If victim is not breathing give artificial respiration. If symptoms develop and persist, seek medical attention.

Following skin contact

Immediately remove contaminated clothing. Wash affected skin areas thoroughly with plenty of water and soap. If symptoms develop and persist, seek medical attention.

Following eye contact

Immediately flush eyes with running water, keeping eyelids apart. If irritation persists, seek professional medical attention.

Following ingestion

Do not induce vomiting! Rinse mouth thoroughly with water. Immediately consult a doctor. Show the physician the safety data sheet or label.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation

Skin contact

No data available.

Print date: 23.8.2019 Page 3 of 13

Product name: 9122 Hardener

Creation date: 2.2.2011 · Revision: 9.8.2019 · Version: 1



Eye contact

-

Ingestion

-

4.3. Indication of any immediate medical attention and special treatment needed

_

SECTION 5. FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide. Dry chemical powder. Water spray. Alcohol resistant foam.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

-

5.3. Advice for firefighters

Protective actions

In case of fire or heating do not breathe fumes/vapours. Cool containers at risk with water spray. If possible remove containers from endangered area.

Special protective equipment for firefighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment

Use personal protective equipment (Section 8).

Emergency procedures

Ensure adequate ventilation. Keep away from sources of ignition and/or heat; No smoking!

6.1.2. For emergency responders

_

6.2. Environmental precautions

Do not allow product to reach water/drains/sewage systems or permeable soil. If accidental large entry into water or ground occurs, inform responsible authorities.

6.3. Methods and material for containment and cleaning up

6.3.1. For containment

_

6.3.2. For cleaning up

Absorb product (with inert material), collect it in special container and dispose it to a licensed hazardous-waste disposal contractor.

Print date: 23.8.2019 Page 4 of 13

Product name: 9122 Hardener

Creation date: 2.2.2011 · Revision: 9.8.2019 · Version: 1



6.3.3. Other information

-

6.4. Reference to other sections

See also Sections 8 and 13.

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

7.1.1. Protective measures

Measures to prevent fire

Ensure adequate ventilation. Keep away from sources of ignition - no smoking. Use spark-proof tools. Take precautionary measures against static discharges.

Measures to prevent aerosol and dust generation

-

Measures to protect the environment

-

7.1.2. Advice on general occupational hygiene

Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Avoid contact with skin and eyes. Do not breathe vapours/mist.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1. Technical measures and storage conditions

Keep in cool and well ventilated area. Protect from open fire, heat and direct sunlight. Keep away from food, drink and animal feeding stuffs.

7.2.2. Packaging materials

-

7.2.3. Requirements for storage rooms and vessels

-

7.2.4. Storage class

_

7.2.5. Further information on storage conditions

-

7.3. Specific end use(s)

Recommendations

-

Industrial sector specific solutions

-

Print date: 23.8.2019 Page 5 of 13

Product name: 9122 Hardener

Creation date: 2.2.2011 · Revision: 9.8.2019 · Version: 1



SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

8.1.1. Occupational exposure limit values

| , | | alues | Short-term exposure limit | | Remarks | Biological Tolerance Values |
|------------------------------------|-----|-------------------|----------------------------|-------------------|---------|-----------------------------|
| | | mg/m ³ | ml/m ³ (ppm) | mg/m ³ | | |
| 2-Butoxyethyl acetate (112-07-2) | 20 | 133 | 50 | 332 | Sk | |
| Butyl acetate (123-86-4) | 150 | 724 | 200 | 966 | | |
| 1-Methoxypropyl acetate (108-65-6) | 50 | 274 | 100 | 548 | Sk | |

8.1.2. Information on monitoring procedures

BS EN 14042:2003 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 482:2012+A1:2015 Workplace exposure. General requirements for the performance of procedures for the measurement of chemical agents. BS EN 689:2018 Workplace exposure. Measurement of exposure by inhalation to chemical agents. Strategy for testing compliance with occupational exposure limit values.

8.1.3. DNEL/DMEL values

No information.

8.1.4. PNEC values

No information.

8.2. Exposure controls

8.2.1. Appropriate engineering control

Substance/mixture related measures to prevent exposure during identified uses

Use good personal hygiene practices - wash hands at breaks and when done working with material.

Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration.

8.2.2. Personal protective equipment

Eye and face protection

Tight fitting protective goggles (EN 166).

Hand protection

Protective gloves (EN 374).

Skin protection

Cotton protective clothing and shoes that cover the entire foot (EN ISO 20345).

Respiratory protection

Wear suitable protective breathing mask (EN 136) with filter A2-P2 (EN 14387).

Thermal hazards

-

8.2.3. Environmental exposure controls

-

Print date: 23.8.2019 Page 6 of 13

Product name: 9122 Hardener

Creation date: 2.2.2011 · Revision: 9.8.2019 · Version: 1



SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

| - | Physical state: | liquid |
|---|-----------------|--------------|
| - | Colour: | colourless |
| - | Odour: | solvent like |

Important health, safety and environmental information

| - | рН | No information. |
|---|-------------------------------------|--|
| - | Melting point/freezing point | No information. |
| - | Initial boiling point/boiling range | No information. |
| - | Flash point | 28 °C |
| - | Evaporation rate | No information. |
| - | Flammability (solid, gas) | No information. |
| - | Explosion limits (vol%) | No information. |
| - | Vapour pressure | No information. |
| - | Vapour density | No information. |
| - | Density | Density : 0,99 – 1,05 g/cm ³ |
| - | Solubility | No information. |
| - | Partition coefficient | No information. |
| - | Auto-ignition temperature | No information. |
| - | Decomposition temperature | No information. |
| - | Viscosity | No information. |
| - | Explosive properties | No information. |
| - | Oxidising properties | No information. |

9.2. Other information

| - | Solid contents | 50,8 % |
|---|----------------|--------|
| - | Remarks: | |

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity

-

10.2. Chemical stability

Product is stable under normal conditions of use, recommended handling and storage conditions.

10.3. Possibility of hazardous reactions

-

10.4. Conditions to avoid

No special precautions required. Consider the directions for use and storage.

Print date: 23.8.2019 Page 7 of 13

Product name: 9122 Hardener

Creation date: 2.2.2011 · Revision: 9.8.2019 · Version: 1



10.5. Incompatible materials

Oxidants.
Strong bases.
Strong acids. Water.
Alcohols.

10.6. Hazardous decomposition products

Under normal use conditions no hazardous decomposition products are expected. In case of fire/explosion vapours/gases that pose a health hazard are released. Carbon dioxide; Carbon monoxide. Hydrogen cyanide.

Nitrogen oxides.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

(a) Acute toxicity

| Name | Exposure route | Туре | Species | Time | Value | Method | Remark |
|--|----------------|------------------|---------|------|-------------|--------|--------|
| n-butyl acetate (123-86-4) | oral | LD ₅₀ | mouse | | 6 mg/kg | | |
| n-butyl acetate (123-86-4) | oral | LD ₅₀ | rat | | 10768 mg/kg | | |
| 2-methoxy-1-methylethyl acetate (108-65-6) | dermal | LD ₅₀ | rat | | 5000 mg/kg | | |
| 2-methoxy-1-methylethyl acetate (108-65-6) | oral | LD ₅₀ | rat | | 8532 mg/kg | | |

(b) Skin corrosion/irritation

No information.

(c) Serious eye damage/irritation

No information.

(d) Respiratory or skin sensitisation

Additional information: May cause an allergic skin reaction.

(e) (Germ cell) mutagenicity

No information.

(f) Carcinogenicity

No information.

(g) Reproductive toxicity

No information.

Summary of evaluation of the CMR properties

No information.

(h) STOT-single exposure

No information.

(i) STOT-repeated exposure

No information.

(i) Aspiration hazard

No information.

Print date: 23.8.2019 Page 8 of 13

Product name: 9122 Hardener

Creation date: 2.2.2011 · Revision: 9.8.2019 · Version: 1



SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Acute (short-term) toxicity

For components

| Substance (CAS Nr.) | Туре | Value | Exposure time | Species | Organism | Method | Remark |
|--|------------------|----------------|---------------|-----------|----------|--------|--------|
| n-butyl acetate (123-86-4) | EC ₅₀ | 32 mg/L | 48 h | crustacea | | | |
| | LC ₅₀ | 18 – 19 mg/L | 96 h | fish | | | |
| | LC ₅₀ | 62 mg/L | 96 h | fish | | | |
| | LC ₅₀ | 185 mg/L | 96 h | fish | | | |
| | LC ₅₀ | 18 mg/L | 96 h | fish | | | |
| | LC ₅₀ | 100 mg/L | 96 h | fish | | | |
| 2-methoxy-1-methylethyl acetate (108-65-6) | LC ₅₀ | 100 – 180 mg/L | 96 h | fish | | | |
| | EC ₅₀ | 500 mg/L | 48 h | crustacea | | | |

12.1.2. Chronic (long-term) toxicity

No information.

12.2. Persistence and degradability

12.2.1. Abiotic degradation, physical- and photo-chemical elimination

No information.

12.2.2. Biodegradation

No information.

12.3. Bioaccumulative potential

12.3.1. Partition coefficient

No information.

12.3.2. Bioconcentration factor (BCF)

No information.

12.4. Mobility in soil

12.4.1. Known or predicted distribution to environmental compartments

No information.

12.4.2. Surface tension

No information.

12.4.3. Adsorption/Desorption

No information.

12.5. Results of PBT and vPvB assessment

No evaluation.

12.6. Other adverse effects

No information.

12.7. Additional information

For product

Do not allow to reach ground water, water courses or sewage system.

Print date: 23.8.2019 Page 9 of 13

Product name: 9122 Hardener

Creation date: 2.2.2011 · Revision: 9.8.2019 · Version: 1



SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

13.1.1. Product / Packaging disposal

Waste chemical

Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste.

Packaging

Completely emptied and cleaned containers leave to approved waste disposal authorities in charge.

13.1.2. Waste treatment-relevant information

-

13.1.3. Sewage disposal-relevant information

-

13.1.4. Other disposal recommendations

-

SECTION 14. TRANSPORT INFORMATION

14.1. UN number

UN 1263

14.2. UN proper shipping name

PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

3

14.4. Packing group

Ш

14.5. Environmental hazards

NO.

14.6. Special precautions for user

Limited quantities

5 L

Tunnel restriction code

(D/E)

IMDG flashpoint

28 °C, c.c.

IMDG EmS

F-E, <u>S-E</u>

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Goods may not be carried in bulk in bulk containers, containers or vehicles.



Print date: 23.8.2019 Page 10 of 13

Product name: 9122 Hardener

Creation date: 2.2.2011 · Revision: 9.8.2019 · Version: 1



SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (including last amendment Commission Regulation (EU) 2015/830)
- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

15.1.1. Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-quideline)

Not applicable.

15.2. Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16. OTHER INFORMATION

Indication of changes

.

Abbreviations and acronyms

ATE - Acute Toxicity Estimate

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

CEN - European Committee for Standardisation

C&L - Classification and Labelling

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

CAS# - Chemical Abstracts Service number

CMR - Carcinogen, Mutagen, or Reproductive Toxicant

CSA - Chemical Safety Assessment

CSR - Chemical Safety Report

DMEL - Derived Minimal Effect Level

DNEL - Derived No Effect Level

DPD - Dangerous Preparations Directive 1999/45/EC

DSD - Dangerous Substances Directive 67/548/EEC

DU - Downstream User

EC - European Community

ECHA - European Chemicals Agency

EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS)

EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway)

EEC - European Economic Community

EINECS - European Inventory of Existing Commercial Substances

ELINCS - European List of notified Chemical Substances

EN - European Standard

EQS - Environmental Quality Standard

EU - European Union

Euphrac - European Phrase Catalogue

EWC - European Waste Catalogue (replaced by LoW - see below)

GES - Generic Exposure Scenario

GHS - Globally Harmonized System

IATA - International Air Transport Association

ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG - International Maritime Dangerous Goods

IMSBC - International Maritime Solid Bulk Cargoes

IT - Information Technology

IUCLID - International Uniform Chemical Information Database

IUPAC - International Union for Pure Applied Chemistry

JRC - Joint Research Centre

Kow - octanol-water partition coefficient

Print date: 23.8.2019 Page 11 of 13

Product name: 9122 Hardener

Creation date: 2.2.2011 · Revision: 9.8.2019 · Version: 1



 ${\rm LC}_{50}$ - Lethal Concentration to 50 % of a test population

LD₅₀ - Lethal Dose to 50% of a test population (Median Lethal Dose)

LE - Legal Entity

LoW - List of Wastes (see http://ec.europa.eu/environment/waste/framework/list.htm)

LR - Lead Registrant

M/I - Manufacturer / Importer

MS - Member States

MSDS - Material Safety Data Sheet

OC - Operational Conditions

OECD - Organization for Economic Co-operation and Development

OEL - Occupational Exposure Limit

OJ - Official Journal

OR - Only Representative

OSHA - European Agency for Safety and Health at work

PBT - Persistent, Bioaccumulative and Toxic substance

PEC - Predicted Effect Concentration

PNEC(s) - Predicted No Effect Concentration(s)

PPE - Personal Protection Equipment

(Q)SAR - Qualitative Structure Activity Relationship

REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006

RID - Regulations concerning the International Carriage of Dangerous Goods by Rail

RIP - REACH Implementation Project

RMM - Risk Management Measure

SCBA - Self-Contained Breathing Apparatus

SDS - Safety data sheet

SIEF - Substance Information Exchange Forum

SME - Small and Medium sized Enterprises

STOT - Specific Target Organ Toxicity

(STOT) RE - Repeated Exposure

(STOT) SE - Single Exposure

SVHC - Substances of Very High Concern

UN - United Nations

vPvB - Very Persistent and Very Bioaccumulative

Key literature references and sources for data

-

List of relevant H phrases

H226 Flammable liquid and vapour.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

EUH014 Reacts violently with water.

EUH066 Repeated exposure may cause skin dryness or cracking.



☑ Provided correct labelling of the product

☑ Provided correct classification of the product

☑ Provided adequate transport data

© BENS Consulting | www.bens-consulting.com

Print date: 23.8.2019 Page 12 of 13

Product name: 9122 Hardener

Creation date: 2.2.2011 · Revision: 9.8.2019 · Version: 1



The information of this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under Section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.

Print date: 23.8.2019 Page 13 of 13