Product name: 9500 Maxx Matt™ Creation date: 8.4.2011 · Revision: 3.7.2019 · Version: 1

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name

9500 Maxx Matt™

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

clear coat

Uses advised against

No information.

1.3. Details of the supplier of the safety data sheet

Manufacturer

SILCO, D.O.O. Address: Šentrupert 5 a, 3303 Gomilsko, Slovenia Phone: +386 3 703 3180 Fax: +386 3 703 3188 E-mail: n.cvilak@silco-automotive.com Point of contact for safety info: Nejc Cvilak

1.4. Emergency telephone number

Emergency

112

<u>Supplier</u>

+386 3 703 3180

SECTION 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Flam. Liq. 3; H226 Flammable liquid and vapour. Acute Tox. 4; H312 Harmful in contact with skin. Acute Tox. 4; H332 Harmful if inhaled. Aquatic Chronic 3; H412 Harmful to aquatic life with long lasting effects.



chemius.net/tlD01



Product name: 9500 Maxx Matt™ Creation date: 8.4.2011 · Revision: 3.7.2019 · Version: 1



2.2 Label elements

2.2.1. Labelling according to Regulation (EC) No 1272/2008 [CLP]



Signal word: Warning

- H226 Flammable liquid and vapour.
- H312 Harmful in contact with skin.
- H332 Harmful if inhaled.
- H412 Harmful to aquatic life with long lasting effects.
- P240 Ground and bond container and receiving equipment.
- P273 Avoid release to the environment.
- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P403 + P235 Store in a well-ventilated place. Keep cool.
- P501 Dispose of contents/container in accordance with national regulation.

2.2.2. Contains:

xylene (CAS: 1330-20-7, EC: 215-535-7, Index: 601-022-00-9)

2.2.3. Special provisions

Special hazards are not known or expected.

2.3. Other hazards

No information.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

For mixtures see 3.2.



3.2. Mixtures

Name	CAS EC Index	%	Classification according to Regulation (EC) No 1272/2008 (CLP)	Specific Conc. Limits	REACH Registration No.
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7	20-25	Flam. Liq. 3; H226		-
xylene ^[C]	1330-20-7 215-535-7 601-022-00-9	15-20	Flam. Liq. 3; H226 Acute Tox. 4; H312 Skin Irrit. 2; H315 Acute Tox. 4; H332		-
Solvent naphtha (petroleum), light arom [P]	64742-95-6 265-199-0 649-356-00-4	5-7	Flam. Liq. 1; H224 Asp. Tox. 1; H304 STOT SE 3; H336 Aquatic Chronic 2; H411 EUH066		-
n-butyl acetate	123-86-4 204-658-1 607-025-00-1	5-7	Flam. Liq. 3; H226 STOT SE 3; H336 EUH066		-
2-butoxyethyl acetate	112-07-2 203-933-3 607-038-00-2	3-5	Acute Tox. 4; H312 Acute Tox. 4; H332		-
ethylbenzene	100-41-4 202-849-4 601-023-00-4	0,25-0,50	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Acute Tox. 4; H332 STOT RE 2; H373 (hearing organs)		-

Notes for substances:

C Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers.

In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

P The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7).

When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 (Table 3.1) or the S-phrases (2-)23-24-62 (Table 3.2) shall apply.

This note applies only to certain complex oil-derived substances in Part 3.

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

General notes

Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency.

Following inhalation

Remove patient to fresh air - move out of dangerous area. If victim is not breathing give artificial respiration. If symptoms develop and persist, seek medical attention.

Following skin contact

Take off all contaminated clothing. Wash affected skin areas thoroughly with plenty of water and soap. If symptoms develop and persist, seek medical attention.

Following eye contact

Immediately flush eyes with running water, keeping eyelids apart. If irritation persists, seek professional medical attention.

Product name: 9500 Maxx Matt™ Creation date: 8.4.2011 · Revision: 3.7.2019 · Version: 1



Following ingestion

Rinse mouth thoroughly with water. Do not induce vomiting! Immediately consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation

Harmful.

Skin contact

Harmful.

Prolonged and repeated exposure may cause redness, itching and cracking of the skin in sensitive people.

Eye contact

Ingestion

-

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5. FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide. Dry chemical powder. Water spray. Alcohol resistant foam.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

5.3. Advice for firefighters

Protective actions

In case of fire or heating do not breathe fumes/vapours. Cool containers at risk with water spray. If possible remove containers from endangered area.

Special protective equipment for firefighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment

Use personal protective equipment (Section 8).

Emergency procedures

Ensure adequate ventilation. Keep away from sources of ignition and/or heat; No smoking!

6.1.2. For emergency responders

Print date: 23.8.2019

Product name: 9500 Maxx Matt[™] Creation date: 8.4.2011 · Revision: 3.7.2019 · Version: 1



6.2. Environmental precautions

Do not allow product to reach water/drains/sewage systems or permeable soil. If accidental large entry into water or ground occurs, inform responsible authorities.

6.3. Methods and material for containment and cleaning up

6.3.1. For containment

6.3.2. For cleaning up

Absorb product (with inert material), collect it in special container and dispose it to a licensed hazardous-waste disposal contractor.

6.3.3. Other information

-

6.4. Reference to other sections

See also Sections 8 and 13.

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

7.1.1. Protective measures

Measures to prevent fire

Ensure adequate ventilation. Keep away from sources of ignition - no smoking.

Measures to prevent aerosol and dust generation

Measures to protect the environment

-

7.1.2. Advice on general occupational hygiene

Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Avoid contact with skin and eyes. Do not breathe vapours/mist.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1. Technical measures and storage conditions

Keep in cool and well ventilated area. Protect from open fire, heat and direct sunlight. Keep away from food, drink and animal feeding stuffs.

7.2.2. Packaging materials

7.2.3. Requirements for storage rooms and vessels

7.2.4. Storage class

7.2.5. Further information on storage conditions

7.3. Specific end use(s)

Recommendations

Industrial sector specific solutions



SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

8.1.1. Occupational exposure limit values

Name (CAS)			Short-term exposure limit		Remarks	Biological Tolerance Values
	ml/m ³ (ppm)	mg/m ³	ml/m ³ (ppm)	mg/m ³		
2-Butoxyethyl acetate (112-07-2)	20	133	50	332	Sk	
Butyl acetate (123-86-4)	150	724	200	966		
Ethylbenzene (100-41-4)	100	441	125	552	Sk	
1-Methoxypropyl acetate (108-65- 6)	50	274	100	548	Sk	
Xylene, o-,m-,p- or mixed isomers (1330-20-7)	50	220	100	441	Sk, BMGV	650 mmol methyl hippuric acid/mol creatinine in urine - Post shift

8.1.2. Information on monitoring procedures

BS EN 14042:2003 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 482:2012+A1:2015 Workplace exposure. General requirements for the performance of procedures for the measurement of chemical agents. BS EN 689:2018 Workplace exposure. Measurement of exposure by inhalation to chemical agents. Strategy for testing compliance with occupational exposure limit values.

8.1.3. DNEL/DMEL values

No information.

8.1.4. PNEC values

No information.

8.2. Exposure controls

8.2.1. Appropriate engineering control

Substance/mixture related measures to prevent exposure during identified uses

Use good personal hygiene practices - wash hands at breaks and when done working with material.

Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration.

8.2.2. Personal protective equipment

Eye and face protection

Tight fitting protective goggles (EN 166).

Hand protection

Protective gloves (EN 374).

Appropriate materials

Material	Thickness	Penetration Time	Remark
Butyl rubber			
Nitrile			
PVC			

Skin protection

Cotton protective clothing and shoes that cover the entire foot (EN ISO 20345).

Product name: 9500 Maxx Matt™

Creation date: $\textbf{8.4.2011} \cdot \text{Revision: } \textbf{3.7.2019} \cdot \text{Version: } \textbf{1}$



Respiratory protection

In case of insufficient ventilation wear suitable respiratory protection. Wear suitable protective breathing mask (EN 136) with filter A2-P2 (EN 14387).

Thermal hazards

8.2.3. Environmental exposure controls

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

-	Physical state:	liquid
-	Colour:	colourless
-	Odour:	characteristic

Important health, safety and environmental information

-	рН	No information.
-	Melting point/freezing point	No information.
-	Initial boiling point/boiling range	> 35 °C
-	Flash point	> 23 °C
-	Evaporation rate	No information.
-	Flammability (solid, gas)	400 °C
-	Explosion limits (vol%)	2 – 11 vol %
-	Vapour pressure	No information.
-	Vapour density	No information.
-	Density	No information.
-	Solubility	No information.
-	Partition coefficient	No information.
-	Auto-ignition temperature	No information.
-	Decomposition temperature	No information.
-	Viscosity	No information.
-	Explosive properties	No information.
-	Oxidising properties	No information.

9.2. Other information

-	Weight organic solvents	34,69 %
-	Solid contents	50,56 %
-	Remarks:	

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity

10.2. Chemical stability

Product is stable under normal conditions of use, recommended handling and storage conditions.

Product name: 9500 Maxx Matt™ Creation date: 8.4.2011 · Revision: 3.7.2019 · Version: 1



10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

No special precautions required. Consider the directions for use and storage.

10.5. Incompatible materials

Oxidants.

10.6. Hazardous decomposition products

Under normal use conditions no hazardous decomposition products are expected. In case of fire/explosion vapours/gases that pose a health hazard are released.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

(a) Acute toxicity

Name	Exposure route	Туре	Species	Time	Value	Method	Remark
2-methoxy-1-methylethyl acetate (108-65-6)	dermal	LD_{50}	rat		5000 mg/kg		
2-methoxy-1-methylethyl acetate (108-65-6)	oral	LD_{50}	rat		8532 mg/kg		
xylene (1330-20-7)	oral	LD_{50}	rat		930 mg/kg		
n-butyl acetate (123-86-4)	oral	LD_{50}	mouse		6 mg/kg		
n-butyl acetate (123-86-4)	oral	LD_{50}	rat		10768 mg/kg		
2-butoxyethyl acetate (112-07-2)	dermal	LD_{50}	rat		1580 mg/kg		
ethylbenzene (100-41-4)	oral	LD_{50}	rat		4710 mg/kg		
ethylbenzene (100-41-4)	oral	LD_{50}	rat		3500 mg/kg		

(b) Skin corrosion/irritation

Name	Species	Time	Result	Method	Remark
xylene (1330-20-7)			Irritating.		
n-butyl acetate (123-86-4)			Irritating.		
2-butoxyethyl acetate (112-07-2)			Prolonged and repeated contact can cause dermatitis.		

(c) Serious eye damage/irritation

Name	Species	Time	Result	Method	Remark
2-methoxy-1-methylethyl acetate (108-65-6)			May cause irritation.		
xylene (1330-20-7)			Irritating.		
n-butyl acetate (123-86-4)			Irritating.		

(d) Respiratory or skin sensitisation

No information.

(e) (Germ cell) mutagenicity

No information.

(f) Carcinogenicity

No information.

(g) Reproductive toxicity

No information.

Product name: 9500 Maxx Matt™

Creation date: 8.4.2011 · Revision: 3.7.2019 · Version: 1



Summary of evaluation of the CMR properties

No information.

(h) STOT-single exposure

Name	Exposure route	Туре	Species	Time	Organ	Value	Result	Method	Remark
xylene (1330-20-7)	inhalation						Irritates respiratory system.		
n-butyl acetate (123-86-4)	inhalation						Irritates respiratory system.		
ethylbenzene (100-41-4)	inhalation						Harmful by inhalation.		

(i) STOT-repeated exposure

No information.

(j) Aspiration hazard

No information.

SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Acute (short-term) toxicity

For components

Substance (CAS Nr.)	Туре	Value	Exposure time	Species	Organism	Method	Remark
2-methoxy-1-methylethyl acetate (108-65-6)	LC_{50}	100 – 180 mg/L	96 h	fish			
	EC_{50}	500 mg/L	48 h	crustacea			
xylene (1330-20-7)	EC_{50}	7,4 mg/L	48 h	crustacea			
n-butyl acetate (123-86-4)	EC_{50}	32 mg/L	48 h	crustacea			
	LC_{50}	18 mg/L	96 h	fish			
ethylbenzene (100-41-4)	EC_{50}	33 mg/L	72 h	algae			
	LC_{50}	12 mg/L	96 h	fish			

12.1.2. Chronic (long-term) toxicity

No information.

12.2. Persistence and degradability

12.2.1. Abiotic degradation, physical- and photo-chemical elimination

No information.

12.2.2. Biodegradation

For components

Substance (CAS Nr.)	Туре	Rate	Time	Evaluation	Method	Remark
ethylbenzene (100-41-4)	aerobic				OECD 301 A (Modified AFNOR Test)	

12.3. Bioaccumulative potential

12.3.1. Partition coefficient

No information.

12.3.2. Bioconcentration factor (BCF)

No information.

12.4. Mobility in soil

12.4.1. Known or predicted distribution to environmental compartments

No information.

Product name: 9500 Maxx Matt[™] Creation date: 8.4.2011 · Revision: 3.7.2019 · Version: 1



12.4.2. Surface tension

No information.

12.4.3. Adsorption/Desorption

No information.

12.5. Results of PBT and vPvB assessment

No evaluation.

12.6. Other adverse effects

No information.

12.7. Additional information

For product

Do not allow to reach ground water, water courses or sewage system. Harmful to aquatic organisms. May cause long term adverse effects in the aquatic environment.

For components

Substance: n-butyl acetate

Water hazard class 1 (Self-assessment): slightly hazardous for water

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

13.1.1. Product / Packaging disposal

Waste chemical

Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste.

Packaging

Deliver completely emptied containers to approved waste disposal authorities.

13.1.2. Waste treatment-relevant information

-

13.1.3. Sewage disposal-relevant information

-

13.1.4. Other disposal recommendations

SECTION 14. TRANSPORT INFORMATION

14.1. UN number

UN 1263

14.2. UN proper shipping name

PAINT

14.3. Transport hazard class(es)

3

14.4. Packing group

III

14.5. Environmental hazards

NO.



Product name: 9500 Maxx Matt[™] Creation date: 8.4.2011 · Revision: 3.7.2019 · Version: 1



14.6. Special precautions for user

Limited quantities

5 L

Tunnel restriction code

(D/E)

IMDG flashpoint

23 °C, c.c.

IMDG EmS

F-E, <u>S-E</u>

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Goods may not be carried in bulk in bulk containers, containers or vehicles.

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (including last amendment Commission Regulation (EU) 2015/830)

- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

<u>15.1.1. Information according 2004/42/EC about limitation of emissions of volatile organic compounds</u> (VOC-guideline)

Not applicable.

15.2. Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16. OTHER INFORMATION

Indication of changes

Abbreviations and acronyms

- ATE Acute Toxicity Estimate
- ADR European Agreement concerning the International Carriage of Dangerous Goods by Road
- ADN European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
- CEN European Committee for Standardisation
- C&L Classification and Labelling
- CLP Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
- CAS# Chemical Abstracts Service number
- CMR Carcinogen, Mutagen, or Reproductive Toxicant
- CSA Chemical Safety Assessment
- CSR Chemical Safety Report
- DMEL Derived Minimal Effect Level
- DNEL Derived No Effect Level
- DPD Dangerous Preparations Directive 1999/45/EC
- DSD Dangerous Substances Directive 67/548/EEC
- DU Downstream User
- EC European Community
- ECHA European Chemicals Agency
- EC-Number EINECS and ELINCS Number (see also EINECS and ELINCS)

EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway)

EEC - European Economic Community

EINECS - European Inventory of Existing Commercial Substances

ELINCS - European List of notified Chemical Substances

Product name: 9500 Maxx Matt[™] Creation date: 8.4.2011 · Revision: 3.7.2019 · Version: 1



EN - European Standard EQS - Environmental Quality Standard EU - European Union Euphrac - European Phrase Catalogue EWC - European Waste Catalogue (replaced by LoW - see below) GES - Generic Exposure Scenario GHS - Globally Harmonized System IATA - International Air Transport Association ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air IMDG - International Maritime Dangerous Goods IMSBC - International Maritime Solid Bulk Cargoes IT - Information Technology IUCLID - International Uniform Chemical Information Database IUPAC - International Union for Pure Applied Chemistry JRC - Joint Research Centre Kow - octanol-water partition coefficient LC₅₀ - Lethal Concentration to 50 % of a test population LD₅₀ - Lethal Dose to 50% of a test population (Median Lethal Dose) LE - Legal Entity LoW - List of Wastes (see http://ec.europa.eu/environment/waste/framework/list.htm) LR - Lead Registrant M/I - Manufacturer / Importer MS - Member States MSDS - Material Safety Data Sheet **OC** - Operational Conditions OECD - Organization for Economic Co-operation and Development **OEL - Occupational Exposure Limit** OJ - Official Journal **OR** - Only Representative OSHA - European Agency for Safety and Health at work PBT - Persistent, Bioaccumulative and Toxic substance PEC - Predicted Effect Concentration PNEC(s) - Predicted No Effect Concentration(s) PPE - Personal Protection Equipment (Q)SAR - Qualitative Structure Activity Relationship REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006 RID - Regulations concerning the International Carriage of Dangerous Goods by Rail **RIP - REACH Implementation Project** RMM - Risk Management Measure SCBA - Self-Contained Breathing Apparatus SDS - Safety data sheet SIEF - Substance Information Exchange Forum SME - Small and Medium sized Enterprises STOT - Specific Target Organ Toxicity (STOT) RE - Repeated Exposure (STOT) SE - Single Exposure SVHC - Substances of Very High Concern **UN - United Nations** vPvB - Very Persistent and Very Bioaccumulative Key literature references and sources for data

Product name: 9500 Maxx Matt™


Creation date: 8.4.2011 · Revision: 3.7.2019 · Version: 1



List of relevant H phrases

- H224 Extremely flammable liquid and vapour.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure .
- H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.



The information of this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under Section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.