

Description

High quality, antisilicone degreaser for degreasing and cleaning of surfaces before painting. Effective removal of residual grease, oil, wax, silicones, etc.


Cleaning and degreasing of:

- bare steel, aluminium, zinc-coated steel
- plastic parts, primers, surfacers and fillers
- all kinds of existing coatings

Substrate preparation

Surfaces to be treated must be clean and dry.

Application data



Mixing ratio

The product is ready to use!

Apply the 9515 degreaser using a sprayer or with a cloth. Clean the entire surface.
Use a second dry cloth and make sure you wipe the surface until it is dry.

Prod. Nr.	Description	Volume	Packaging Box
9515-1	/	1 L	6
9515-5	/	5 L	3

VOC

VOC 2004/42/IIIB(a) (850) <850

Shelf life

Min. 36 months from the production date under normal storage conditions and unopened can.

Additional Information

FOR PROFESSIONAL USE ONLY!

Always read the instructions.

IMPORTANT: This product contains hazardous substances at work so it is necessary to always use/wear appropriate protective equipment. For further instructions, check the label on the product and safety data sheet. A person who uses the product for any purpose other than recommended in this technical data sheet, acts at his own risk. It is the user's responsibility to take all necessary steps to fulfil the local legislation.

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public.

Information and methods described are based on the best information and practices known to us and serve merely as guidelines for optimal use, without liability to performance, results or fitness for any intended use. We do not accept any responsibility for the behaviour of the product or damage arising from the use of the product. Before using the product, the user must check if this is the latest version.

All products mentioned in this data sheet are trademarks owned by Silco.