

### Description

Pre-fill for solvent based coatings with 275 ml of propellant, solvent and additives with capacity of 100 ml of paint.


### Features & Benefits

Spray can pre-filled with suitable propellant and thinner for filling with paint.  
With special aerosol head for paint application.

### Substrate preparation


Are must be clean, dry and free of grease and dust.

### Application data



#### Mixing ratio

The product is ready for use!  
Amount of propellant: 275 ml of propellant  
Suitable for 100 ml of paint



#### Application

Shake the aerosol before use for 2 minutes.  
Aerosol pressure: 3,5 bar at 20 °C/68 °F.  
Spraying distance: 15 – 20 cm  
Spray several thin coats at the recommended distance.

**Important:** the thinner the paint coat is applied, the better is the temperature-resistance and adhesion. No primer needed. The best results is achieved at the application on bare metal! It is strongly recommended that ready for use product is applied at a temperature higher than 15 °C/59 °F.

Slight colour differences may occur.

After spraying turn the can upside down and spray until the valve is clean.



#### Drying

In the case of forced drying drying time depends on used quality of paint.  
Recoatible with 1K or 2K clear coats.

Prod. Nr.	Description	Volume	Packaging Box
9584	Pre-fill	400 ml	12

### VOC

VOC 2004/42/IIB (840) <780

### Shelf life

Min. 24 months from the production date under normal storage conditions and unopened can.

### Additional Information

#### FOR PROFESSIONAL USE ONLY!

Always read the instructions.

**IMPORTANT:** This product contains hazardous substances at work so it is necessary to always use/wear appropriate protective equipment. For further instructions, check the label on the product and safety data sheet. A person who uses the product for any purpose other than recommended in this technical data sheet, acts at his own risk. It is the user's responsibility to take all necessary steps to fulfil the local legislation.

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public.

Information and methods described are based on the best information and practices known to us and serve merely as guidelines for optimal use, without liability to performance, results or fitness for any intended use. We do not accept any responsibility for the behaviour of the product or damage arising from the use of the product. Before using the product, the user must check if this is the latest version.

All products mentioned in this data sheet are trademarks owned by Silco.